Deployment and Repository Evidence Register

Status: public app URL and Sepolia contract now observed; authenticated acceptance and v2.1 redeployment still pending.

Public identifiers

Required item	Recorded value / status
GitHub repository URL	Not available; workspace has no Git metadata
Source commit / release tag	Not available; do not invent history
Render public deployment URL	https://saving-sepolia.onrender.com — public health/config checked, version 2.0.0; v2.1 update pending
Sepolia contract address	0xC2609E2Ce2E231E3c90DCb6e84C68988f93df3a5 — code/rate/deposit receipt checked
Deployment transaction hash	Not available
Deployer wallet address	Not recorded
Explorer source verification URL	Not available
Demo video URL or live-demo record	Not recorded; timed script supplied

Known reproducible configuration

Chain ID: 11155111 (Sepolia). Solidity: 0.8.30. EVM target: Shanghai. Optimizer: enabled, 200 runs. Constructor: annualRateBps, default 500. Contract: Savings, in contract/Savings.sol. The deployer's address becomes immutable owner. New contracts added to meet the brief require an updated deployment record.

Runtime: Docker, Python 3.12/FastAPI/Uvicorn backend, Node 24 Next.js standalone frontend, API port 4000 behind web port 10000, SQLite at /app/data/saving.sqlite. Render Blueprint: render.yaml, starter plan and a 1 GB disk. Required service secrets: SEPOLIA_RPC_URL, ADMIN_REGISTRATION_CODE and AUDITOR_REGISTRATION_CODE; required public configuration: CONTRACT_ADDRESS. The deployment key belongs only in the contract deployment environment, never the hosted web app.

Publication procedure

1. Review the agreed relaxed scope in docs/SCOPE.md and the original-brief comparison. Run python3 scripts/collect-evidence.py and regenerate the documents after material changes.

2. Create an actual repository and genuine commits. Follow .gitignore. Verify .env files, signing keys, database files and node_modules are excluded. The source ZIP is a reviewable snapshot, not a hosted repository.

3. Publish to a GitHub repository under your account. Record its URL and actual source commit. No authorised account/session is available here to publish on your behalf.

4. Set testnet-only deployment credentials in contract/.env; run cd contract && npm run deploy. Save the printed address and obtain the deployment hash from the deployment wallet or explorer. Verify

compiler/arguments when publishing contract source to the explorer.

5. Create a Render Blueprint from the repository, enter RPC and contract values, and deploy. Retrieve the generated admin invitation secret privately. Record the real public URL after opening it successfully.

6. Register an admin, link the owner wallet and fund reserve. Use a separate customer wallet for deposit, withdrawal and interest scenarios. Confirm explorer receipts and record timestamps.

7. Verify HTTPS login, cross-account access restrictions, disk persistence after restart, mobile layout and service recovery. Record actual observations, not just a checkbox plan.

8. Complete the public identifiers above, add redacted screenshots, run the live demonstration or upload a genuine 10-minute recording. Regenerate the submission snapshot after evidence is added.

Capture checklist

Include: public app URL, successful health check, admin/customer screens with private emails redacted where appropriate, explorer contract page, funding and deposit/withdraw/claim receipts, and persistence/restart evidence. Never publish RPC access tokens, the invitation code, private keys, seed phrases or session cookies. No generated wireframe is a substitute for a deployed screenshot.

Current release decision

Do not label this version production-ready or claim every original numeric threshold is met. Local build/test evidence exists; public deployment, contribution history and performed demonstration evidence do not. Credentials and service ownership are required to complete external publication; real MetaMask and public-host validation remain necessary. Use APP_ENV=production and the exact PUBLIC_ORIGIN (or Render-provided RENDER_EXTERNAL_URL) for public hosting.