

Contents

- [question 1](#)
- [cheby1](#)
- [cheby2](#)
- [ellip](#)
- [question2-yulewalk](#)

question 1

```
rand('seed',72);
n=wgn(1,1000,0);

wc = 1/4;
order = 5;
%%butter
[b,a] = butter(order, wc);




figure(1);
    zplane(b,a);
    title('zeros and poles butter')
figure(2);
    freqz(b,a);
    title('freq butter')



%%imp response
figure(3);
impz(b,a,100)
title('imp response butter')


%%rondom butter
%%noise after fillter
butter_filter = filter(b,a,n);

figure(4);
plot(n)
title('rond data x')

x_filter_abs= abs(fftshift(fft(butter_filter)));
figure(5);
plot(x_filter_abs)
title('output from butter')
```







cheby1

```
n=randn(1,10000);

wc = 1/4;




order = 5;

[z,p]=cheby1(order,0.5,wc);

figure(1);

    zplane(z,p);


    title('zeros and poles cheby1')
figure(2);
    freqz(z,p);
    title('freq cheby1')
```



```

%%imp response
figure(3);
impz(z,p,1000)
title('imp response cheby1')

```



```



%%rondom cheby1
%%noise after fillter
cheby1_filter = filter(z,p,n);

figure(4);
stem(abs(fftshift(fft(n))))
title('rond data x')

x_filter_abs= abs(fftshift(fft(cheby1_filter)));

figure(5);
stem(x_filter_abs)
title('output from cheby1')

```



cheby2

```
n=randn(1,1000);

wc = 1/4;




order = 5;

[z,p]=cheby2(order,0.5,wc);

figure(1);

    zplane(z,p);


    title('zeros and poles cheby2')
figure(2);
    freqz(z,p);
    title('freq cheby2')
```

```

%%imp response
figure(3);
impz(z,p,1000)
title('imp response cheby2')

```



```



%%rondom cheby2
%%noise after fillter
cheby2_filter = filter(z,p,n);

figure(4);
stem(abs(fftshift(fft(n))))
title('rond data x')

x_filter_abs= abs(fftshift(fft(cheby2_filter)));

figure(5);
stem(x_filter_abs)
title('output from cheby2')

```



ellip

```
n=wgn(1,1000,0);

wc = 1/4;

order = 5;

[b,a] = ellip(order,0.5,33, wc);

figure(1);

    zplane(b,a);




    title('zeros and poles ellip')
figure(2);
    freqz(b,a);
    title('freq ellip')



%%imp response
figure(3);
impz(b,a,100)
title('imp response ellip')


%%rondom ellip
%%noise after fillter
ellip_filter = filter(b,a,n);

figure(4);
plot(n)
title('rond data n')

x_filter_abs= abs(fftshift(fft(ellip_filter)));
figure(5);
plot(x_filter_abs)
title('output from ellip')
```







question2-yulewalk

```
n=randn(1,100);

f = [0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 1];

m = [0 0 1 1 0 0 1 1 0 0];

[b,a] = yulewalk(10,f,m);

figure(1);

    zplane(b,a);

    title('zeros and poles yulewalk')
figure(2);
    freqz(b,a);
    title('freq yulewalk')

%%imp response
figure(3);
```

```
impz(b,a,100)




title('imp response yulewalk')



%%rondom butter
%%noise after fillter
yulewalk_filter = filter(b,a,n);


figure(4);
stem(abs(fftshift(fft(n))))
title('rond data n')

x_filter_abs= abs(fftshift(fft(yulewalk_filter)));

figure(5);
stem(x_filter_abs)
title('output from yulewalk')
```





question 3 - tone detection

Contents

- [step1](#)
- [step2](#)
- [step3](#)

step1

the number is : 0 1 0 9 5 0 1 7 7 6 3

```
Nt = 205;  
  
original_f =[697 770 852 941 1209 1336 1477];  
  
num=[1 2 3;4 5 6 ;7 8 9;10 0 11];  
  
[y,Fs]=audioread('C:\Users\SOUQ  
COMPUTER\Downloads\audiocheck.net_dtmf_01095017763.wav');
```

```
number_og_digits=length(y)/1600;
freq_indices = round(original_f/Fs*Nt)+1;
numbers=zeros(1,number_og_digits*2);
```

step2

use goertzel algorithm to detect the db of each freq then take the absolute of them then detect the 2 max and arrange them to save the low freq before the high one then plot every digit freq

```
for digits =0:number_og_digits-1;
    first=1+(digits*1600);
    end2=205+(digits*1600);


    y2=y(first:end2,:);
    dft_data = goertzel(y2,freq_indices);
    abs_data=abs(dft_data);

    subplot(4,3,1+digits);
    stem(original_f,abs_data)
    title(['digit ',num2str(digits+1)])

    %get max1
    [max1,max_index1]=max(abs_data);
    abs_data(max_index1)=0;
    %get max2
    [max2,max_index2]=max(abs_data);
    abs_data(max_index1)=0;

    %arrange them
    if max_index1>max_index2
        numbers(2*digits+1)=max_index2;
        numbers(2*digits+2)=max_index1;
    else
        numbers(2*digits+1)=max_index1;
        numbers(2*digits+2)=max_index2;
    end

end
```



step3

```
%detect the numbers and save them in res

res=zeros(1,number_of_digits);
ind=1;
for index=1:2:(number_of_digits*2)

    res(ind)= num(numbers(index),numbers(index+1)-4);
    ind=ind+1;
end

disp(res)
```

0 1 0 9 5 0 1 7 7 6 3

Another clear pic for the frequencies of the detected digits

