
FNFTpy Documentation

Release 0.4.0

Christoph Mahnke

Jun 27, 2021

CONTENTS:

1	Module overview	1
2	Auxiliary functions	3
2.1	set destination of FNFT library	3
2.2	get and print FNFT version	3
3	Korteweg-de-Fries equation	5
3.1	kdvv - calculate the Nonlinear Fourier Transform	5
3.2	kdvv_wrapper - interact with FNFT library	6
3.3	get, set and print options for kdvv_wrapper	7
3.4	options KdvvOptionsStruct	8
4	Nonlinear Schroedinger equation with periodic boundaries	9
4.1	nsep - calculate the Nonlinear Fourier Transform	9
4.2	nsep_wrapper - interact with FNFT library	11
4.3	get, set and print options for nsep wrapper	11
4.4	options NsepOptionsStruct	13
5	Nonlinear Schroedinger equation with vanishing boundaries	15
5.1	nsev - calculate the Nonlinear Fourier Transform	15
5.2	nsev_wrapper - interact with FNFT library	17
5.3	get, set and print options for nsep wrapper	18
5.4	options NsevOptionsStruct	20
6	Nonlinear Schroedinger equation with vanishing boundaries - Inverse Nonlinear Fourier Transform	21
6.1	nsev_inverse_xi_wrapper	21
6.2	nsev_inverse - calculate the Inverse Nonlinear Fourier Transform	22
6.3	nsev_inverse_wrapper - interact with FNFT library	23
6.4	get, set and print options for nsev_inverse_wrapper	24
6.5	options NsevInverseOptionsStruct	26
	Python Module Index	27
	Index	29

MODULE OVERVIEW

This file is part of FNFTpy. FNFTpy provides wrapper functions to interact with FNFT, a library for the numerical computation of nonlinear Fourier transforms.

For FNFTpy to work, a copy of FNFT has to be installed. For general information, source files and installation of FNFT, visit FNFT's github page: <https://github.com/FastNFT>

For information about setup and usage of FNFTpy see README.md or documentation.

FNFTpy is free software; you can redistribute it and/or modify it under the terms of the version 2 of the GNU General Public License as published by the Free Software Foundation.

FNFTpy is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Contributors:

Christoph Mahnke, 2018 - 2020

AUXILIARY FUNCTIONS

2.1 set destination of FNFT library

`FNFTpy.get_lib_path()`

Return the path of the FNFT file.

Edit this function to set the location of the compiled library for FNFT. See example strings below.

Returns:

- `libstring` : string holding library path

Example paths:

- `libstr = "C:/Libraries/local/libfnft.dll"` # example for windows
- `libstr = "/usr/local/lib/libfnft.so"` # example for linux

2.2 get and print FNFT version

`FNFTpy.get_fnft_version()`

Get the version of FNFT used by calling `fnft_version`.

Returns:

- **rdict: dictionary holding the fields:**
 - `return_value` : return value from FNFT
 - `major` : major version number
 - `minor` : minor version number
 - `patch` : patch level
 - `suffix` : suffix string

`FNFTpy.print_fnft_version()`

Prints the path and the version of FNFT library used.

KORTEWEG-DE-FRIES EQUATION

3.1 kdvv - calculate the Nonlinear Fourier Transform

`FNFTpy.fnft_kdvv_wrapper.kdvv(u, tvec, M=128, Xi1=-2, Xi2=2, dis=None)`

Calculate the Nonlinear Fourier Transform for the Korteweg-de Vries equation with vanishing boundaries.

This function is intended to be 'convenient', which means it automatically calculates some variables needed to call the C-library and uses some default options. Own options can be set by passing optional arguments (see below).

Currently, only the continuous spectrum is calculated.

It converts all Python input into the C equivalent and returns the result from FNFT. If a more C-like interface is desired, the function 'kdvv_wrapper' can be used (see documentation there).

Arguments:

- `u` : numpy array holding the samples of the field to be analyzed
- `tvec` : time vector
- `M` : number of samples for the continuous spectrum to calculate,

Optional arguments:

- `Xi1, Xi2` : min and max frequency for the continuous spectrum, default = [-2,2]
- `dis`: discretization, default = 17 (for details see FNFT documentation)
 - 0 = 2SPLIT1A
 - 1 = 2SPLIT1B
 - 2 = 2SPLIT2A
 - 3 = 2SPLIT2B
 - 4 = 2SPLIT2S
 - 5 = 2SPLIT3A
 - 6 = 2SPLIT3B
 - 7 = 2SPLIT3S
 - 8 = 2SPLIT4A
 - 9 = 2SPLIT4B
 - 10 = 2SPLIT5A
 - 11 = 2SPLIT5B
 - 12 = 2SPLIT6A
 - 13 = 2SPLIT6B
 - 14 = 2SPLIT7A

- 15 = 2SPLIT7B
- 16 = 2SPLIT8A
- 17 = 2SPLIT8B
- 18 = 4SPLIT4A
- 19 = 4SPLIT4B
- 20 = BO
- 21 = CF4_2
- 22 = CF4_3
- 23 = CF5_3
- 24 = CF6_4

Returns:

- rdict : dictionary holding the fields:
 - return_value : return value from FNFT
 - cont : continuous spectrum
 - options : KdvvOptionsStruct with options used

3.2 kdvv_wrapper - interact with FNFT library

`FNFTpy.fnft_kdvv_wrapper.kdvv_wrapper(D, u, T1, T2, M, Xi1, Xi2, K, options)`

Calculate the Nonlinear Fourier Transform for the Korteweg-de Vries equation with vanishing boundaries.

This function's interface mimics the behavior of the function 'fnft_kdvv' of FNFT. It converts all Python input into the C equivalent and returns the result from FNFT. If a more simplified version is desired, 'kdvv' can be used (see documentation there).

Currently, only the continuous spectrum is calculated.

Arguments:

- D : number of samples
- u : numpy array holding the samples of the field to be analyzed
- T1, T2 : time positions of the first and the last sample
- M : number of values for the continuous spectrum to calculate
- Xi1, Xi2 : min and max frequency for the continuous spectrum
- K : maximum number of bound states to calculate (no effect yet)
- options : options for kdvv as KdvvOptionsStruct. Can be generated e.g. with 'get_kdvv_options()'

Returns:

- rdict : dictionary holding the fields:
 - return_value : return value from FNFT
 - cont : continuous spectrum
 - options : KdvvOptionsStruct with options used

3.3 get, set and print options for kdvv_wrapper

`FNFTpy.options_handling.fnft_kdvv_default_options_wrapper()`

Get the default options for kdvv directly from the FNFT C-library.

Returns:

- options : KdvvOptionsStruct with options for kdvv_wrapper

`FNFTpy.options_handling.get_kdvv_options(dis=None)`

Get an KdvvOptionsStruct struct for use with kdvv_wrapper.

When called without additional optional arguments, the default values from FNFT are used.

Optional arguments:

- dis: discretization, default = 17 (for details see FNFT documentation)
 - 0 = 2SPLIT1A
 - 1 = 2SPLIT1B
 - 2 = 2SPLIT2A
 - 3 = 2SPLIT2B
 - 4 = 2SPLIT2S
 - 5 = 2SPLIT3A
 - 6 = 2SPLIT3B
 - 7 = 2SPLIT3S
 - 8 = 2SPLIT4A
 - 9 = 2SPLIT4B
 - 10 = 2SPLIT5A
 - 11 = 2SPLIT5B
 - 12 = 2SPLIT6A
 - 13 = 2SPLIT6B
 - 14 = 2SPLIT7A
 - 15 = 2SPLIT7B
 - 16 = 2SPLIT8A
 - 17 = 2SPLIT8B
 - 18 = 4SPLIT4A
 - 19 = 4SPLIT4B
 - 20 = BO
 - 21 = CF4_2
 - 22 = CF4_3
 - 23 = CF5_3
 - 24 = CF6_4

Returns:

- options : KdvvOptionsStruct

`FNFTpy.options_handling.print_kdvv_options(options=None)`

Print options of a `KdvvOptionsStruct`.

When called without additional argument, the default options from FNFT are printed.

Optional arguments:

- `options` : `KdvvOptionsStruct`, e.g. created by `get_kdvv_options()`

3.4 options `KdvvOptionsStruct`

class `FNFTpy.typesdef.KdvvOptionsStruct`

Ctypes options struct for interfacing `fnft_kdvv`.

Fields:

- `discretization`

Options can be printed directly to screen, e.g.

```
print(get_kdvv_options())
```

String representation can be generated by

```
repr(get_kdvv_options())
```

NONLINEAR SCHROEDINGER EQUATION WITH PERIODIC BOUNDARIES

4.1 nsep - calculate the Nonlinear Fourier Transform

```
FNFTpy.fnft_nsep_wrapper.nsep(q, T1, T2, kappa=1, loc=None, filt=None, bb=None, maxev=None,  
                               dis=None, nf=None, floq_range=None, ppspine=None, dsub=None,  
                               tol=None, phase_shift=0.0)
```

Calculate the Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with periodic boundaries.

This function is intended to be ‘convenient’, which means it automatically calculates some variables needed to call the C-library and uses some default options. Own options can be set by passing optional arguments (see below). Options can be set by passing optional arguments (see below).

It converts all Python input into the C equivalent and returns the result from FNFT. If a more C-like interface is desired, the function ‘nsep_wrapper’ can be used (see documentation there).

Arguments:

- *q* : numpy array holding the samples of the input field
- *T1, T2* : time positions of the first and the (D+1) sample, where D is the number of samples

Optional arguments:

- *kappa* : +/- 1 for focussing/defocussing nonlinearity, default = 1
- *loc* : localization method for the spectrum, default = 2
 - 0 = subsample and refine
 - 1 = gridsearch
 - 2 = mixed
- *filt* : filtering of spectrum, default = 2
 - 0 = none
 - 1 = manual
 - 2 = auto
- *bb*: bounding box used for manual filtering, default = [-inf, inf, -inf, inf]
- *maxev* : maximum number of evaluations for root refinement, default = 20
- *nf* : normalization flag default = 1
 - 0 = off
 - 1 = on
- *dis* : discretization, default = 4
 - 0 = 2SPLIT2_MODAL

- 1 = BO
- 2 = 2SPLIT1A
- 3 = 2SPLIT1B
- 4 = 2SPLIT2A
- 5 = 2SPLIT2B
- 6 = 2SPLIT2S
- 7 = 2SPLIT3A
- 8 = 2SPLIT3B
- 9 = 2SPLIT3S
- 10 = 2SPLIT4A
- 11 = 2SPLIT4B
- 12 = 2SPLIT5A
- 13 = 2SPLIT5B
- 14 = 2SPLIT6A
- 15 = 2SPLIT6B
- 16 = 2SPLIT7A
- 17 = 2SPLIT7B
- 18 = 2SPLIT8A
- 19 = 2SPLIT8B
- 20 = 4SPLIT4A
- 21 = 4SPLIT4B
- 22 = CF4_2
- 23 = CF4_3
- 24 = CF5_3
- 25 = CF6_4
- 26 = ES4
- 27 = TES4
- nf : normalization flag, default=1
 - 0 = off
 - 1 = on
- floq_range : array of two reals defining Floquet range, default = [-1, 1]
- ppspin : points per spine: defining the grid between interval set by floq_range
- dsusb : approximate number of samples for 'subsample and refine' localization
- tol : Tolerance, for root search refinement. Can be either positive number or (default =-1 (=auto))
- phase_shift : change of the phase over one quasi-period, $\arg(q(t+(T_2-T_1)/q(t))$ (default=0)

Returns:

- rdict : dictionary holding the fields (depending on options)
 - return_value : return value from FNFT
 - K : number of points in the main spectrum

- main : main spectrum
- M: number of points in the auxiliary spectrum
- aux: auxiliary spectrum
- options : NsepOptionsStruct with options used

4.2 nsep_wrapper - interact with FNFT library

`FNFTpy.fnft_nsep_wrapper.nsep_wrapper(D, q, T1, T2, phase_shift, kappa, options)`

Calculate the Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with periodic boundaries.

This function's interface mimics the behavior of the function 'fnft_nsep' of FNFT. It converts all Python input into the C equivalent and returns the result from FNFT. If a more simplified version is desired, 'nsep' can be used (see documentation there).

Arguments:

- D : number of sample points
- q : numpy array holding the samples of the input field
- T1, T2 : time positions of the first and the (D+1) sample
- phase_shift : change of the phase over one quasi-period, $\arg(q(t+(T2-T1)/q(t))$
- kappa : +/- 1 for focussing/defocussing nonlinearity
- options : options for nsep as NsepOptionsStruct. Can be generated e.g. with 'get_nsep_options()'

Returns:

- rdict : dictionary holding the fields (depending on options)
 - return_value : return value from FNFT
 - K : number of points in the main spectrum
 - main : main spectrum
 - M: number of points in the auxiliary spectrum
 - aux: auxiliary spectrum
 - options : NsepOptionsStruct with options used

4.3 get, set and print options for nsep wrapper

`FNFTpy.options_handling.fnft_nsep_default_options_wrapper()`

Get the default options for nsep directly from the FNFT C-library.

Returns:

- options : NsepOptionsStruct for nsep_wrapper

`FNFTpy.options_handling.get_nsep_options(loc=None, filt=None, bb=None, maxev=None, dis=None, nf=None, floq_range=None, ppspine=None, dsub=None, tol=None)`

Get a NsepOptionsStruct struct for use with nsep_wrapper.

When called without additional optional argument, the default values from FNFT are used.

Optional arguments:

- loc : localization method for the spectrum, default = 2

- 0 = subsample and refine
- 1 = gridsearch
- 2 = mixed
- filt : filtering of spectrum, default = 2
 - 0 = none
 - 1 = manual
 - 2 = auto
- bb: bounding box used for manual filtering, default = [-inf, inf, -inf, inf]
- maxev : maximum number of evaluations for root refinement, default = 20
- dis : discretization, default = 4
 - 0 = 2SPLIT2_MODAL
 - 1 = BO
 - 2 = 2SPLIT1A
 - 3 = 2SPLIT1B
 - 4 = 2SPLIT2A
 - 5 = 2SPLIT2B
 - 6 = 2SPLIT2S
 - 7 = 2SPLIT3A
 - 8 = 2SPLIT3B
 - 9 = 2SPLIT3S
 - 10 = 2SPLIT4A
 - 11 = 2SPLIT4B
 - 12 = 2SPLIT5A
 - 13 = 2SPLIT5B
 - 14 = 2SPLIT6A
 - 15 = 2SPLIT6B
 - 16 = 2SPLIT7A
 - 17 = 2SPLIT7B
 - 18 = 2SPLIT8A
 - 19 = 2SPLIT8B
 - 20 = 4SPLIT4A
 - 21 = 4SPLIT4B
 - 22 = CF4_2
 - 23 = CF4_3
 - 24 = CF5_3
 - 25 = CF6_4
 - 26 = ES4
 - 27 = TES4
- nf : normalization flag, default=1

- 0 = off
- 1 = on
- floq_range : array of two reals defining Floquet range, default = [-1, 1]
- ppspine : points per spine: defining the grid between interval set by floq_range
- dsub : approximate number of samples for ‘subsample and refine’ localization
- tol : Tolerance, for root search refinement. Can be either positive number or (default == -1 (=auto))

Returns:

- options : NsepOptionsStruct

`FNFTpy.options_handling.print_nsep_options(options=None)`

Print options of a NsepOptionsStruct.

When called without additional arguments, the default options from FNFT are printed.

Optional arguments:

- options : NsepOptionsStruct, e.g. created by `get_nsep_options`

4.4 options NsepOptionsStruct

class `FNFTpy.typesdef.NsepOptionsStruct`

Ctypes options struct for interfacing `fnft_nsep`.

Fields:

- localization
- filtering
- bounding_box
- max_evals
- discretization
- normalization_flag
- floquet_range
- points_per_spine
- dsub
- tolerance

Options can be printed directly to screen, e.g.

```
print(get_nsep_options())
```

String representation can be generated by

```
repr(get_nsep_options())
```


NONLINEAR SCHROEDINGER EQUATION WITH VANISHING BOUNDARIES

5.1 nsev - calculate the Nonlinear Fourier Transform

```
FNFTpy.fnft_nsev_wrapper.nsev(q, tvec, Xi1=-2, Xi2=2, M=128, K=128, kappa=1, bsf=None, bsl=None,
                               niter=None, Dsub=None, dst=None, cst=None, nf=None, dis=None,
                               ref=None)
```

Calculate the Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with vanishing boundaries.

This function is intended to be ‘convenient’, which means it automatically calculates some variables needed to call the C-library and uses some default options. Own options can be set by passing optional arguments (see below). Options can be set by passing optional arguments (see below).

It converts all Python input into the C equivalent and returns the result from FNFT. If a more C-like interface is desired, the function ‘nsev_wrapper’ can be used (see documentation there).

Arguments:

- *q* : numpy array holding the samples of the input field
- *tvec*: time vector

Optional arguments:

- *Xi1, Xi2* : min and max frequency for the continuous spectrum. default = -2,2
- *M* : number of values for the continuous spectrum to calculate default = 128
- *K* : maximum number of bound states to calculate default = 128
- *kappa* : +/- 1 for focussing/defocussing nonlinearity, default = 1
- *bsf* : bound state filtering, default = 2
 - 0 = none
 - 1 = basic
 - 2 = full
- *bsl* : bound state localization, default = 2
 - 0 = fast eigenvalue
 - 1 = Newton
 - 2 = subsample and refine
- *niter* : number of iterations for Newton bound state location, default = 10
- *Dsub* : number of samples used for ‘subsampling and refine’-method, default = 0 (auto)
- *dst* : type of discrete spectrum, default = 0
 - 0 = norming constants

- 1 = residues
 - 2 = both
 - 3 = skip computing discrete spectrum
- `csf` : type of continuous spectrum, default = 0
 - 0 = reflection coefficient
 - 1 = a and b
 - 2 = both
 - 3 = skip computing continuous spectrum
- `dis` : discretization, default = 11
 - 0 = 2SPLIT2_MODAL
 - 1 = BO
 - 2 = 2SPLIT1A
 - 3 = 2SPLIT1B
 - 4 = 2SPLIT2A
 - 5 = 2SPLIT2B
 - 6 = 2SPLIT2S
 - 7 = 2SPLIT3A
 - 8 = 2SPLIT3B
 - 9 = 2SPLIT3S
 - 10 = 2SPLIT4A
 - 11 = 2SPLIT4B
 - 12 = 2SPLIT5A
 - 13 = 2SPLIT5B
 - 14 = 2SPLIT6A
 - 15 = 2SPLIT6B
 - 16 = 2SPLIT7A
 - 17 = 2SPLIT7B
 - 18 = 2SPLIT8A
 - 19 = 2SPLIT8B
 - 20 = 4SPLIT4A
 - 21 = 4SPLIT4B
 - 22 = CF4_2
 - 23 = CF4_3
 - 24 = CF5_3
 - 25 = CF6_4
 - 26 = ES4
 - 27 = TES4
- `nf` : normalization flag, default = 1
 - 0 = off

- 1 = on
- ref : richardson extrapolation flag, default = 0
 - 0 = off
 - 1 = on

Returns:

- rdict : dictionary holding the fields (depending on options)
 - return_value : return value from FNFT
 - bound_states_num : number of bound states found
 - bound_states : array of bound states found
 - disc_norm : discrete spectrum - norming constants
 - disc_res : discrete spectrum - residues
 - cont_ref : continuous spectrum - reflection coefficient
 - cont_a : continuous spectrum - scattering coefficient a
 - cont_b : continuous spectrum - scattering coefficient b
 - options : NsevOptionsStruct with the options used

5.2 nsev_wrapper - interact with FNFT library

`FNFTpy.fnft_nsev_wrapper.nsev_wrapper(D, q, T1, T2, Xi1, Xi2, M, K, kappa, options)`

Calculate the Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with vanishing boundaries.

This function's interface mimics the behavior of the function 'fnft_nsev' of FNFT. It converts all Python input into the C equivalent and returns the result from FNFT. If a more simplified version is desired, 'nsev' can be used (see documentation there).

Arguments:

- D : number of sample points
- q : numpy array holding the samples of the field to be analyzed
- T1, T2 : time positions of the first and the last sample
- Xi1, Xi2 : min and max frequency for the continuous spectrum
- M : number of values for the continuous spectrum to calculate
- K : maximum number of bound states to calculate
- kappa : +/- 1 for focussing/defocussing nonlinearity
- options : options for nsev as NsevOptionsStruct

Returns:

- rdict : dictionary holding the fields (depending on options)
 - return_value : return value from FNFT
 - bound_states_num : number of bound states found
 - bound_states : array of bound states found
 - disc_norm : discrete spectrum - norming constants
 - disc_res : discrete spectrum - residues

- `cont_ref` : continuous spectrum - reflection coefficient
- `cont_a` : continuous spectrum - scattering coefficient a
- `cont_b` : continuous spectrum - scattering coefficient b
- `options` : `NsepOptionsStruct` with the options used

5.3 get, set and print options for nsep wrapper

`FNFTpy.options_handling.fnft_nsev_default_options_wrapper()`

Get the default options for nsev directly from the FNFT C-library.

Returns:

- `options` : `NsepOptionsStruct` with options for `nsev_wrapper`

`FNFTpy.options_handling.get_nsev_options(bsf=None, bsl=None, niter=None, Dsub=None, dst=None, cst=None, nf=None, dis=None, ref=None)`

Get a `NsepOptionsStruct` for use with `nsev_wrapper`.

When called without additional optional arguments, the default values from FNFT are used.

Optional arguments:

- `bsf` : bound state filtering, default = 2
 - 0 = none
 - 1 = basic
 - 2 = full
- `bsl` : bound state localization, default = 2
 - 0 = fast eigenvalue
 - 1 = Newton
 - 2 = subsample and refine
- `niter` : number of iterations for Newton bound state location, default = 10
- `Dsub` : number of samples used for ‘subsampling and refine’-method, default = 0 (auto)
- `dst` : type of discrete spectrum, default = 0
 - 0 = norming constants
 - 1 = residues
 - 2 = both
 - 3 = skip computing discrete spectrum
- `cst` : type of continuous spectrum, default = 0
 - 0 = reflection coefficient
 - 1 = a and b
 - 2 = both
 - 3 = skip computing continuous spectrum
- `dis` : discretization, default = 11
 - 0 = 2SPLIT2_MODAL
 - 1 = BO
 - 2 = 2SPLIT1A

- 3 = 2SPLIT1B
 - 4 = 2SPLIT2A
 - 5 = 2SPLIT2B
 - 6 = 2SPLIT2S
 - 7 = 2SPLIT3A
 - 8 = 2SPLIT3B
 - 9 = 2SPLIT3S
 - 10 = 2SPLIT4A
 - 11 = 2SPLIT4B
 - 12 = 2SPLIT5A
 - 13 = 2SPLIT5B
 - 14 = 2SPLIT6A
 - 15 = 2SPLIT6B
 - 16 = 2SPLIT7A
 - 17 = 2SPLIT7B
 - 18 = 2SPLIT8A
 - 19 = 2SPLIT8B
 - 20 = 4SPLIT4A
 - 21 = 4SPLIT4B
 - 22 = CF4_2
 - 23 = CF4_3
 - 24 = CF5_3
 - 25 = CF6_4
 - 26 = ES4
 - 27 = TES4
- nf : normalization flag, default = 1
 - 0 = off
 - 1 = on
 - ref : richardson extrapolation flag, default = 0
 - 0 = off
 - 1 = on

Returns:

- options : NsevOptionsStruct

FNFTpy.options_handling.print_nsev_options(options=None)

Print options of a NsevOptionsStruct.

When called without additional argument, the default options from FNFT are printed.

Optional arguments:

- options : NsevOptionsStruct, e.g. created by get_nsev_options()

5.4 options NsevOptionsStruct

class FNFTpy.typesdef.NsevOptionsStruct
Ctypes options struct for interfacing fnft_nsev.

Fields:

- bound_state_filtering
- bound_state_localization
- Dsub
- niter
- discspec_type
- contspec_type
- normalization_flag
- discretization
- richardson_extrapolation_flag

Options can be printed directly to screen, e.g.

```
print(get_nsev_options())
```

String representation can be generated by

```
repr(get_nsev_options())
```


NONLINEAR SCHROEDINGER EQUATION WITH VANISHING BOUNDARIES - INVERSE NONLINEAR FOURIER TRANSFORM

6.1 nsev_inverse_xi_wrapper

`FNFTpy.nsev_inverse_xi_wrapper(D, T1, T2, M, dis=None)`

Helper function for `nsev_inverse` to calculate the spectral borders for a given time window.

Return value is an array holding the position of the first and the last spectral sample to be used for `nsev_inverse`.

Arguments:

- D : number of sample points for the time window
- T1, T2 : borders of the time window
- M : number of samples for the continuous spectrum

Optional Arguments:

- dis : nse discretization parameter, default = 4
 - 0 = 2SPLIT2_MODAL
 - 1 = BO
 - 2 = 2SPLIT1A
 - 3 = 2SPLIT1B
 - 4 = 2SPLIT2A
 - 5 = 2SPLIT2B
 - 6 = 2SPLIT2S
 - 7 = 2SPLIT3A
 - 8 = 2SPLIT3B
 - 9 = 2SPLIT3S
 - 10 = 2SPLIT4A
 - 11 = 2SPLIT4B
 - 12 = 2SPLIT5A
 - 13 = 2SPLIT5B
 - 14 = 2SPLIT6A
 - 15 = 2SPLIT6B
 - 16 = 2SPLIT7A
 - 17 = 2SPLIT7B

- 18 = 2SPLIT8A
- 19 = 2SPLIT8B

Returns:

- rv : return value of the C-function
- xi : two-element C double vector containing XI borders

6.2 nsev_inverse - calculate the Inverse Nonlinear Fourier Transform

`FNFTpy.fnft_nsev_inverse_wrapper.nsev_inverse(xivec, tvec, contspec, bound_states, discspec, dis=None, cst=None, csim=None, dst=None, max_iter=None, osf=None, kappa=1)`

Calculate the Inverse Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with vanishing boundaries.

This function is intended to be ‘clutter-free’, which means it automatically calculates some variables needed to call the C-library. Options can be set by passing optional arguments (see below). It converts all Python input into the C equivalent and returns the result from FNFT. If a more C-like interface is desired, the function ‘nsev_inverse_wrapper’ can be used (see documentation there).

!!! Attention: time and frequency vector can not be choosen independently (yet). use `nsev_inverse_xi_wrapper` to calculate xivec forom tvec !!!

Arguments:

- xivec: frequency vector
- tvec: time vector
- contspec: continuous spectrum (of xi). Pass None if for pure soliton state.
- bound_states: array holding the bound states. Pass None if no bound states present.
- discspec: discrete spectrum. Pass None if no bound states present.

Optional arguments:

- dis : discretization, default = 4
 - 0 = 2SPLIT2_MODAL
 - 1 = BO
 - 2 = 2SPLIT1A
 - 3 = 2SPLIT1B
 - 4 = 2SPLIT2A
 - 5 = 2SPLIT2B
 - 6 = 2SPLIT2S
 - 7 = 2SPLIT3A
 - 8 = 2SPLIT3B
 - 9 = 2SPLIT3S
 - 10 = 2SPLIT4A
 - 11 = 2SPLIT4B
 - 12 = 2SPLIT5A
 - 13 = 2SPLIT5B

- 14 = 2SPLIT6A
- 15 = 2SPLIT6B
- 16 = 2SPLIT7A
- 17 = 2SPLIT7B
- 18 = 2SPLIT8A
- 19 = 2SPLIT8B
- 20 = 4SPLIT4A
- 21 = 4SPLIT4B
- 22 = CF4_2
- 23 = CF4_3
- 24 = CF5_3
- 25 = CF6_4
- 26 = ES4
- 27 = TES4
- `cst` : type of continuous spectrum, default = 0
 - 0 = Reflection coefficient
 - 1 = b of xi
 - 2 = b of tau
- `csim` : inversion method for the continuous part, default = 0
 - 0 = default
 - 1 = Transfermatrix with reflection coefficients
 - 2 = Transfermatrix with a,b from iteration
 - 3 = seed potential
- `dst` : type of discrete spectrum, default = 0
 - 0 = norming constants
 - 1 = residues
- `max_iter` : maximum number of iterations for iterative methods, default = 100
- `osf` : oversampling factor, default = 8

6.3 nsev_inverse_wrapper - interact with FNFT library

`FNFTpy.fnft_nsev_inverse_wrapper.nsev_inverse_wrapper`(*M, contspec, Xi1, Xi2, K, bound_states, normconst_or_residues, D, T1, T2, kappa, options*)

Calculate the Inverse Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with vanishing boundaries.

This function's interface mimics the behavior of the function 'fnft_nsev_inverse' of FNFT. It converts all Python input into the C equivalent and returns the result from FNFT. If a more simplified version is desired, 'nsev_inverse' can be used (see documentation there).

Arguments:

- `M` : number of sample points for continuous spectrum

- `contspec` : numpy array holding the samples of the continuous spectrum (can be None if $M=0$)
- **`Xi1, Xi2`** [frequencies defining the frequency range of the continuous spectrum.] ! Currently, the positions returned by `nsev_inverse_xi_wrapper` must be used !
- `K` : number of bound states
- `bound_states` : bound states (can be None if $K=0$)
- `normconst_or_residues` : bound state spectral coefficients (can be None if $K=0$)
- `D` : number of samples for the output field
- `T1, T2` : borders of the desired time window
- `kappa` : +1/-1 for focussing / defocussing NSE
- `options` : options for `nsev_inverse` as `NsevInverseOptionsStruct`

Returns:

- `rdict` : dictionary holding the fields (depending on options)
 - `return_value` : return value from FNFT
 - `q` : time field resulting from inverse transform
 - `options` : options for `nsev_inverse` as `NsevInverseOptionsStruct`

6.4 get, set and print options for `nsev_inverse_wrapper`

`FNFTpy.options_handling.fnft_nsev_inverse_default_options_wrapper()`

Get the default options for `nsev_inverse` directly from the FNFT C-library.

Returns:

- `options` : `NsevInverseOptionsStruct` with options for `nsev_inverse_wrapper`

`FNFTpy.options_handling.get_nsev_inverse_options(dis=None, cst=None, csim=None, dst=None, max_iter=None, osf=None)`

Get a `NsevInverseOptionsStruct` for use with `nsev_inverse_wrapper`.

When called without additional optional arguments, the default values from FNFT are used.

Optional arguments:

- `dis` : discretization, default = 4
 - 0 = 2SPLIT2_MODAL
 - 1 = BO
 - 2 = 2SPLIT1A
 - 3 = 2SPLIT1B
 - 4 = 2SPLIT2A
 - 5 = 2SPLIT2B
 - 6 = 2SPLIT2S
 - 7 = 2SPLIT3A
 - 8 = 2SPLIT3B
 - 9 = 2SPLIT3S
 - 10 = 2SPLIT4A
 - 11 = 2SPLIT4B

- 12 = 2SPLIT5A
- 13 = 2SPLIT5B
- 14 = 2SPLIT6A
- 15 = 2SPLIT6B
- 16 = 2SPLIT7A
- 17 = 2SPLIT7B
- 18 = 2SPLIT8A
- 19 = 2SPLIT8B
- 20 = 4SPLIT4A
- 21 = 4SPLIT4B
- 22 = CF4_2
- 23 = CF4_3
- 24 = CF5_3
- 25 = CF6_4
- 26 = ES4
- 27 = TES4
- `cst` : type of continuous spectrum, default = 0
 - 0 = Reflection coefficient
 - 1 = b of xi
 - 2 = b of tau
- `csm` : inversion method for the continuous part, default = 0
 - 0 = default
 - 1 = Transfermatrix with reflection coefficients
 - 2 = Transfermatrix with a,b from iteration
 - 3 = seed potential
- `dst` : type of discrete spectrum, default = 0
 - 0 = norming constants
 - 1 = residues
- `max_iter` : maximum number of iterations for iterative methods, default = 100
- `osf` : oversampling factor, default = 8

Returns:

- `options` : `NsevInverseOptionsStruct`

`FNFTpy.options_handling.print_nsev_inverse_options(options=None)`

Print options of a `NsevInverseOptionsStruct` for `nsev_inverse`.

When called without additional argument, the default options from FNFT are printed.

Optional arguments:

- `options` : `NsevInverseOptionsStruct`, e.g. created by `get_nsev_options()`

6.5 options NsevInverseOptionsStruct

class FNFTpy.typesdef.NsevInverseOptionsStruct
Ctypes options struct for interfacing fnft_nsev_inverse.

Fields:

- discretization
- contspec_type
- contspec_inversion_method
- discspec_type
- max_iter
- oversampling_factor

Options can be printed directly to screen, e.g.

```
print(get_nsev_inverse_options())
```

String representation can be generated by

```
repr(get_nsev_inverse_options())
```

PYTHON MODULE INDEX

f

FNFTpy, 1

F

`fnft_kdvv_default_options_wrapper()` (in module `FNFTpy.options_handling`), 7
`fnft_nsep_default_options_wrapper()` (in module `FNFTpy.options_handling`), 11
`fnft_nsev_default_options_wrapper()` (in module `FNFTpy.options_handling`), 18
`fnft_nsev_inverse_default_options_wrapper()` (in module `FNFTpy.options_handling`), 24
`FNFTpy`
 module, 1

G

`get_fnft_version()` (in module `FNFTpy`), 3
`get_kdvv_options()` (in module `FNFTpy.options_handling`), 7
`get_lib_path()` (in module `FNFTpy`), 3
`get_nsep_options()` (in module `FNFTpy.options_handling`), 11
`get_nsev_inverse_options()` (in module `FNFTpy.options_handling`), 24
`get_nsev_options()` (in module `FNFTpy.options_handling`), 18

K

`kdvv()` (in module `FNFTpy.fnft_kdvv_wrapper`), 5
`kdvv_wrapper()` (in module `FNFTpy.fnft_kdvv_wrapper`), 6
`KdvvOptionsStruct` (class in `FNFTpy.typesdef`), 8

M

module
`FNFTpy`, 1

N

`nsep()` (in module `FNFTpy.fnft_nsep_wrapper`), 9
`nsep_wrapper()` (in module `FNFTpy.fnft_nsep_wrapper`), 11
`NsepOptionsStruct` (class in `FNFTpy.typesdef`), 13
`nsev()` (in module `FNFTpy.fnft_nsev_wrapper`), 15
`nsev_inverse()` (in module `FNFTpy.fnft_nsev_inverse_wrapper`), 22
`nsev_inverse_wrapper()` (in module `FNFTpy.fnft_nsev_inverse_wrapper`), 23
`nsev_inverse_xi_wrapper()` (in module `FNFTpy`), 21

`nsev_wrapper()` (in module `FNFTpy.fnft_nsev_wrapper`), 17
`NsevInverseOptionsStruct` (class in `FNFTpy.typesdef`), 26
`NsevOptionsStruct` (class in `FNFTpy.typesdef`), 20

P

`print_fnft_version()` (in module `FNFTpy`), 3
`print_kdvv_options()` (in module `FNFTpy.options_handling`), 7
`print_nsep_options()` (in module `FNFTpy.options_handling`), 13
`print_nsev_inverse_options()` (in module `FNFTpy.options_handling`), 25
`print_nsev_options()` (in module `FNFTpy.options_handling`), 19