

✓ A two-dimensional (2D) array `Account[]` contains account holders' names and passwords for a banking program. ← string

A 2D array `AccDetails[]` has three columns containing the following details:

- ✓
- column one stores the balance – the amount of money in the account, for example 250.00
 - column two stores the overdraft limit – the maximum total amount an account holder can borrow from the bank after the account balance reaches 0.00, for example 100.00
 - column three stores the withdrawal limit – the amount of money that can be withdrawn at one time, for example 200.00

✓ The amount of money in a bank account can be negative (overdrawn) but **not** by more than the overdraft limit.

For example, an account with an overdraft limit of 100.00 must have a balance that is greater than or equal to -100.00

Suitable error messages must be displayed if a withdrawal cannot take place, for example if the overdraft limit or the size of withdrawal is exceeded.

The bank account ID gives the index of each account holder's data held in the two arrays.

For example, account ID 20's details would be held in:

Account[20,1] and Account[20,2] ← password

AccDetails[20,1] AccDetails[20,2] and AccDetails[20,3]

Name ← balance ← o/d limit ← withdrawal limit
The variable `Size` contains the number of accounts.

The arrays and variable `Size` have already been set up and the data stored.

Write a program that meets the following requirements:

- checks the account ID exists and the name and password entered by the account holder match the name and password stored in `Account[]` before any action can take place
- displays a menu showing the four actions available for the account holder to choose from:
 1. display balance
 2. withdraw money
 3. deposit money
 4. exit
- allows an action to be chosen and completed. Each action is completed by a procedure with a parameter of the account ID.

You must use pseudocode or program code **and** add comments to explain how your code works. All inputs and outputs must contain suitable messages.

You only need to declare any local arrays and local variables that you use.

You do **not** need to declare and initialise the data in the global arrays `Account[]` and `AccDetails[]` and the variable `Size`

Account		AccDetails 2		
0	Name, Password	Balance	Overdraft Limit	Withdrawal Limit
0	Bob, Bob1	250.00	100.00	200.00
1	Fred, TheGreat	37.13	100.00	200.00
2	Jim, Jiminy	647.32	100.00	200.00

Size

20 →

AccID

0 1 0 1 2

-100.00

		Account
print (Account [0][0]	Bob 0
	Account [2][0]	Jim 2
	Account [1][1]	The Great
	Row Col	

(Username & password entry)

INPUT Choice

CASE OF CHOICE

- 1: Balance (AccID)
- 2: Withdraw (AccID)
- 3: Deposit (AccID)
- 4: Exit ← TRUE

OTHERWISE : OUTPUT "Invalid Choice"

ENDCASE

User / Row

PROCEDURE Balance (Acid)

OUTPUT AccDetails [User, 0]

END PROCEDURE