Fragile Authentication of PDF Signatures via Bit-Exact Quantization Index Modulation on Vector Geometry

Yaroslav V. Baienko

***Abstract*—A PDF signature verifies the bytes it covers, not the page a human sees. The visible layer—seals and stamps—is not cryptographically bound to the signed content, so a valid signature can accompany altered or transplanted visual material. We study a fragile-authentication watermarking approach that closes this gap at the rendering level: the digest of the signed document is embedded, bit-exactly, into the geometry of the visible seal, so the mark a person sees is also the mark that is verified. The carrier is a planar incidence configuration of nine triangles (27 degrees of freedom); the payload uses keyed dithered quantization index modulation over an integer coordinate lattice with an IEEE-754 rounding argument, and a disjoint degree of freedom carries a per-recipient identifier. No external QR/barcode is added. We evaluate 180 PDFs from 60 documents (LibreOffice, Typst and Chromium), in native, flattened and print-scan-simulated variants, plus ten project and five independent public documents. On 1,800 stamped PDFs the 266-bit payload is recovered exactly, survives 8-decimal re-serialisation, fails closed at 7 decimals, and detects every edited payload coordinate; flattening destroys the vector carrier and fails closed. Same-carrier baselines expose a capacity–distortion trade-off. Two implementation facts: the PDF writer must preserve at least nine decimal places, and the verifier must parse coordinates as text—32-bit-float drawing APIs destroy the 1.8×10^{-8} pt lattice. A print-scan check fails closed in all five cases; digital controls verify exactly. It complements, not replaces, PAdES/eIDAS signatures.**

***Index Terms*—fragile watermarking, quantization index modulation, vector graphics, PDF signatures, document authentication.**

I. Introduction

A signed PDF can be *valid* and still mislead. The signature covers a byte range; the visual seal is an image or a vector drawing that the signature does not necessarily cover, and incremental updates or flattened copies live outside the signed bytes. The literature on PDF signature attacks documents hidden content [1] and signature spoofing [2], and document workflows add a third problem: a data room can hand every recipient a visually identical copy, so a leak cannot be attributed.

This paper asks a watermarking question rather than a cryptographic one: can a fragile mark be carried by the visible layer itself, so that (i) the mark is exactly recoverable from the rendered page, (ii) any modification of the mark is detected, and (iii) the mark identifies the recipient copy? The answer explored here is a bit-exact QIM payload embedded in the coordinates of a vector seal. The word *fragile* is deliberate: the goal is not robustness to editing but detection of it.

The contributions are: (1) a bit-exact fragile payload in vector geometry with an exact rounding bound; (2) a carrier that uses the seal itself, so removing or transplanting the seal breaks verification; (3) a disjoint recipient channel; and (4) an evaluation protocol with same-carrier baselines, three document generators, flattened and print-scan variants, a carrier ablation, and a public and independent-document anchor set. Section II positions the work; Section III states the model; Section V describes the method; Section VII reports the evaluation; Section VIII gives the attack matrix and the limits of the security argument; Sections IX–XIV discuss validity, reproducibility and limitations.

Prior versions. Earlier editions of this research line were posted as preprints [3]. The present manuscript is a substantially re-framed and expanded version: it narrows the claim to fragile authentication, adds the PDF-level evaluation, same-carrier baselines, the writer-precision study and the physical print-scan check, and is not a duplicate of those editions.

II. Related Work

A. Fragile versus robust watermarking

Robust watermarking aims to survive processing; fragile watermarking aims to detect it. Our work belongs to the second class and is therefore not comparable to robust schemes on bit-error rate under compression—the meaningful axes are exact recovery, distortion and detection. The QIM family [4]–[6] supplies the lattice;

Manuscript received October 23, 2026. The author is an independent researcher (Attorney-at-Law, Legal Engineer & Applied Cryptography Researcher), Kyiv, Ukraine (ORCID: 0009-0006-7498-2133). A preprint is archived on Zenodo (concept DOI 10.5281/zenodo.23429017); a Ukrainian patent application (a 2026 06266) covers the sealing method.

spread-spectrum schemes [7] and early data-hiding constructions [8] supply the historical contrast. Watermarking security analysis [9] and QIM steganalysis [10] frame what a keyed dither can and cannot promise.

The QIM literature is mature on rate–distortion: dither modulation, distortion-compensated QIM and spread-transform variants trade rate against distortion under an additive-noise model [4], [5]. Our setting differs in two ways. First, the channel is fragile: the verifier must reject any change, so there is no noise budget to optimise against and the relevant question is exactness, not robustness. Second, the host is a vector drawing whose coordinates are serialised as decimal text, so the lattice step must survive decimal formatting and parsing, not an analog channel. A formal steganographic-security claim is left out of scope.

B. Reversible data hiding

Difference expansion [11], histogram shifting [12] and prediction-error expansion [13] define the RDH family. On a 27-slot carrier these schemes are capacity-limited, which we report rather than hide; 2D vector-map RDH [14], [15] operates on much larger vertex sets, where capacity is not the binding constraint.

C. Vector graphics and PDF watermarking

Fourier-descriptor watermarking of 2D vector graphics [16], blind vector-graphics schemes [17], [18], polar-coordinate vector-data watermarking [19] and mesh-spectral maps [20] are the closest carrier-level relatives. PDF watermarking itself has been studied in [21], and print-scan resilience in [22]. Our carrier is unusual in that the mark is a *visible seal*, not a hidden embedding in an existing drawing; this is what makes the transplant attack meaningful.

D. PDF signature security and standards

Shadow attacks [1], signature spoofing [2], certification attacks [23] and practical decryption exfiltration [24] establish the threat model. Standards [25]–[27] define what a compliant signature does and does not cover. Our method does not change the signature; it makes the visible layer that the signature leaves uncovered tamper-evident.

E. Geometric background and visible seals

The nine-triangle incidence configuration has been studied as a mathematical object [28], [29], and projective incidence algebra is standard [30]; the paper uses the configuration only as a stabilised carrier and does not claim a new geometric theorem. Floating-point exactness follows the standard treatment [31]. A related industrial idea is the visible digital seal: a QR or bar-code symbol printed next to a document and bound to its content. Such a seal is an *external* symbol that can be detached or replaced; the present work removes the symbol and lets the drawing itself carry the payload, which is what makes the transplant attack meaningful.

TABLE I
POSITIONING AGAINST WATERMARKING FAMILIES.

Family	Purpose	Carrier	Optimises
Spread spectrum [7]	robustness	pixels/coeff.	survival
QIM/dither [4]–[6]	rate–distortion	scalar samples	capacity at distortion
RDH [11]–[15]	reversibility	pixels/vertices	exact cover recovery
Vector graphics [16]–[19]	robustness	2D geometry	survival under rescaling
PDF marking [21]	marking	text/objects	blind detection
This work	fragility	visible seal geometry	bit-exact digest recovery

F. Commitments, fingerprinting, terminology

Vector commitments [32], [33] and traitor tracing [34], [35] are related but not claimed here: the construction is a watermark, not a commitment scheme, and the recipient channel is attribution, not collusion-resistant tracing. The paper deliberately avoids "vector commitment" and "traitor tracing" as descriptions of its own mechanism.

G. What is new, and what is not

Table I positions the families; the paper does not claim a new modulation family: QIM, dither modulation and the capacity–distortion view are classical [4]–[6], and RDH [11]–[13] and vector-graphics watermarking [16]–[18] are established. The claim is narrower: a *visible seal* can carry a 256-bit digest bit-exactly, which turns a fragile watermark into a signature-to-rendering binding; the same carrier provides a geometric invariant and a disjoint recipient channel; and the implementation precondition (nine-decimal writers, text-level parsing) is made explicit. The paper does not claim cryptographic security from a watermarking argument and does not claim robustness.

III. System Model and Notation

We consider a document d with a canonical byte representation and a visible seal S drawn as a planar collection of triangles. The issuer computes a 256-bit digest $h = H(d)$ and a 10-bit recipient word r, and embeds (h, r) into the seal geometry with a secret key k. A verifier receives a PDF and a claimed

TABLE II
NOTATION.

Symbol	Meaning
d, $h = H(d)$	document and its 256-bit digest
r	10-bit recipient identifier
$\mathbf{s}$	27 carrier slots in page coordinates
$\delta(w)$	lattice shift for a 10-bit word, step 18 npt
π_K, d_K	keyed slot permutation and word dither
valid/modified/absent	verifier output states

digest (from the same document) and returns a state in $\{\text{valid}, \text{modified}, \text{absent}\}$. The carrier is described by 27 scalar slots $\mathbf{s} = (s_1, \ldots, s_{27})$ in page coordinates. Table II lists the notation.

IV. Threat Model and Requirements

The adversary can (a) edit the PDF content stream, (b) re-serialise coordinates at reduced precision, (c) flatten the page to a raster image, (d) transplant a visual seal from another document, and (e) redistribute a copy. The verifier knows the canonical seal geometry and the document digest. We state four requirements: *exactness* (the 256-bit digest is recovered bit for bit); *fragility* (any edit of a payload coordinate changes the recovered digest); *fail-closed* behaviour (when the vector layer is absent, the verifier refuses rather than accepts); and *attribution* (a recipient identifier is carried independently of the digest).

The threat model is deliberately weaker than a cryptographic one: we do not claim that an adversary cannot produce a new document with a new seal, only that an edited or transplanted seal is detectable relative to a known document digest.

V. Method

A. Carrier and degrees of freedom

The seal is drawn as nine triangles. Each triangle contributes three degrees of freedom—base line, apex, half-width—for 27 scalar slots. Because the triangles share a construction centre, the bilateral relation $lx + rx = 2cx$ and the common centre are geometric invariants, checked independently of the payload. A generic 27-vertex polyline and a 9×3 grid are used as ablations: they carry the same 27 slots at the same distortion, but have no such invariant (Fig. 1).

B. Bit-exact word mapping

A 256-bit digest is split into 26 words of 10 bits; the 27th word carries a 10-bit recipient identifier. A 10-bit word w maps to the coordinate shift

$$\delta(w) = (18w - 9207) \times 10^{-9} \text{ pt}, \tag{1}$$

i.e. a multiple of 18 npt $= 1.8 \times 10^{-8}$ pt, with $w \in [0, 1023]$.

C. Exactness argument

At coordinates of the order of 3×10^2 pt the IEEE-754 double spacing is $2^{-52} \times 2^9 \approx 1.1 \times 10^{-13}$ pt, more than four orders of magnitude below the step, so every lattice point is exactly representable and a recovered word has no rounding ambiguity. Re-serialising a coordinate with eight decimal places rounds it to the nearest 10^{-8} pt, an error of at most 5×10^{-9} pt, below half a step (9×10^{-9} pt); seven decimal places (error up to 5×10^{-8} pt) exceeds half a step and destroys the word.

D. Keyed dither and recipient channel

A key derives a permutation π_K of the 27 slots and a word-level dither d_K. The digest words are dithered and permuted before embedding, and the recipient word is placed in the remaining slot. The dither does not change the lattice spacing, so exactness is preserved; it changes which physical slot carries which word, so an unkeyed reader cannot align the payload with the geometry.

E. Encoding and decoding

Encode (d, r, k): (1) $h \leftarrow H(d)$; split h into 26 ten-bit words $w_1..w_{26}$; append $w_{27} \leftarrow r$. (2) derive (π_K, d_K) from the key and a document nonce; $v_i \leftarrow (w_{\pi_K(i)} + d_K(i)) \bmod 1024$. (3) $s'_i \leftarrow s_i + \delta(v_i)$ for $i = 1..27$. (4) write the path operators with nine decimals; return the stamped PDF and h.

Decode (PDF, h, k): (1) parse the content stream as text; locate the carrier path by marker colour/width. (2) reconstruct s'_i from the path; $v_i \leftarrow \delta^{-1}(s'_i - s_i)$; undo (π_K, d_K). (3) reassemble the 27 words; compare words 1–26 with $H(d)$; return the recipient word. (4) if the path is absent return *absent*; if comparison fails return *modified*; else *valid*.

F. Implementation precondition

The carrier must be written with at least nine decimal places. Common PDF writers emit five decimals, which destroys the 1.8×10^{-8} pt lattice; the reference implementation therefore injects path operators into the content stream directly rather than using a drawing API. The verifier must parse the numbers as text, because drawing APIs that store coordinates as 32-bit floats lose the lattice as well.

G. Complexity and deployment notes

Stamping is linear in the number of pages and constant in payload length: the carrier is a fixed 27-slot path, so the cost is one content-stream edit per page. On the development machine stamping costs about 1.05 ms and verification about 0.33 ms per page. A deployment assigns 10-bit recipient identifiers, which bounds one key epoch to 1,024 tracked copies; larger deployments rotate the key or extend the identifier space.




Fig. 1. The three carriers used in the ablation. All three carry the same 27 slots at the same distortion; only the incidence configuration (left) has the bilateral and common-centre invariants.

VI. Design Rationale and Alternatives

Why a visible seal rather than a hidden watermark? A hidden payload can be removed without changing the rendered page, so a human cannot tell that the mark is gone. The threat here is not extraction of a payload from a marked document; it is a document that looks legitimate while its visible authentication layer is altered or transplanted. Keeping the payload in the visible seal makes the verifier and the human inspect the same object. The cost is that the mark is intentionally fragile: any re-drawing or re-serialisation that changes the geometry is detected as a change, including innocent format conversion.

Why the incidence configuration? The nine-triangle construction supplies 27 scalar slots with known bilateral relations and a shared centre. The relations do not increase capacity; they supply a geometric invariant that is checked independently of the payload. A generic 27-vertex polyline and a 9×3 grid carry the same slot budget and are included in the ablation; they recover the payload equally well but do not detect a centre-line edit outside the payload slots. The carrier is therefore justified by the invariant, not by capacity or distortion.

Alternatives considered. A QR code or a second barcode would carry more bits per area but adds a visible machine-only object and is easy to separate from the seal; it is excluded by the design requirement that the authentication layer be the seal itself. Robust spread-spectrum and DCT schemes [7], [36] survive compression but do not guarantee bit-exact recovery of a cryptographic digest. Reversible data hiding [11]–[13] can recover the cover exactly but is capacity-limited on a 27-slot carrier. LSB-style embedding is invisible but is destroyed by the same re-serialisation that a PDF writer performs routinely. The chosen point is the one where exactness, visibility and fragility coincide.

Why exactness rather than error tolerance. A 256-bit digest has no error-correcting code in this design; a single changed bit makes the authenticated digest meaningless. Error tolerance would require a different payload budget and would weaken the binding between the signed bytes and the rendered seal. The paper therefore treats the zero-error requirement as a design constraint and reports the decimal-precision cliff explicitly, rather than presenting a robustness curve that would obscure it.

VII. Evaluation

A. Corpus

Sixty synthetic documents are generated by three independent pipelines: LibreOffice (DOCX to PDF), Typst, and Chromium print-to-PDF. Each document exists in three variants: *native*, *flattened* (300 dpi raster re-wrapped as an image-only PDF) and *print-scan simulated* (200 dpi, Gaussian blur, sensor noise, JPEG q=70). The corpus contains 180 PDFs (51.1 MB) with a SHA-256 manifest. Ten unique public project documents (whitepapers, manuscript PDFs and patent description PDFs; no client data) plus five independent public NIST standards (FIPS 186-5, FIPS 180-4, FIPS 202, SP 800-57 Part 1 Rev. 5 and FIPS 140-3) are used as anchors.

B. Protocol

For each document and seed, the payload is $H(\text{doc_sha}\|\text{seed})$; the 266-bit payload is embedded with keyed QIM, and the stamped PDF is attacked in the content stream (8/7-decimal truncation, payload-coordinate edit, centre-line edit) or flattened. The experiment runs 60 documents $\times$ 30 seeds (1,800 samples), plus 360 samples on flattened/print-scan inputs, plus an ablation over three carriers and keyed/unkeyed embedding,




Fig. 2. Capacity versus geometric distortion on the same 27-slot carrier. The proposed payload carries 266 bits at RMSE 5.3×10^{-6} pt; capacity-limited baselines are marked at their maximum capacity.

plus 150 samples on the public project-document and independent-document anchors.

C. Metrics and attack parameters

Geometric RMSE is the root-mean-square coordinate change over the 27 slots; $PSNR_{geom}$ is $20\log_{10}(300/\mathrm{RMSE})$ with the 300 pt geometry normalisation. *Exact* is one only if all 27 recovered words equal the embedded words. *Detection* is one if the recovered words differ from the expected words (payload edit) or if a geometric invariant fails (centre-line edit). Truncation rewrites every coordinate number in the carrier path to 8 or 7 decimal places. The payload-coordinate edit changes one coordinate by 10^{-4} pt; the centre-line edit changes a non-payload coordinate by 0.5 pt. Flattening replaces the page by a 300 dpi raster image.

D. Results

Fig. 2 and Tables III–IX summarise the results. On the main experiment, the 266-bit payload is recovered exactly in 100% of 1,800 samples (mean geometric RMSE 5.31×10^{-6} pt, $\mathrm{PSNR}_{\mathrm{geom}} = 155.1$ dB), survives 8-decimal truncation in 100% of samples, is detected at 7-decimal truncation in 100%, detects every payload-coordinate edit, and fails closed on every flattened page. The per-generator breakdown is in Table IV and Fig. 3; the ten project-document and five independent public-document anchors reproduce the same behaviour (150 samples).

E. Precision precondition in practice

The exactness argument predicts a cliff between eight and seven decimal places. The measurement matches the prediction: exact recovery is 100% at 9 and 8 decimals and drops to 0% at 7 and 6 decimals (Fig. 4). This is a property of the pipeline after sealing, not of the

TABLE III
PDF-LEVEL RESULTS ON 60 NATIVE DOCUMENTS × 30 SEEDS.

Metric	Result	95% CI	Samples
Exact digest recovery	100%	0.00	1800/1800
Survives 8-decimal truncation	100%	0.00	1800/1800
Detected at 7-decimal truncation	100%	0.00	1800/1800
Edited payload coordinate detected	100%	0.00	1800/1800
Flattening removes the carrier	100%	0.00	1800/1800

TABLE IV
PER-GENERATOR BREAKDOWN OF THE MAIN EXPERIMENT.

Generator	Samples	Exact	Detected at 7 dec.	RMSE (pt)
LibreOffice	600	100%	100%	5.30×10^{-6}
Typst	600	100%	100%	5.33×10^{-6}
Chromium	600	100%	100%	5.29×10^{-6}

document generator: the corpus generators themselves emit between three and six decimal places (Table VI), and the carrier is injected after generation. A production document-management system that re-writes coordinates with fewer than eight decimals destroys the mark; the verifier reports *absent* rather than *valid* (fail-closed).

F. Public and independent-document anchors

Ten unique public project documents (from twelve source PDFs; two duplicate layouts were excluded) plus five independent public documents from NIST (FIPS 186-5, FIPS 180-4, FIPS 202, SP 800-57 Part 1 Rev. 5 and FIPS 140-3) were stamped and attacked under the same protocol (10 seeds each, 150 samples). The ten project documents are the author's public project documents (whitepapers, manuscript versions and patent PDFs); the five NIST documents are independent third-party public standards. Together they test production PDF writers beyond the synthetic corpus, though not a population of enterprise DMS pipelines. Results match the synthetic corpus: exact recovery in 100% of samples, 8-decimal re-serialisation survives, 7-decimal re-serialisation and payload edits are detected, and flattening removes the carrier. Mean geometric RMSE is 5.30×10^{-6} pt ($\mathrm{PSNR}_{\mathrm{geom}} = 155.1$ dB). Table VII gives the per-document breakdown for the five independent NIST anchors.

G. Capacity, performance and storage

Capacity is per visible seal: 266 bits over a seal of about 126×185 pt (23,227 pt^2), i.e. 0.0115 bit/pt^2; no document-wide capacity claim is made. Stamping is linear in the number of pages and constant in payload length. On the development machine, stamping costs about 1.05 ms per page and verification about 0.33 ms

TABLE V
CARRIER ABLATION: ALL CARRIERS CARRY THE SAME 27 SLOTS.

Carrier	Keyed	Exact	Trunc-8	Centre edit detected
Sri Yantra	yes	100%	100%	100%
Sri Yantra	no	100%	100%	100%
Generic polyline	yes	100%	100%	0%
Generic polyline	no	100%	100%	0%
Grid	yes	100%	100%	0%
Grid	no	100%	100%	0%




Fig. 3. Embedding distortion per document generator (geometric RMSE in nanometres; medians 1.87–1.88 nm).




Fig. 4. Word recovery versus the number of decimal places preserved on re-serialisation.

TABLE VI
WRITER PRECISION OF THE CORPUS GENERATORS.

Generator	Avg. decimals	Carrier exact after injection
LibreOffice DOCX to PDF	3.16	100%
Chromium print-to-PDF	5.27	100%
Typst	5.76	100%

per page, dominated by PDF parsing and stream rewriting rather than by the embedding arithmetic. The carrier path is small and, after stream compression, adds only a few bytes to the file in our samples; memory use is proportional to one page at a time.

H. Physical print-scan capture

The simulated print-scan variant is complemented by a physical check. Five A4 documents were stamped, printed on a monochrome laser multifunction device (Canon i-SENSYS MF3010, 600 dpi) and scanned at 300 dpi in grayscale on the same device. All five digital controls verify as *valid*; all five physical captures verify as *absent*—the vector layer does not survive printing and scanning, and the verifier fails closed rather than accepting a raster page (Table VIII). Recovery of a payload from a raster capture belongs to the optical companion channel and is out of scope here.

I. Same-carrier baselines

STDM-DCT, Fourier-descriptor and LSB-RDH embedding were re-implemented on the same carrier at slot level and re-run at the PDF level (20 documents $\times$ 10 seeds, 600 samples). The comparison is a capacity–distortion–fragility frontier, not a ranking (Table IX). Only the proposed scheme reaches a 266-bit digest on 27 slots; STDM reaches 140 bits at higher distortion; Fourier descriptors reach 13 bits; LSB reaches 27 bits at negligible distortion but is destroyed by 8-decimal re-serialisation.

J. Discussion

Why exactness changes the application. An error-tolerant watermark can carry a few bits and survive processing, but it cannot carry a cryptographic digest: one flipped bit makes the digest meaningless. Exactness is what turns the visible seal into a verifier of the signed bytes. The price is fragility—the mark dies under any change, including innocent re-serialisation—and the paper makes that price explicit rather than hiding it behind a robustness claim.

What the carrier adds. With capacity and distortion held fixed, the generic polyline and the grid recover the payload as reliably as the incidence configuration (Table V). The difference is the geometric invariant: the incidence construction fixes the triangle centres, so a centre-line edit outside the payload slots is detected even before the digest comparison.

What the baselines show. STDM and Fourier-descriptor embedding reach 140 and 13 bits on the same carrier at higher distortion; LSB reaches 27 bits at negligible distortion but is destroyed by 8-decimal re-serialisation.

VIII. ATTACK MATRIX AND SECURITY DISCUSSION

The construction authenticates the rendering layer, not the cryptographic signature (Tables X and XI). It does not prevent an attacker from producing a new document with a new valid seal; it makes a transplanted or edited

TABLE VII
INDEPENDENT PUBLIC NIST ANCHORS: PER-DOCUMENT EXACTNESS AND GEOMETRIC DISTORTION (10 SEEDS EACH).

Document (NIST)	Pages	Exact	RMSE (nm)
FIPS 186-5	86	100%	5.41
FIPS 180-4	36	100%	5.15
FIPS 202	37	100%	5.01
SP 800-57 Pt. 1 Rev. 5	171	100%	5.32
FIPS 140-3	11	100%	5.34

TABLE VIII
PHYSICAL CAPTURE RESULTS.

Sample	Result
Digital control (stamped PDF)	5/5 valid, exact
Physical capture (print + 300 dpi scan)	5/5 absent (fail-closed)

seal detectable relative to a known document digest. The recipient channel provides attribution for a leaked copy; it is not a collusion-resistant fingerprinting code, and traitor-tracing security is not claimed.

A. Assumptions and claims

A1: the verifier knows the canonical seal geometry for the document class. *A2*: the document digest is known or can be recomputed from the signed bytes. *A3*: the key is secret. *A4*: the post-sealing pipeline preserves at least nine decimal places.

P1 (payload-edit detection): changing any payload slot changes the recovered word, because the lattice step exceeds the rounding error by a factor of two and the digest is compared bit for bit. *P2 (fail-closed)*: if the carrier path is absent, the verifier returns *absent*. *P3 (attribution)*: with the key, the recovered recipient word equals the embedded word; without the key, the recovered words are unpredictable to the adversary. These are watermarking claims, not cryptographic reductions: the paper does not claim that an adversary cannot produce a new document with a new valid seal, and it does not claim collusion resistance of the recipient channel.

IX. THREATS TO VALIDITY

Internal validity. Exactness is deterministic by construction, so the zero-width confidence intervals do not measure real-world variability; the meaningful variation must come from document generators, production PDF writers and physical capture, which this draft only partially exercises.

External validity. The corpus is synthetic and generated by three pipelines on one machine; real documents pass through enterprise DMS flattening, print-to-PDF converters, optimisers and archival re-writers whose coordinate serialisation differs. The 8-decimal precondition is a filter that such pipelines may fail.

TABLE IX
SAME-CARRIER BASELINES: STDM/FOURIER/LSB AT PDF LEVEL (600 SAMPLES), DE-RDH FROM THE SLOT-LEVEL RUN.

Method	Capacity	RMSE (pt)	Exact	Exact at 8 dec.
Proposed (keyed QIM)	266	5.31×10^{-6}	100%	100%
STDM-DCT	140	6.16×10^{-5}	100%	100%
Fourier descriptors	13	7.27×10^{-5}	100%	100%
LSB-RDH	27	7.03×10^{-10}	100%	0%
DE-RDH	0	2.91×10^{-10}	n/a	n/a

TABLE X
ATTACK MATRIX.

Attack	Expected outcome	Measured
Payload-coordinate edit	digest changes, detected	100%
Centre-line edit	geometry invariant fails	100% (incidence only)
8-decimal re-serialisation	digest unchanged	100% exact
7-decimal re-serialisation	digest changes, detected	100%
Flattening	carrier absent, fail-closed	100% absent
Seal transplant	digest mismatch	by construction

Construct validity. The baselines share the carrier and the distortion metric but not the PDF-level embedding code of the proposed method, which favours the proposed method on implementation maturity; the PDF-level baseline re-runs reduce but do not remove this gap.

Conclusion validity. The comparisons are exact-match and distortion measurements with 30 seeds; they are not hypothesis tests about a population of documents.

X. ETHICAL CONSIDERATIONS

The method is intended for document integrity and leak attribution in lawful workflows. Its recipient channel is an attribution mechanism, not a surveillance mechanism. The evaluation uses synthetic documents and public project plus independent public documents only; no client data and no personal data are processed. A deployment must disclose recipient marking to the parties where the applicable law requires it.

XI. REPRODUCIBILITY AND DECLARATIONS

The corpus builder, carrier layer, attack harness and baseline implementations are versioned with the manuscript; the corpus manifest records a SHA-256 per file and the corpus is regenerated deterministically from a seed. The measured tables are produced by the harness. Code and the corpus manifest are available from the

TABLE XI
ATTACK TAXONOMY AND RESIDUAL RISK.

Class	Capability	Detection / residual risk
Stream edit	rewrite path or text	digest mismatch; geometry invariant
Precision loss	re-serialise with $d \leq 7$ decimals	digest mismatch; fail-closed if path lost
Geometric edit	move a non-payload coordinate	incidence invariant (Sri Yantra only)
Rasterisation	flatten or print-scan	carrier absent, fail-closed; optical channel out of scope
Seal transplant	paste a seal from another document	digest mismatch
Redistribution	forward a sealed copy	recipient word attribution

author; the corpus is regenerated by the provided script. Earlier editions of this line are cited in [3]. Competing interests: none. Funding: none. The method is covered by a pending Ukrainian patent application (a 2026 06266).

A. Controlled verification

A controlled run accompanies the implementation. It executes 43 tests covering the word map (with known-answer vectors), the P1 and P2 stamp profiles, truncation and single-coordinate edits, rasterisation, wrong-profile rejection, reserved-zone templates (no text overlap), corpus manifest hashes and the physical print-scan results; the seal-path modules reach 85.0% branch coverage (pdf_layer 72.3%, profiles 93.7%, harness 80.5%). The word map is cross-verified against an independent JavaScript implementation and against the production signer (1024/1024 words), and a 12-sample cross-validation matrix (2 profiles $\times$ 3 documents $\times$ 2 seeds) reproduces exactness, 8-decimal survival, 7-decimal and single-coordinate detection, the geometric invariant and fail-closed rasterisation, with the same matrix hash across two independent runs. For placement, the paper profile uses a fixed region; a reserved-area template keeps the stamp out of body text (tested on generated documents), without any change to the cryptographic logic.

XII. Failure Modes in Deployment

Three failure modes follow directly from the design. (i) *Precision loss:* any pipeline stage that re-writes coordinates with fewer than eight decimals destroys the word; the verifier fails closed. (ii) *Rasterisation:* flattening removes the vector layer; the verifier reports absent. (iii) *Seal regeneration:* if a verifier is given a new document and a new valid seal, the method has nothing to compare against; it authenticates a seal relative to a known document digest, not the identity of a signer.

XIII. Future Work

Three directions follow. First, the carrier can be tested against production document-management pipelines that re-write coordinates, which quantifies the eight-decimal precondition on real enterprise documents beyond the five printed samples. Second, the recipient channel can be extended beyond 1,024 copies per key epoch at a known capacity cost. Third, a broader multi-vendor corpus (different printer/scanner pairs) would map the optical failure envelope; the physical capture reported here covers one multifunction device, not a population study.

XIV. Limitations and Conclusion

The evaluation is a first harness result. STDM, Fourier-descriptor and LSB baselines are re-implemented at both slot and PDF level; DE-RDH is capacity-limited to zero pairs on this carrier and is reported from the slot-level run. The print-scan variant is simulated, and the physical check covers five documents on one multifunction device, not a population of printer/scanner pairs; the corpus is synthetic and the public anchors include ten project documents and five independent NIST standards, not a population of enterprise DMS pipelines; and exactness is deterministic, so the reported confidence intervals are not informative about real-world variability. Capacity numbers are per seal, not per document area. Within these limits the result is consistent and reproducible: 1,800 PDF-level samples recover the 266-bit payload exactly, 8-decimal re-serialisation is safe, 7-decimal re-serialisation and any payload edit are detected, flattening fails closed, and five physical captures reproduce the fail-closed behaviour.

Appendix A
Proof Details

Lemma 1 (the word map is a bijection). Write $\delta(w) = (18w - 9207) \times 10^{-9}$. For integer w the values are distinct because $18w$ is strictly increasing; neighbouring words differ by exactly 18×10^{-9} pt. The decoder computes $n = \mathrm{round}(\delta \cdot 10^9) = 18w - 9207$ exactly while the coordinate error is below 0.5×10^{-9} pt; then $\mathrm{round}((n + 9207)/18) = w$.

Lemma 2 (eight decimals are sufficient). Rounding a real coordinate x to d decimal places yields $|x - \mathrm{round}_d(x)| \leq 0.5 \times 10^{-d}$ pt. For $d = 8$ this is at most

TABLE XII
SYNTHETIC CORPUS COMPOSITION (THREE VARIANTS PER DOCUMENT).

Generator	Files	Pages	Size (MB)
LibreOffice DOCX to PDF	60	80	18.4
Typst	60	80	20.3
Chromium print-to-PDF	60	60	12.5
Total	180	220	51.1

TABLE XIII
FIXED IMPLEMENTATION PARAMETERS.

Parameter	Value
Carrier slots	27 (9 triangles $\times$ 3)
Payload	256-bit digest + 10-bit recipient word = 266 bits
Lattice step	18 npt $\approx 1.8 \times 10^{-8}$ pt
Maximum coordinate shift	9.207×10^{-6} pt
Capacity per seal	270 bits
Stamp time / verify time	1.05 ms / 0.33 ms per page
Reserved seal region	fixed bottom-right, template-tested
Required writer precision	≥ 8 decimals (9 recommended)

5×10^{-9} pt, while half the lattice step is 9×10^{-9} pt; the decoder returns the same word. For $d = 7$ the bound is 5×10^{-8} pt, above half a step, so adjacent words can be confused.

APPENDIX B
GENERATOR SETTINGS

The corpus is generated with LibreOffice headless (DOCX to PDF, default settings), Typst (A4, 2.2 cm margins) and Chromium print-to-PDF (headless, no header/footer). Flattening uses a 300 dpi raster; the print-scan simulation uses 200 dpi, a Gaussian blur, additive Gaussian sensor noise and JPEG quality 70. All settings are recorded in the corpus builder so the corpus can be regenerated from the published script and seed.

APPENDIX C
DATASET COMPOSITION AND IMPLEMENTATION PARAMETERS

Table XII summarises the synthetic corpus by generator; each generator contributes 60 documents in three variants (native, flattened, print-scan-simulated), giving 180 PDFs and 220 pages. Table XIII lists the fixed implementation parameters used in every sample.

APPENDIX D
REPRODUCTION PROTOCOL

All measured tables are produced by the harness in the released repository. The controlled environment used for this paper recorded Python 3.13.5, PyMuPDF 1.28.2, Node 22.23.4, Typst 0.15.1 and Linux x86-64; the pinned dependencies are listed in `requirements-dev.txt`. The main artefacts can be regenerated as follows:

```
python3 eval/build_corpus.py --out eval/corpus --s
python3 eval/run_pdf_experiments.py
python3 eval/run_pdf_baselines.py
python3 eval/run_pdf_real.py 10
python3 paper_v3/tests/run_controlled.py
```

The corpus manifest records one SHA-256 per PDF, the real-anchor manifest records the public source URLs and SHA-256 values, and seeds are the integers 0–29 for the main experiment and 0–9 for the anchors. NIST PDFs are not redistributed; they are re-downloadable from the URLs recorded in the manifest. No client personal data are used. The controlled report in `paper_v3/tests/controlled_run/` records the environment snapshot, 43-test result, branch coverage and cross-validation matrix hash.

APPENDIX E
BASELINE IMPLEMENTATION DETAILS

All baselines use the same 27-slot carrier, the same unit (page points), the same distortion metric and the same attack harness. STDM-DCT embeds a 140-bit spread-transform sequence on the carrier slots; Fourier-descriptor watermarking embeds 13 bits in the descriptor vector; LSB-RDH embeds 27 bits at negligible distortion and is destroyed by 8-decimal re-serialisation; DE-RDH is capacity-limited to zero pairs on this carrier and is therefore reported from the slot-level run. No baseline number is copied from another paper; the PDF-level table is produced by the released code on the same documents and seeds. This makes the comparison a capacity–distortion–fragility frontier rather than a ranking of full systems, as stated in the main text.

APPENDIX F
DEPLOYMENT AUDIT CHECKLIST

A deployment should also retain the verification report, the document digest and the recipient-key epoch with the signed artefact; these are evidentiary artefacts, not part of the cryptographic signature.

REFERENCES

[1] C. Mainka, V. Mladenov, and S. Rohlmann, "Shadow attacks: Hiding and replacing content in signed pdfs," in *Proceedings 2021 Network and Distributed System Security Symposium*, ser. NDSS 2021. Internet Society, 2021. [Online]. Available: http://dx.doi.org/10.14722/ndss.2021.24117

[2] V. Mladenov, C. Mainka, K. Meyer zu Selhausen, M. Grothe, and J. Schwenk, "1 trillion dollar refund: How to spoof pdf signatures," in *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, ser. CCS '19. ACM, Nov. 2019, pp. 1–14. [Online]. Available: http://dx.doi.org/10.1145/3319535.3339812

TABLE XIV
PRECONDITIONS A DEPLOYMENT MUST AUDIT FOR THE MARK TO REMAIN VERIFIABLE.

Precondition	What to audit	Failure if violated
Writer precision	every pipeline stage preserves ≥ 8 decimal places (9 recommended)	word changes; fail-closed
Verifier parsing	verifier reads the content stream as decimal text, not 32-bit floats	lattice destroyed; absent/mismatch
Page placement	declared seal pages really contain the visible seal	verification fails closed
Rasterisation	document stays vector; no flatten-to-image conversion	carrier absent
Signature	seal is complementary to PAdES/eIDAS, not a replacement	wrong legal/security claim
Recipient channel	10-bit identifier space and key-epoch disclosure are managed	attribution ambiguity

[3] Y. V. Baienko, "Marma-256 (marma-crypto v2.1.0): Sub-micron dithered quantization index modulation, orthogonal subspace multiplexing, universal vector emblems (sri yantra / tryzub / cad), and optical screen-photo ecc for bijective 2d vector graphics watermarking and pades-b-lta authentication over gf(2^257) (dstu 4145-2002)," Zenodo preprint, version 2.1.0-rev1, 2026, concept DOI 10.5281/zenodo.23429017; earlier versions 10.5281/zenodo.23429018, 23436152, 23510005, 23540160; accessed 2026-10-24.

[4] B. Chen and G. Wornell, "Quantization index modulation: a class of provably good methods for digital watermarking and information embedding," *IEEE Transactions on Information Theory*, vol. 47, no. 4, pp. 1423–1443, May 2001. [Online]. Available: http://dx.doi.org/10.1109/18.923725

[5] J. Eggers, R. Bauml, R. Tzschoppe, and B. Girod, "Scalar costa scheme for information embedding," *IEEE Transactions on Signal Processing*, vol. 51, no. 4, pp. 1003–1019, Apr. 2003. [Online]. Available: http://dx.doi.org/10.1109/TSP.2003.809366

[6] F. Perez-Gonzalez, M. Barni, A. Abrardo, and C. Mosquera, "Rational dither modulation: a novel data-hiding method robust to value-metric scaling attacks," in *IEEE 6th Workshop on Multimedia Signal Processing, 2004.* IEEE, 2004, pp. 139–142. [Online]. Available: http://dx.doi.org/10.1109/MMSP.2004.1436443

[7] I. Cox, J. Kilian, F. Leighton, and T. Shamoon, "Secure spread spectrum watermarking for multimedia," *IEEE Transactions on Image Processing*, vol. 6, no. 12, pp. 1673–1687, Dec. 1997. [Online]. Available: http://dx.doi.org/10.1109/83.650120

[8] W. Bender, D. Gruhl, N. Morimoto, and A. Lu, "Techniques for data hiding," *IBM Systems Journal*, vol. 35, no. 3.4, pp. 313–336, 1996. [Online]. Available: http://dx.doi.org/10.1147/sj.353.0313

[9] F. Cayre, C. Fontaine, and T. Furon, "Watermarking security: theory and practice," *IEEE Transactions on Signal Processing*, vol. 53, no. 10, pp. 3976–3987, Oct. 2005. [Online]. Available: http://dx.doi.org/10.1109/TSP.2005.855418

[10] J. Yang and S. Li, "Steganalysis of joint codeword quantization index modulation steganography based on codeword bayesian network," *Neurocomputing*, vol. 313, pp. 316–323, Nov. 2018. [Online]. Available: http://dx.doi.org/10.1016/j.neucom.2018.06.005

[11] J. Tian, "Reversible data embedding using a difference expansion," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 13, no. 8, pp. 890–896, Aug. 2003. [Online]. Available: http://dx.doi.org/10.1109/TCSVT.2003.815962

[12] Z. Ni, Y.-Q. Shi, N. Ansari, and W. Su, "Reversible data hiding," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 16, no. 3, pp. 354–362, Mar. 2006. [Online]. Available: http://dx.doi.org/10.1109/TCSVT.2006.869964

[13] D. M. Thodi and J. J. Rodriguez, "Expansion embedding techniques for reversible watermarking," *IEEE Transactions on Image Processing*, vol. 16, no. 3, pp. 721–730, Mar. 2007. [Online]. Available: http://dx.doi.org/10.1109/TIP.2006.891046

[14] N. Wang, H. Zhang, and C. Men, "A high capacity reversible data hiding method for 2d vector maps based on virtual coordinates," *Computer-Aided Design*, vol. 47, pp. 108–117, Feb. 2014. [Online]. Available: http://dx.doi.org/10.1016/j.cad.2013.10.005

[15] F. Peng, Z.-X. Lin, X. Zhang, and M. Long, "Reversible data hiding in encrypted 2d vector graphics based on reversible mapping model for real numbers," *IEEE Transactions on Information Forensics and Security*, vol. 14, no. 9, pp. 2400–2411, Sep. 2019. [Online]. Available: http://dx.doi.org/10.1109/TIFS.2019.2899520

[16] V. R. Doncel, N. Nikolaidis, and I. Pitas, "An optimal detector structure for the fourier descriptors domain watermarking of 2d vector graphics," *IEEE Transactions on Visualization and Computer Graphics*, vol. 13, no. 5, pp. 851–863, Sep. 2007. [Online]. Available: http://dx.doi.org/10.1109/TVCG.2007.1050

[17] Y. Li and L. Xu, "A blind watermarking of vector graphics images," in *Proceedings Fifth International Conference on Computational Intelligence and Multimedia Applications. ICCIMA 2003*, ser. ICCIMA-03. IEEE Comput. Soc, 2003, pp. 424–429. [Online]. Available: http://dx.doi.org/10.1109/ICCIMA.2003.1238163

[18] H. Hou, J. Li, J. Qi, and J. Guo, "A blind watermarking for 2d-vector engineering graphics," *Information Technology Journal*, vol. 13, no. 5, pp. 869–873, Feb. 2014. [Online]. Available: http://dx.doi.org/10.3923/itj.2014.869.873

[19] M. R. Mouhamed, A. M. Rashad, and A. ella Hassanien, "Blind 2d vector data watermarking approach using random table and polar coordinates," in *2012 2nd International Conference on Uncertainty Reasoning and Knowledge Engineering*. IEEE, Aug. 2012, pp. 67–70. [Online]. Available: http://dx.doi.org/10.1109/URKE.2012.6319586

[20] R. Ohbuchi, H. Ueda, and S. Endoh, "Watermarking 2d vector maps in the mesh-spectral domain," in *2003 Shape Modeling International.*, ser. SMI-03. IEEE Comput. Soc, 2003, pp. 216–225. [Online]. Available: http://dx.doi.org/10.1109/SMI.2003.1199619

[21] M. W. Hatoum, R. Darazi, and J.-F. Couchot, "Blind pdf document watermarking robust against pca and ica attacks," in *Proceedings of the 15th International Joint Conference on e-Business and Telecommunications*. SCITEPRESS - Science and Technology Publications, 2018, pp. 420–427. [Online]. Available: http://dx.doi.org/10.5220/0006899604200427

[22] D. He and Q. Sun, "A practical print-scan resilient watermarking scheme," in *IEEE International Conference on Image Processing 2005*. IEEE, 2005, pp. I–257. [Online]. Available: http://dx.doi.org/10.1109/ICIP.2005.1529736

[23] S. Rohlmann, V. Mladenov, C. Mainka, and J. Schwenk, "Breaking the specification: Pdf certification," in *2021 IEEE Symposium on Security and Privacy (SP)*. IEEE, May 2021, pp. 1485–1501. [Online]. Available: http://dx.doi.org/10.1109/SP40001.2021.00110

[24] J. Müller, F. Ising, V. Mladenov, C. Mainka, S. Schinzel, and J. Schwenk, "Practical decryption exfiltration: Breaking pdf encryption," in *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, ser. CCS '19. ACM, Nov. 2019, pp. 15–29. [Online]. Available: http://dx.doi.org/10.1145/3319535.3354214

[25] ISO, "Document management — portable document format — part 2: Pdf 2.0," ISO 32000-2:2020, 2020.

[26] ETSI, "Electronic signatures and infrastructures (esi); pades digital signatures; part 1: Building blocks and pades baseline signatures," ETSI EN 319 142-1 V1.1.1, 2016.

[27] European Parliament and Council, "Regulation (eu) no 910/2014 on electronic identification and trust services for electronic transactions in the internal market (eidas), as amended by regulation

(eu) 2024/1183," Official Journal of the European Union L 257, 2014.

[28] A. P. Kulaichev, "Sriyantra and its mathematical properties," *Indian Journal of History of Science*, vol. 19, no. 3, pp. 279–292, 1984. [Online]. Available: https://insa.nic.in/writereaddata/UpLoadedFiles/IJHS/Vol19_3_7_APKulaichev.pdf

[29] G. Huet, "Śrı yantra geometry," *Theoretical Computer Science*, vol. 281, no. 1-2, pp. 609–628, Jun. 2002. [Online]. Available: http://dx.doi.org/10.1016/S0304-3975(02)00028-2

[30] J. Richter-Gebert, *Perspectives on Projective Geometry: A Guided Tour Through Real and Complex Geometry*. Heidelberg: Springer, 2011.

[31] J.-M. Muller, N. Brunie, F. de Dinechin, C.-P. Jeannerod, M. Joldes, V. Lefèvre, G. Melquiond, N. Revol, and S. Torres, *Handbook of Floating-Point Arithmetic*, 2nd ed. Birkhäuser, 2018.

[32] D. Catalano and D. Fiore, *Vector Commitments and Their Applications*. Springer Berlin Heidelberg, 2013, pp. 55–72. [Online]. Available: http://dx.doi.org/10.1007/978-3-642-36362-7_5

[33] B. Libert, S. C. Ramanna, and M. Yung, "Functional commitment schemes: From polynomial commitments to pairing-based accumulators from simple assumptions," in *43rd International Colloquium on Automata, Languages, and Programming (ICALP 2016)*, ser. LIPIcs, vol. 55, 2016, pp. 30:1–30:14.

[34] D. Boneh and M. Franklin, *An Efficient Public Key Traitor Tracing Scheme*. Springer Berlin Heidelberg, 1999, pp. 338–353. [Online]. Available: http://dx.doi.org/10.1007/3-540-48405-1_22

[35] G. Tardos, "Optimal probabilistic fingerprint codes," *Journal of the ACM*, vol. 55, no. 2, pp. 1–24, May 2008. [Online]. Available: http://dx.doi.org/10.1145/1346330.1346335

[36] I. J. Cox, M. L. Miller, J. A. Bloom, J. Fridrich, and T. Kalker, *Digital Watermarking and Steganography*, 2nd ed. Morgan Kaufmann, 2008.