

**PEMROSESAN PARALEL**  
**“MPI”**




**Disusun oleh :**

Nama : Ahmad Gimnastiar  
NIM : 09011282126050  
Kelas : SK5B Indralaya  
Dosen Pengampuh : Adi Hermansyah, S.Kom., M.T

**FAKULTAS ILMU KOMPUTER**  
**JURUSAN SISTEM KOMPUTER**  
**UNIVERSITAS SRIWIJAYA**  
**TAHUN 2023/2024**

## 1. Konfigurasi Hosts


MASTER



```
mpi@master: ~  
File Edit View Search Terminal Help  
GNU nano 6.2 /etc/hosts *  
127.0.0.1 localhost  
127.0.1.1 yarrzeee-VirtualBox  
  
192.168.1.7 master  
192.168.1.12 worker1  
192.168.1.10 worker2  
# The following lines are desirable for IPv6 capable hosts  
::1 ip6-localhost ip6-loopback  
fe00::0 ip6-localnet  
ff00::0 ip6-mcastprefix  
ff02::1 ip6-allnodes  
ff02::2 ip6-allrouters  
  
^G Help ^O Write Out ^W Where Is ^K Cut ^T Execute ^C Location  
^X Exit ^R Read File ^\ Replace ^U Paste ^J Justify ^_ Go To Line
```

WORKER

Pada konfigurasi worker cukup isi dengan ip master dengan ip worker itu sendiri



```
mpi@worker1: ~  
File Edit View Search Terminal Help  
GNU nano 6.2 /etc/hosts  
127.0.0.1 localhost  
127.0.1.1 yarrzeee-VirtualBox  
  
192.168.1.7 master  
192.168.1.12 worker1  
# The following lines are desirable for IPv6 capable hosts  
::1 ip6-localhost ip6-loopback  
fe00::0 ip6-localnet  
ff00::0 ip6-mcastprefix  
ff02::1 ip6-allnodes  
ff02::2 ip6-allrouters  
  
[ Read 11 lines ]  
^G Help ^O Write Out ^W Where Is ^K Cut ^T Execute ^C Location  
^X Exit ^R Read File ^\ Replace ^U Paste ^J Justify ^_ Go To Line
```

## 2. Create User MPI

MASTER & WORKER

```
sudo adduser mpi
```

## 3. Kasih Akses Root ke User

MASTER & WORKER

```
sudo usermod -aG sudo mpi
```

## 4. Masuk ke User

MASTER & WORKER

```
su - mpi
```

## 5. Konfigurasi SSH

MASTER & WORKER

Sebelum melakukan konfigurasi SSH, install openssh-server terlebih dahulu

```
sudo apt install openssh-server
```

Untuk melakukan pengecekan SSH, lakukan command berikut.

```
MASTER : ssh mpi@worker  
WORKER : ssh mpi@master
```

Jika telah berganti user maka ssh telah tersambung. Untuk kembali ke user awal cukup lakukan perintah "exit".

## 6. Generate Keygen

MASTER

```
ssh-keygen -t rsa
```

## 7. Copy Keygen ke Worker

MASTER

```
cd .ssh  
cat id_rsa.pub | ssh mpi@worker "mkdir .ssh; cat >> .ssh/authorized_keys"
```

## 8. Create Shared Folder

MASTER & WORKER

```
cd  
mkdir cloud
```


## 9. Konfigurasi NFS

MASTER

Lakukan installasi NFS Server terlebih dahulu

```
sudo apt install nfs-kernel-server
```

Kemudian tambahkan “/home/mpi/cloud \*(rw,sync,no\_root\_squash,no\_subtree\_check)” pada file “/etc/exports”

A screenshot of a terminal window titled 'mpi@master: ~'. The terminal shows the 'nano' text editor editing the '/etc/exports' file. The file content includes comments about NFSv2, NFSv3, and NFSv4, and a line at the bottom: '/home/mpi/cloud \*(rw,sync,no\_root\_squash,no\_subtree\_check)'. The bottom status bar of the nano editor shows '[ Read 11 lines ]' and various keyboard shortcuts like '^G Help', '^O Write Out', etc.

```
mpi@master: ~
File Edit View Search Terminal Help
GNU nano 6.2 /etc/exports
# /etc/exports: the access control list for filesystems which may be exported
# to NFS clients.  See exports(5).
#
# Example for NFSv2 and NFSv3:
# /srv/homes hostname1(rw,sync,no_subtree_check) hostname2(ro,sync,no_subtree_check)
#
# Example for NFSv4:
# /srv/nfs4 gss/krb5i(rw,sync,fsid=0,crossmnt,no_subtree_check)
# /srv/nfs4/homes gss/krb5i(rw,sync,no_subtree_check)
#
/home/mpi/cloud *(rw,sync,no_root_squash,no_subtree_check)

[ Read 11 lines ]
^G Help  ^O Write Out  ^W Where Is  ^K Cut       ^T Execute   ^C Location
^X Exit  ^R Read File  ^\ Replace   ^U Paste     ^J Justify   ^_ Go To Line
```

Kemudian lakukan export dan restart nfs

```
sudo exportfs -a
sudo systemctl restart nfs-kernel-server
```

## 10. Konfigurasi NFS Client

WORKER

```
sudo apt install nfs-common
```

## 11. Mounting

WORKER

```
sudo mount master:/home/mpi/cloud /home/mpi/cloud
```

```
mpi@worker1:~$ cd cloud
mpi@worker1:~/cloud$ ls
mpi@worker1:~/cloud$ cd
mpi@worker1:~$ sudo mount master:/home/mpi/cloud /home/mpi/cloud
mpi@worker1:~$ cd cloud
mpi@worker1:~/cloud$ ls
bubblesort.py  contoh.py  numerik.py  test  test.py
mpi@worker1:~/cloud$
```

## 12. Install MPI

MASTER & WORKER

```
sudo apt install openmpi-bin libopenmpi-dev
```

## 13. Bubble Sort

MASTER

```
from mpi4py import MPI

def bubble_sort_parallel(data):
    comm = MPI.COMM_WORLD
    rank = comm.Get_rank()
    size = comm.Get_size()

    local_data = data[rank::size]
    local_data.sort()

    for step in range(1, size):
        if rank % 2 == 0:
            if rank < size - 1:
                comm.send(local_data, dest=rank+1)
                received_data = comm.recv(source=rank+1)
                local_data = merge(local_data, received_data)
            else:
                comm.send(local_data, dest=rank-1)
                received_data = comm.recv(source=rank-1)
                local_data = merge(local_data, received_data)

        sorted_data = comm.gather(local_data, root=0)
        if rank == 0:
            sorted_data = merge_sorted_arrays(sorted_data)
            return sorted_data
    else:
```

```

        return None

def merge(arr1, arr2):
    merged_array = []
    i = j = 0
    while i < len(arr1) and j < len(arr2):
        if arr1[i] < arr2[j]:
            merged_array.append(arr1[i])
            i += 1
        else:
            merged_array.append(arr2[j])
            j += 1
    merged_array.extend(arr1[i:])
    merged_array.extend(arr2[j:])
    return merged_array

def merge_sorted_arrays(arrays):
    merged_array = []
    for array in arrays:
        merged_array = merge(merged_array, array)
    return merged_array

if __name__ == "__main__":
    data = [5, 2, 9, 1, 5, 6]
    comm = MPI.COMM_WORLD
    rank = comm.Get_rank()

    if rank == 0:
        sorted_data = bubble_sort_parallel(data)
        print("Sorted Data:", sorted_data)
    else:
        bubble_sort_parallel(data)

```

```

mpi@master:~/cloud$ python3 bubblesort.py
Authorization required, but no authorization protocol specified
Authorization required, but no authorization protocol specified
Authorization required, but no authorization protocol specified
Data: [5, 2, 9, 1, 5, 6]
Sorted Data: [1, 2, 5, 5, 6, 9]
Execution Time: 0.0001556873321533203 s
mpi@master:~/cloud$ mpirun -n 1 python3 bubblesort.py
Authorization required, but no authorization protocol specified
Authorization required, but no authorization protocol specified
Data: [5, 2, 9, 1, 5, 6]
Sorted Data: [1, 2, 5, 5, 6, 9]
Execution Time: 0.00011324882507324219 s
mpi@master:~/cloud$

```

Untuk waktu eksekusi MPI lebih cepat 0.00004243850708007811 dari eksekusi python direct.

## 14. Numerik

MASTER

```
from mpi4py import MPI
import time

start = time.time()

def main():
    comm = MPI.COMM_WORLD
    rank = comm.Get_rank()
    size = comm.Get_size()

    # Data yang akan dihitung
    data = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

    # Bagi data di antara proses
    chunk_size = len(data) // size
    start = rank * chunk_size
    end = (rank + 1) * chunk_size

    if rank == size - 1:
        # Pastikan semua data terhitung jika panjang data tidak habis dibagi
        # oleh jumlah proses
        end = len(data)

    local_sum = sum(data[start:end])

    # Kumpulkan hasil dari semua proses
    total_sum = comm.reduce(local_sum, op=MPI.SUM, root=0)

    if rank == 0:
        print("Total hasil perhitungan:", total_sum)

if __name__ == '__main__':
    main()
end = time.time()
print("waktu dikerjakan", end-start)
```

```
mpi@master:~/cloud$ python3 numerik.py
Authorization required, but no authorization protocol specified
Authorization required, but no authorization protocol specified
Authorization required, but no authorization protocol specified
Total hasil perhitungan: 55
waktu dikerjakan 0.0003948211669921875
mpi@master:~/cloud$ mpirun -n 1 python3 numerik.py
Authorization required, but no authorization protocol specified
Authorization required, but no authorization protocol specified
Total hasil perhitungan: 55
waktu dikerjakan 0.00038170814514160156
mpi@master:~/cloud$
```

Untuk waktu eksekusi MPI lebih cepat 0.00001311302185058594 dari eksekusi python direct.