RStudio Pro

Go to file/function | Addins | Posit Assistant | Project: (None)

EX-5.R | EX-6.R | EX-7.R | EX-8.R | EX-9.R | EX-10.R

Source on Save | Run | Source

```r
exam_data <- data.frame(
  name = c("John", "Mary", "David", "Alice"),
  score = c(85, 72, 90, 65),
  attempts = c(1, 2, 1, 3),
  qualifying = c(TRUE, TRUE, TRUE, FALSE)
)

print("Exam Data:")
print(exam_data)

print("Names:")
print(exam_data$name)

print("Second Row:")
print(exam_data[2, ])

print("Score of John:")
print(exam_data[1, "score"])

new_row <- data.frame(
  name = "Robert"
```

19:1 (Top Level) R Script

Console | Terminal | Background Jobs

R 4.6.1 · ~/

```
> source("~/Desktop/EX-10.R")
[1] "Exam Data:"
   name score attempts qualifying
1  John    85        1       TRUE
2  Mary    72        2       TRUE
3 David    90        1       TRUE
4 Alice    65        3      FALSE
[1] "Names:"
[1] "John"  "Mary"  "David" "Alice"
[1] "Second Row:"
  name score attempts qualifying
2 Mary    72        2       TRUE
[1] "Score of John:"
[1] 85
[1] "After Adding New Row:"
```

Environment | History | Connections | Tutorial

Import Dataset | 120 MiB | List

R | Global Environment

Values

arr	int [1:2, 1:3, 1:2] 1 2 3 4 5 6 7 8 9 10 ...
count	'table' int [1:37(1d)] 1 2 2 2 2 1 3 1 2 2 ...
factors	int [1:2] 1 2
height	num [1:15] 58 59 60 61 62 63 64 65 66 67 ...
height_factor	Factor w/ 15 levels "58","59","60",..: 1 2 3 4 5…
i	2L
letter_factor	Factor w/ 10 levels "C","K","O","P",..: 6 7 10 4…
letters_sample	chr [1:10] "S" "U" "Y" "P" "R" "K" "X" "O" "W" "…

Files | Plots | Packages | Help | Viewer | Presentation

Zoom | Export | Publish

