RStudio Pro

Go to file/function | Addins | Posit Assistant | Project: (None)

EX-1.R | EX-2.R

Source on Save | Run | Source

```r
matrix_5x4_row <- matrix(1:20, nrow = 5, ncol = 4, byrow = TRUE)
rownames(matrix_5x4_row) <- paste0("R", 1:5)
colnames(matrix_5x4_row) <- paste0("C", 1:4)

print("5 x 4 Matrix - Filled by Row")
print(matrix_5x4_row)

matrix_3x3_col <- matrix(1:9, nrow = 3, ncol = 3, byrow = FALSE)
rownames(matrix_3x3_col) <- paste0("R", 1:3)
colnames(matrix_3x3_col) <- paste0("C", 1:3)

print("3 x 3 Matrix - Filled by Column")
print(matrix_3x3_col)

matrix_2x2_row <- matrix(1:4, nrow = 2, ncol = 2, byrow = TRUE)
rownames(matrix_2x2_row) <- paste0("R", 1:2)
colnames(matrix_2x2_row) <- paste0("C", 1:2)

print("2 x 2 Matrix - Filled by Row")
print(matrix_2x2_row)
```

19:1 (Top Level) R Script

Console | Terminal | Background Jobs

R 4.6.1 · ~/

```
[1] "5 x 4 Matrix - Filled by Row"
   C1 C2 C3 C4
R1  1  2  3  4
R2  5  6  7  8
R3  9 10 11 12
R4 13 14 15 16
R5 17 18 19 20
[1] "3 x 3 Matrix - Filled by Column"
   C1 C2 C3
R1  1  4  7
R2  2  5  8
R3  3  6  9
[1] "2 x 2 Matrix - Filled by Row"
   C1 C2
```

Environment | History | Connections | Tutorial

Import Dataset | 138 MiB | List

R | Global Environment

Data

matrix_2x2_row	int [1:2, 1:2] 1 3 2 4
matrix_3x3_col	int [1:3, 1:3] 1 2 3 4 5 6 7 8 9
matrix_5x4_row	int [1:5, 1:4] 1 5 9 13 17 2 6 10 14 18 ...

Files | Plots | Packages | Help | Viewer | Presentation

Folder | File | Delete | Rename

Home

Name	Size	Modified
.Rhistory	54 B	30 Sept 2026, 14:48
Applications		
Desktop		
Documents		
Downloads		
Library		
Movies		
Music		
Pictures		
Public		