RStudio Pro

Go to file/function | Addins | Posit Assistant | Project: (None)

EX-1.R | EX-2.R | EX-3.R | EX-4.R

Source on Save | Run | Source

```
1  v <- 1:12
2
3  arr <- array(v, dim = c(2, 3, 2))
4
5  dimnames(arr) <- list(
6    Rows = c("R1", "R2"),
7    Columns = c("C1", "C2", "C3"),
8    Tables = c("T1", "T2")
9  )
10
11 print("Array:")
12 print(arr)
13
14 print("Specific elements:")
15
16 print(arr["R1", "C2", "T1"])
17 print(arr["R2", "C3", "T2"])
```

13:1 (Top Level) R Script

Console | Terminal | Background Jobs

R 4.6.1 · ~/

```
  R1  1  3  5
  R2  2  4  6

, , Tables = T2

    Columns
Rows C1 C2 C3
  R1  7  9 11
  R2  8 10 12

[1] "Specific elements:"
[1] 3
[1] 12
>
```

Environment | History | Connections | Tutorial

Import Dataset | 90 MiB | List

R | Global Environment

Data	
matrix_2x2_row	int [1:2, 1:2] 1 3 2 4
matrix_3x3_col	int [1:3, 1:3] 1 2 3 4 5 6 7 8 9
matrix_5x4_row	int [1:5, 1:4] 1 5 9 13 17 2 6 10 14 18 ...
Values	
arr	int [1:2, 1:3, 1:2] 1 2 3 4 5 6 7 8 9 10 ...
v	int [1:12] 1 2 3 4 5 6 7 8 9 10 ...

Files | Plots | Packages | Help | Viewer | Presentation

Folder | File | Delete | Rename

Home

Name	Size	Modified
.Rhistory	54 B	30 Sept 2026, 14:48
Applications		
Desktop		
Documents		
Downloads		
Library		
Movies		
Music		
Pictures		
Public		