RStudio Pro

Go to file/function | Addins | Posit Assistant | Project: (None)

EX-1.R | EX-2.R | EX-3.R | EX-4.R | EX-5.R | EX-6.R

Source on Save | Run | Source

```
1  v <- c(10, 20, 30, 40, 50)
2
3  m <- matrix(1:9, nrow = 3, ncol = 3)
4
5  add_numbers <- function(a, b) {
6    return(a + b)
7  }
8
9  my_list <- list(
10   Vector = v,
11   Matrix = m,
12   Function = add_numbers
13 )
14
15 print("Complete List:")
16 print(my_list)
17
18 print("Vector:")
19 print(my_list$Vector)
20
```

26:1 (Top Level) R Script

Console | Terminal | Background Jobs

R 4.6.1 · ~/

```
[1] "Vector:"
[1] 10 20 30 40 50
[1] "Matrix:"
     [,1] [,2] [,3]
[1,]    1    4    7
[2,]    2    5    8
[3,]    3    6    9
[1] "Function:"
function(a, b) {
  return(a + b)
}
[1] "Function Result:"
[1] 30
>
```

Environment | History | Connections | Tutorial

Import Dataset | 65 MiB | List

R | Global Environment

my_list	List of 3
Values	
arr	int [1:2, 1:3, 1:2] 1 2 3 4 5 6 7 8 9 10 ...
height	num [1:15] 58 59 60 61 62 63 64 65 66 67 ...
height_factor	Factor w/ 15 levels "58","59","60",..: 1 2 3 4 5…
letter_factor	Factor w/ 10 levels "C","K","O","P",..: 6 7 10 4…
letters_sample	chr [1:10] "S" "U" "Y" "P" "R" "K" "X" "O" "W" "…
v	num [1:5] 10 20 30 40 50
Functions	

Files | Plots | Packages | Help | Viewer | Presentation

Folder | File | Delete | Rename

Home

Name	Size	Modified
.Rhistory	54 B	30 Sept 2026, 14:48
Applications		
Desktop		
Documents		
Downloads		
Library		
Movies		
Music		
Pictures		
Public		