RStudio Pro

Go to file/function | Addins | Posit Assistant | Project: (None)

EX-2.R | EX-3.R | EX-4.R | EX-5.R | EX-6.R | EX-7.R*

Source on Save | Run | Source

```
1  n <- as.integer(readline("Enter a number: "))
2
3  factors <- c()
4
5  for (i in 1:n) {
6    if (n %% i == 0) {
7      factors <- c(factors, i)
8    }
9  }
10
11 print("Factors are:")
12 print(factors)
```

1:1 (Top Level) R Script

Console | Terminal | Background Jobs

R 4.6.1 · ~/

```
[1,]    1    4    7
[2,]    2    5    8
[3,]    3    6    9
[1] "Function:"
function(a, b) {
  return(a + b)
}
[1] "Function Result:"
[1] 30
> source("~/Desktop/EX-7.R")
Enter a number: 5
[1] "Factors are:"
[1] 1 5
>
```

Environment | History | Connections | Tutorial

Import Dataset | 71 MiB | List

R | Global Environment

height	num [1:15] 58 59 60 61 62 63 64 65 66 67 ...
height_factor	Factor w/ 15 levels "58","59","60",..: 1 2 3 4 5…
i	5L
letter_factor	Factor w/ 10 levels "C","K","O","P",..: 6 7 10 4…
letters_sample	chr [1:10] "S" "U" "Y" "P" "R" "K" "X" "O" "W" "…
n	5L
v	num [1:5] 10 20 30 40 50
Functions	
add_numbers	function (a, b)

Files | Plots | Packages | Help | Viewer | Presentation

Folder | File | Delete | Rename

Home

	Name	Size	Modified
	.Rhistory	54 B	30 Sept 2026, 14:48
	Applications		
	Desktop		
	Documents		
	Downloads		
	Library		
	Movies		
	Music		
	Pictures		
	Public		