RStudio Pro

Go to file/function | Addins | Posit Assistant | Project: (None)

EX-4.R | EX-5.R | EX-6.R | EX-7.R | EX-8.R | EX-9.R

Source on Save | Run | Source

```
1  plot(
2    0, 0,
3    type = "n",
4    xlim = c(-10, 10),
5    ylim = c(-5, 20),
6    xlab = "X-axis",
7    ylab = "Y-axis",
8    main = "Empty Plot"
9  )
```

5:17 (Top Level) R Script

Console | Terminal | Background Jobs

R 4.6.1 · ~/

```
 [91]  1.226082009  0.846150494  0.424710669  1.641961877 -0.780133470
 [96] -0.830050092  1.031525255  1.561241689 -1.092712368  0.376866281
[1] "Count of occurrences:"
rounded_numbers
-2.9 -2.7 -2.6 -1.9 -1.8 -1.7 -1.6 -1.5 -1.4 -1.1 -0.9 -0.8 -0.7 -0.6 -0.5 -0.4
   1    2    2    2    2    1    3    1    2    2    1    3    5    3    2    5
-0.3 -0.2 -0.1    0  0.1  0.2  0.3  0.4  0.5  0.6  0.7  0.8  0.9    1  1.1  1.2
   2    3    3    5    3    3    6    4    3    3    3    3    1    4    2    2
 1.3  1.4  1.5  1.6  2.2
   4    5    1    2    1
> source("~/.active-rstudio-document")
> source("~/.active-rstudio-document")
> source("~/.active-rstudio-document")
>
```

Environment | History | Connections | Tutorial

Import Dataset | 108 MiB | List

R | Global Environment

i	2L
letter_factor	Factor w/ 10 levels "C","K","O","P",..: 6 7 10 4…
letters_sample	chr [1:10] "S" "U" "Y" "P" "R" "K" "X" "O" "W" "…
n	2L
numbers	num [1:100] -1.38913 -0.67633 -0.05388 0.00587 0…
rounded_numbers	num [1:100] -1.4 -0.7 -0.1 0 0.5 0.7 -1.8 1.1 -1…
v	num [1:5] 10 20 30 40 50
Functions	
add_numbers	function (a, b)

Files | Plots | Packages | Help | Viewer | Presentation

Zoom | Export | Publish

