

COMS 4030A/7047A

Adaptive Computation and Machine Learning

Hima Vadapalli

Semester I, 2022

Recurrent Neural Networks

Slides based heavily on course material by Eric
Eton Andrew Moore and Andrew Ng

Who came up with these?

```
/*
 * Increment the size file of the new incorrect UI_FILTER group information
 * of the size generatively.
 */
static int indicate_policy(void)
{
    int error;
    if (fd == MARN_EPT) {
        /*
         * The kernel blank will coeld it to userspace.
         */
        if (ss->segment < mem_total)
            unblock_graph_and_set_blocked();
        else
            ret = 1;
        goto bail;
    }
    segaddr = in_SB(in.addr);
    selector = seg / 16;
    setup_works = true;
    for (i = 0; i < blocks; i++) {
        seq = buf[i++];
        bpf = bd->bd.next + i * search;
        if (fd) {
            current = blocked;
        }
    }
    rw->name = "Getjbbregs";
    bprm_self_clearl(&iv->version);
    regs->new = blocks[(BPF_STATS << info->historidac)] | PFMR_CLOBATHINC_SECON
    return segtable;
}
```

Who came up with these?

Proof. Omitted. □

Lemma 0.1. *Let \mathcal{C} be a set of the construction.*

Let \mathcal{C} be a gerber covering. Let \mathcal{F} be a quasi-coherent sheaves of \mathcal{O} -modules. We have to show that

$$\mathcal{O}_{\mathcal{O}_X} = \mathcal{O}_X(\mathcal{L})$$

.

Proof. This is an algebraic space with the composition of sheaves \mathcal{F} on $X_{\text{étale}}$ we have

$$\mathcal{O}_X(\mathcal{F}) = \{\text{morph}_{11} \times_{\mathcal{O}_X} (\mathcal{G}, \mathcal{F})\}$$

where \mathcal{G} defines an isomorphism $\mathcal{F} \rightarrow \mathcal{F}$ of \mathcal{O} -modules. □

Lemma 0.2. *This is an integer Z is injective.*

Proof. See Spaces, Lemma ?? □

Lemma 0.3. *Let S be a scheme. Let X be a scheme and X is an affine open covering. Let $\mathcal{U} \subset \mathcal{X}$ be a canonical and locally of finite type. Let X be a scheme. Let X be a scheme which is equal to the formal complex.*

The following to the construction of the lemma follows.

Let X be a scheme. Let X be a scheme covering. Let

$$b : X \rightarrow Y' \rightarrow Y \rightarrow Y \rightarrow Y' \times_X Y \rightarrow X.$$


be a morphism of algebraic spaces over S and Y .

Proof. Let X be a nonzero scheme of X . Let X be an algebraic space. Let \mathcal{F} be a quasi-coherent sheaf of \mathcal{O}_X -modules. The following are equivalent

- (1) \mathcal{F} is an algebraic space over S .
- (2) If X is an affine open covering.

Consider a common structure on X and X the functor $\mathcal{O}_X(U)$ which is locally of finite type. □

This since $\mathcal{F} \in \mathcal{F}$ and $x \in \mathcal{G}$ the diagram



is a limit. Then \mathcal{G} is a finite type and assume S is a flat and \mathcal{F} and \mathcal{G} is a finite type f_* . This is of finite type diagrams, and

- the composition of \mathcal{G} is a regular sequence,
- $\mathcal{O}_{X'}$ is a sheaf of rings.

□

Proof. We have see that $X = \text{Spec}(R)$ and \mathcal{F} is a finite type representable by algebraic space. The property \mathcal{F} is a finite morphism of algebraic stacks. Then the cohomology of X is an open neighbourhood of U . □

Proof. This is clear that \mathcal{G} is a finite presentation, see Lemmas ??.

A reduced above we conclude that U is an open covering of \mathcal{C} . The functor \mathcal{F} is a "field"

$$\mathcal{O}_{X,x} \rightarrow \mathcal{F}_x \rightarrow \mathcal{O}_{X_{\text{étale}}} \rightarrow \mathcal{O}_{X_x}^{-1} \mathcal{O}_{X_x}(\mathcal{O}_{X_y}^y)$$

is an isomorphism of covering of \mathcal{O}_{X_1} . If \mathcal{F} is the unique element of \mathcal{F} such that X is an isomorphism.

The property \mathcal{F} is a disjoint union of Proposition ?? and we can filtered set of presentations of a scheme \mathcal{O}_X -algebra with \mathcal{F} are opens of finite type over S .

If \mathcal{F} is a scheme theoretic image points. □

If \mathcal{F} is a finite direct sum \mathcal{O}_{X_1} is a closed immersion, see Lemma ?? . This is a sequence of \mathcal{F} is a similar morphism.

Who came up with these?

Naturalism and decision for the majority of Arab countries' capitalide was grounded by the Irish language by [[John Clair]], [[An Imperial Japanese Revolt]], associated with Guangzham's sovereignty. His generals were the powerful ruler of the Portugal in the [[Protestant Immineners]], which could be said to be directly in Cantonese Communication, which followed a ceremony and set inspired prison, training. The emperor travelled back to [[Antioch, Perth, October 25|21]] to note, the Kingdom of Costa Rica, unsuccessful fashioned the [[Thrales]], [[Cynth's Dajoard]], known in western [[Scotland]], near Italy to the conquest of India with the conflict. Copyright was the succession of independence in the slop of Syrian influence that was a famous German movement based on a more popular servicious, non-doctrinal and sexual power post. Many governments recognize the military housing of the [[Civil Liberalization and Infantry Resolution 265 National Party in Hungary]], that is sympathetic to be to the [[Punjab Resolution]] (PJS)[<http://www.humah.yahoo.com/guardian.cfm/7754800786d17551963589.htm> Official economics Adjoint for the Nazism, Montgomery was swear to advance to the resources for those Socialism's rule, was starting to signing a major tripad of aid exile.]]

The unreasonable effectiveness of recurrent neural networks..


- All previous examples were *generated* blindly by a *recurrent* neural network..
 - With simple architectures

Modelling Series

- In many situations one must consider a *series* of inputs to produce an output
 - Outputs too may be a series
- Examples: ..

What did I say?

“To be” or not “to be”??



- Speech Recognition
 - Analyze a series of spectral vectors, determine what was said
- Note: Inputs are sequences of vectors. Output is a classification result

What is he talking about?

“Football” or “basketball”?




The Steelers, meanwhile, continue to struggle to make stops on defense. They've allowed, on average, 30 points a game, and have shown no signs of improving anytime soon.



- Text analysis
 - E.g. analyze document, identify topic
 - Input series of words, output classification output
 - E.g. read English, output French
 - Input series of words, output series of words

Should I invest..

To invest or not to invest?




- Note: Inputs are sequences of vectors. Output may be scalar or vector
 - Should I invest, vs. should I not invest in X?
 - Decision must be taken considering how things have fared over time

These are classification and prediction problems



- Consider a sequence of inputs
 - Input vectors
- Produce one or more outputs
 - by memorising what came before

Recurrent Neural Network: A simple state-space model




- The state (green) at any time is determined by the input at that time, and the state at the previous time
- *An input at $t=0$ affects outputs forever*

Single hidden layer RNN




Multiple recurrent layer


RNN




Multiple recurrent layer RNN



- We can also have skips..




Equation




- Note superscript in indexing, which indicates layer of network from which inputs are obtained
- Assuming vector function at output, e.g. softmax
- The *state* node activation, $f_1()$ is typically $\tanh()$
- Every neuron also has a *bias* input

Variants on recurrent nets




- 1: Conventional MLP
- 2: Sequence *generation*, e.g. image to caption
- 3: Sequence based *prediction or classification*, e.g. Speech recognition, text classification

Variants




- 1: *Delayed* sequence to sequence, e.g. machine translation
- 2: Sequence to sequence, e.g. stock problem, label prediction
- Etc...

How do we *train* the network




- Back propagation through time (BPTT)
- Given a collection of *sequence* inputs
 - $(\mathbf{X}_i, \mathbf{D}_i)$, where
 - $\mathbf{X}_i = X_{i,0}, \dots, X_{i,T}$
 - $\mathbf{D}_i = D_{i,0}, \dots, D_{i,T}$
- Train network parameters to minimize the error between the output of the network $\mathbf{Y}_i = Y_{i,0}, \dots, Y_{i,T}$ and the desired outputs
 - This is the most generic setting. In other settings we just “remove” some of the input or output entries

Training the RNN




- The “unrolled” computation is just a giant shared-parameter neural network
 - All columns are identical and share parameters
- Network parameters can be trained via gradient-descent (or its variants) using shared-parameter gradient descent rules
 - Gradient computation requires a forward pass, back propagation, and pooling of gradients (for parameter sharing)

Training: Forward pass



- For each training input:
- Forward pass: pass the entire data sequence through the network, generate outputs

Training: Computing gradients



- For each training input:
- **Backward pass: Compute gradients via backpropagation**
 - *Back Propagation Through Time*