

❗ This quiz has been regraded; your new score reflects 0 questions that were affected.

## Quiz (Week 7a)

- Due Oct 21 at 11:59pm
- Points 4
- Questions 4
- Available Oct 16 at 12am - Oct 21 at 11:59pm
- Time Limit None
- Allowed Attempts Unlimited

This quiz was locked Oct 21 at 11:59pm.

## Attempt History

|        | Attempt                   | Time      | Score      | Regraded   |
|--------|---------------------------|-----------|------------|------------|
| LATEST | <a href="#">Attempt 1</a> | 4 minutes | 3 out of 4 | 4 out of 4 |

Score for this attempt: 4 out of 4

Submitted Oct 21 at 9:14pm

This attempt took 4 minutes.



Question 1

1 / 1 pts

Which of the following events would **not** trigger an exception?

☐ page fault

Correct!

☒ load-to-use stall

☐ undefined opcode

☐ arithmetic overflow



Question 2

1 / 1 pts

What is the best instruction to place into a Branch Delay Slot?

Correct!

☒ An independent instruction from before the branch

☐ An instruction from the target

☐ An instruction from the fall-through



Question 3

1 / 1 pts

Architectures without Branch Delay Slots require pipeline flush logic.

Correct!

☒ True

☐ False



Question 4

Original Score: 0 / 1 pts Regraded Score: 1 / 1 pts

⚠ This question has been regraded.

A 2-bit branch prediction table has an entry currently set to **Strong Predict Not Taken**. The next 5 times a branch executes aliases with the entry, the branch is ultimately taken. How many misses exist in these 5?

☐

☐

☐ 3

Correct!

☒ 2

Quiz Score: 4 out of 4