Loops in JS

Loops are used to execute a piece of code again & again

for Loop

```
for (let i = 1; i <= 5; i++) {
    console.log("apna college");
}
```

Apna College

Loops in JS

Infinite Loop : A Loop that never ends

Apna College

Loops in JS

while Loop

```
while (condition) {

    // do some work

}
```

Apna College

Loops in JS

do-while Loop

```
do {

    // do some work

} while (condition);
```

Apna College

Loops in JS

for-of Loop

```
for (let val of strVar) {

    //do some work

}
```

Apna College

Loops in JS

for-in Loop

```
for (let key in objVar) {

    //do some work

}
```

Apna College

Let‘s Practice

Qs1. Print all even numbers from 0 to 100.

Apna College

Let‘s Practice

Qs2.

Create a game where you start with any random game number. Ask the user to keep guessing the game number until the user enters correct value.

Apna College

Strings in JS

String is a sequence of characters used to represent text

Apna College

Create String

```
let str = “Apna College“;
```

String Length

```
str.length
```

String Indices

```
str[0], str[1], str[2]
```

Template Literals in JS

A way to have embedded expressions in strings

```
`this is a template literal`
```

String Interpolation

To create strings by doing substitution of placeholders

```
`string text ${expression} string text`
```

Apna College

String Methods in JS

These are built-in functions to manipulate a string

- str.toUpperCase( )
- str.toLowerCase( )
- str.trim( ) *// removes whitespaces*

Apna College

String Methods in JS

- str.slice(start, end?) *// returns part of string*
- str1.concat(str2) *// joins str2 with str1*
- str.replace(searchVal, newVal)
- str.charAt(idx)

Apna College

Let‘s Practice

Qs1. Prompt the user to enter their full name. Generate a username for them based on the input. Start username with @, followed by their full name and ending with the fullname length.

eg: user name = “shradhakhapra” , username should be “@shradhakhapra13”

Apna College