

@vision — fallback chain

Appears in: [DL-03](#)

agents/vision.py:6, 62-92

"A two-model fallback chain: nemotron-nano-12b-v2-vl:free primary, llama-3.2-11b-vision-instruct:free fallback." ... footnote ¹ — "the code that enforces them is @vision."

@vision — fallback chain

agents/vision.py:6-6

```
6 VISION_MODELS = [OPENROUTER_MODEL, OPENROUTER_FALLBACK_MODEL]
```

...

agents/vision.py:62-92

```
62     last_error = None
63     for model in VISION_MODELS:
64         try:
65             payload = _build_payload(model, image_b64, mime, description)
66             resp = requests.post(
67                 "https://openrouter.ai/api/v1/chat/completions",
68                 headers={
69                     "Authorization": f"Bearer {OPENROUTER_API_KEY}",
70                     "Content-Type": "application/json",
71                 },
72                 json=payload,
73                 timeout=30,
74             )
75             resp.raise_for_status()
76             content = resp.json()["choices"][0]["message"]["content"]
77             result = _parse_content(content)
78             result["model_used"] = model
79             return result
80         except Exception as e:
81             last_error = f"{model}: {e}"
82             continue
83
84     return {
85         "product_type": "unknown",
86         "product_tags": [],
87         "mood": "neutral",
88         "target_signals": [],
89         "suggested_hashtags": [],
90         "model_used": None,
91         "error": last_error,
92     }
```

What it shows: The fallback loop: try the primary :v1 model, fall back to llama, and on double-failure return a safe dict with empty tags so downstream agents run rather than crash.

Source: agents/vision.py:6, 62-92 · image rendered by build_snippets.py