

@guardrails

Appears in: [DL-04](#)

agents/guardrails.py:4-12, 15-40

"Pure Python regex. Seven patterns covering the required categories ..." ... "guardrails.py returns clean_copy (unchanged — it flags, it does not edit) and a flags list (@agent-contracts)."

@guardrails

agents/guardrails.py:4-12

```
4  FLAGGED_PATTERNS = [
5      (r"\b(guaranteed?|guarantee)\b", "Guarantee claim – requires substantiation"),
6      (r"\b(cure[sd]?|heals?|treats?)\b", "Health claim – may require regulatory approval"),
7      (r"\b(#\d+|number one|best in (the )?world)\b", "Superlative claim – requires proof"),
8      (r"\b(free\s+trial|no\s+risk)\b", "Free offer – ensure T&Cs are disclosed"),
9      (r"\b(limited\s+time|act\s+now|last\s+chance)\b", "Urgency language – ensure accuracy"),
10     (r"\b(scientifically\s+proven|clinically\s+tested)\b", "Scientific claim – requires citation"),
11     (r"\b(lose\s+weight|weight\s+loss)\b", "Weight loss claim – FTC regulated"),
12 ]
```

...

agents/guardrails.py:15-40

```
15  def check(copy: dict) -> dict:
16      """
17      Check ad copy variants for compliance flags.
18
19      Args:
20          copy: dict with variant_1 and variant_2 keys
21
22      Returns:
23          dict with clean_copy (same shape as input) and flags (list of dicts)
24      """
25      flags = []
26      clean_copy = {}
27
28      for key in ("variant_1", "variant_2"):
29          text = copy.get(key, "")
30          clean_copy[key] = text
31          for pattern, reason in FLAGGED_PATTERNS:
32              matches = re.findall(pattern, text, flags=re.IGNORECASE)
33              if matches:
34                  flags.append({
35                      "variant": key,
36                      "matched": matches[0] if isinstance(matches[0], str) else matches[0][0],
37                      "reason": reason,
38                  })
39
40      return {"clean_copy": clean_copy, "flags": flags}
```

What it shows: The deterministic compliance gate: seven case-insensitive regex categories; the check flags but never edits, and each flag is a three-field auditable record.

Source: agents/guardrails.py:4-12, 15-40 · image rendered by [build_snippets.py](#)