

@notifications-router

Appears in: [DL-08](#)

server/routers/notifications.py:25-45

"...can be changed at runtime through a settings endpoint ..." (footer @notifications-router)

@notifications-router

server/routers/notifications.py:25-45

```
25 @router.post("/config")
26 def update_notification_config(settings: dict):
27     """Update notification settings at runtime (survives until server restart).
28     To persist across restarts, set the corresponding env vars in .env.
29     """
30     # Map from UI-friendly keys to config module attribute names
31     key_map = {
32         "NOTIFY_EMAIL": "NOTIFY_EMAIL",
33         "SMTP_HOST": "SMTP_HOST",
34         "SMTP_PORT": "SMTP_PORT",
35         "SMTP_USER": "SMTP_USER",
36         "SMTP_PASS": "SMTP_PASS",
37         "NOTIFY_ON_APPROVAL": "NOTIFY_ON_APPROVAL",
38         "NOTIFY_ON_AUTO_PO": "NOTIFY_ON_AUTO_PO",
39         "NOTIFY_ON_SCORE_DROP": "NOTIFY_ON_SCORE_DROP",
40         "NOTIFY_ON_DUPLICATE": "NOTIFY_ON_DUPLICATE",
41         "SCORE_DROP_THRESHOLD": "SCORE_DROP_THRESHOLD",
42     }
43     mapped = {key_map[k]: v for k, v in settings.items() if k in key_map}
44     config.update(mapped)
45     return {"status": "updated", "applied": list(mapped.keys())}
```

What it shows: The endpoints that read/update notification settings at runtime and send a test message — what the dashboard panel talks to.

Source: server/routers/notifications.py:25-45 · image rendered by build_snippets.py