

@betsy — run chips

Appears in: **DL-04**

dashboard/betsy.html:764-768, 1262-1265

"The scenario chips on Betsy's page post to this run-agent endpoint ¹@api-control-layer." (footnote ¹ → @main)

@betsy — run chips

dashboard/betsy.html:764-768

```
764 <button class="scenario-chip reset-chip" id="chip-normal"      onclick="selectScenario('')>Normal</button>
765 <button class="scenario-chip" id="chip-stockout"           onclick="selectScenario('stockout_warning')>🚫 Stockout</button>
766 <button class="scenario-chip" id="chip-price"              onclick="selectScenario('price_spike')>⚠️ Price spike</button>
767 <button class="scenario-chip" id="chip-duplicate"          onclick="selectScenario('duplicate_invoice')>🔴 Duplicate invoice</button>
768 <button class="scenario-chip" id="chip-oos"                onclick="selectScenario('supplier_oos')>🚫 Supplier OOS</button>
```

...

dashboard/betsy.html:1262-1265

```
1262   try {
1263     const params = new URLSearchParams({ mode: 'pipeline' });
1264     if (selectedScenario) params.set('scenario', selectedScenario);
1265     await post(`/api/run-agent?${params}`, {});
```

What it shows: The Run-Betsy handler POSTs `/api/run-agent?mode=pipeline&scenario=...`; the chips at 764-768 set the selected scenario.

Source: dashboard/betsy.html:764-768, 1262-1265 · image rendered by build_snippets.py