

@approvals

Appears in: [DL-05](#)

server/routers/approvals.py:36-90

"Build the approvals API as a standalone router with three endpoints — list pending, approve, reject ..." ...
"The approve endpoint in @approvals picks that payload up, creates the PO directly in state, and logs the human decision (@act)."

@approvals

server/routers/approvals.py:36-90

```
36 @router.post("/{decision_id}/approve")
37 def approve(decision_id: str):
38     appr = next((a for a in state.approvals if a["decision_id"] == decision_id), None)
39     if not appr:
40         raise HTTPException(status_code=404, detail="Approval not found")
41     if appr["status"] != "pending":
42         raise HTTPException(status_code=400, detail="Already resolved")
43
44     appr["status"] = "approved"
45     appr["resolved_at"] = datetime.now().isoformat()
46     db.update_approval(decision_id, "approved", appr["resolved_at"])
47
48     result = {}
49     if appr["action"] == "generate_po" and appr.get("payload"):
50         payload = appr["payload"]
51         supplier = next(
52             (s for s in state.suppliers if s["supplier_id"] == payload["supplier_id"]),
53             None,
54         )
55         if supplier and supplier["availability"]:
56             lead_days = supplier.get("catalog", {}).get(
57                 payload["sku_id"], {}
58             ).get("lead_days", 7)
59             po_id = f"PO-{datetime.now().strftime('%Y%m%d')}-{str(uuid.uuid4())[4].upper()}"
60             order = {
61                 "po_id": po_id,
62                 "supplier_id": payload["supplier_id"],
63                 "sku_id": payload["sku_id"],
64                 "quantity": payload["quantity"],
65                 "unit_price": payload["unit_price"],
66                 "total_amount": round(payload["unit_price"] * payload["quantity"], 2),
67                 "order_date": datetime.now().isoformat(),
68                 "expected_delivery": (
69                     datetime.now() + timedelta(days=lead_days)
70                 ).isoformat(),
71                 "actual_delivery": None,
72                 "status": "approved",
73                 "reason": payload.get("reason", ""),
74                 "requested_by": "betsy-human-approved",
75             }
76             state.purchase_orders.append(order)
77             result = {"po_id": po_id}
78
79     log_entry = {
80         "timestamp": datetime.now().isoformat(),
81         "trigger": appr.get("sku_id", "approval"),
82         "analysis": f"Human approved {appr['action']} — decision {decision_id[:8]}",
83         "decision": "human_approved",
84         "confidence": appr.get("confidence", 1.0),
85         "metadata": {"decision_id": decision_id, "action": appr["action"], **result},
86     }
87     state.agent_log.append(log_entry)
88     db.save_log_entry(log_entry)
89
90     return {"status": "approved", **result}
```

What it shows: The three-endpoint approvals router. approve() pulls the pre-built payload, creates the PO directly in state.purchase_orders with requested_by = "betsy-human-approved", and writes the human decision to the log.