Name: Yash Chand Roll No: 05 CSE (DS) Deep Learning Exp 4

Back Propagation in Deep Learning

In simple terms, backpropagation is a supervised learning algorithm that allows a neural network to learn from its mistakes by adjusting its weights and biases. It enables the network to iteratively improve its performance on a given task, such as classification or regression.

Code:

```
import numpy as np
```

```
class NeuralNetwork:
  def __init__(self, input_size, hidden_size, output_size):
     self.input_size = input_size
     self.hidden size = hidden size
     self.output size = output size
     # Initialize weights and biases for the hidden layer and output layer
     self.W1 = np.random.randn(hidden_size, input_size)
     self.b1 = np.zeros((hidden_size, 1))
     self.W2 = np.random.randn(output size, hidden size)
     self.b2 = np.zeros((output size, 1))
  def sigmoid(self, x):
     return 1/(1 + np.exp(-x))
  def sigmoid derivative(self, x):
     return x * (1 - x)
  def forward(self, X):
     # Forward pass
     self.z1 = np.dot(self.W1, X) + self.b1
```

```
self.a1 = self.sigmoid(self.z1)
     self.z2 = np.dot(self.W2, self.a1) + self.b2
     self.a2 = self.sigmoid(self.z2)
     return self.a2
  def backward(self, X, y, learning rate):
     m = X.shape[1]
     # Compute the gradients
     dZ2 = self.a2 - y
     dW2 = (1 / m) * np.dot(dZ2, self.a1.T)
     db2 = (1 / m) * np.sum(dZ2, axis=1, keepdims=True)
     dZ1 = np.dot(self.W2.T, dZ2) * self.sigmoid derivative(self.a1)
     dW1 = (1 / m) * np.dot(dZ1, X.T)
     db1 = (1 / m) * np.sum(dZ1, axis=1, keepdims=True)
     # Update weights and biases using gradients and learning rate
     self.W2 -= learning rate * dW2
     self.b2 -= learning rate * db2
     self.W1 -= learning rate * dW1
     self.b1 -= learning rate * db1
  def train(self, X, y, epochs, learning_rate):
     for epoch in range(epochs):
       # Forward pass
       predictions = self.forward(X)
       # Compute the mean squared error loss
       loss = np.mean((predictions - y) ** 2)
       # Backward pass to update weights and biases
       self.backward(X, y, learning rate)
       if epoch % 100 == 0:
          print(f"Epoch {epoch}, Loss: {loss:.4f}")
  def predict(self, X):
     return self.forward(X)
# Example usage:
input size = 2
```

```
hidden_size = 4
output_size = 1
learning_rate = 0.1
epochs = 10000
# Generate some sample data
X = np.array([[0, 0], [0, 1], [1, 0], [1, 1]]).T
y = np.array([[0, 1, 1, 0]])
# Create the neural network
nn = NeuralNetwork(input_size, hidden_size, output_size)
# Train the neural network
nn.train(X, y, epochs, learning_rate)
# Make predictions
predictions = nn.predict(X)
print("Predictions:", predictions)
```

Output:



