

```
mysql> CREATE TABLE inventory (  
    ->     item_id INT PRIMARY KEY AUTO_INCREMENT,  
    ->     item_name VARCHAR(50) NOT NULL,  
    ->     quantity INT NOT NULL  
    -> );  
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> INSERT INTO inventory (item_name, quantity) VALUES ('Apple', 50);  
Query OK, 1 row affected (0.00 sec)  
  
mysql> INSERT INTO inventory (item_name, quantity) VALUES ('Banana', 30);  
Query OK, 1 row affected (0.01 sec)  
  
mysql> INSERT INTO inventory (item_name, quantity) VALUES ('Orange', 20);  
Query OK, 1 row affected (0.00 sec)
```

```
mysql> CREATE user 'tester'@'localhost' IDENTIFIED by 'tester';  
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> GRANT all privileges on ADS.* TO 'tester'@'localhost';  
Query OK, 0 rows affected, 1 warning (0.02 sec)
```

```
mysql> █
```

```
→ ~ docker exec -it mysqlContainer bash  
bash-5.1#  
bash-5.1# mysql -utester -p  
Enter password:  
Welcome to the MySQL monitor.  Commands end with ; or \g.  
Your MySQL connection id is 10  
Server version: 9.0.0 MySQL Community Server - GPL  
  
Copyright (c) 2000, 2024, Oracle and/or its affiliates.  
  
Oracle is a registered trademark of Oracle Corporation and/or its  
affiliates. Other names may be trademarks of their respective  
owners.  
  
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.  
mysql>
```

```
mysql> start transaction;  
Query OK, 0 rows affected (0.01 sec)  
  
mysql> SELECT * FROM inventory WHERE item_name = 'Apple' LOCK IN SHARE MODE;  
+-----+-----+-----+  
| item_id | item_name | quantity |  
+-----+-----+-----+  
|      1 | Apple     |      50 |  
+-----+-----+-----+  
1 row in set (0.00 sec)  
  
mysql> █
```

```
[mysql> UPDATE inventory
-> SET quantity = 30
-> WHERE item_name = 'apple'
-> ;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> █
```

```
[mysql> select * from inventory ;
+-----+-----+-----+
| item_id | item_name | quantity |
+-----+-----+-----+
|      1 | Apple     |      50 |
|      2 | Banana    |      30 |
|      3 | Orange    |      20 |
+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> █
```

```
[mysql> SELECT * FROM inventory WHERE item_name = 'Apple' FOR UPDATE;
+-----+-----+-----+
| item_id | item_name | quantity |
+-----+-----+-----+
|      1 | Apple     |      50 |
+-----+-----+-----+
1 row in set (0.00 sec)

mysql> █
```

```
[mysql> UPDATE inventory
-> SET quantity = 30
-> WHERE item_name = 'apple'
-> ;

ERROR 1205 (HY000): Lock wait timeout exceeded; try restarting transaction
mysql>

[mysql> UPDATE inventory
-> SET quantity = 30
-> WHERE item_name = 'apple'
-> ;

ERROR 1205 (HY000): Lock wait timeout exceeded; try restarting transaction
mysql>
```

```
[mysql> commit ;
Query OK, 0 rows affected (0.00 sec)
```