

RMS Device Suite - API Execution Report

Date/Time: 2026-08-21 17:05:32
Target AP: RMS-3E30
Role: Security Admin
Session Token: 853c550a4be2ac16

Execution Overview

Sr.	API Name	Method	URL	Read Status	Write Status
1	Authentication API (Write API Login)	POST	http://192.168.4.1/api/login	-----	200 OK
2	Authentication API (Read API Login)	GET	http://192.168.4.1/api/auth/status	200 OK	-----
3	UUID Checking Single-phase	POST	http://192.168.4.1/api/config/parameter	-----	200 OK
4	UUID Checking Single-phase(Get)	GET	http://192.168.4.1/api/config/parameter?tab=1	200 OK	-----
5	isp Configuration API	POST	http://192.168.4.1/api/config/isp	-----	200 OK
6	Get isp Configuration	GET	http://192.168.4.1/api/config/isp	200 OK	-----
7	Remote Server Configuration API	POST	http://192.168.4.1/api/config/remote-server	-----	200 OK
8	Remote Server Configuration Read API	GET	http://192.168.4.1/api/config/remote-server	200 OK	-----
9	Device Metadata API	GET	http://192.168.4.1/api/device/metadata	200 OK	-----
10	Secure Broker Connection Trigger & Status API	POST	http://192.168.4.1/api/device/broker/connect	-----	200 OK
11	Read API - Broker Connection Status	GET	http://192.168.4.1/api/device/broker/status	200 OK	-----
12	Read API - Get Inverter Communication Configuration	GET	http://192.168.4.1/api/config/inverter-communication	200 OK	-----
13	Write API - Get Inverter Communication Configuration	POST	http://192.168.4.1/api/config/inverter-communication	-----	400 Bad Request
15	Offline Historical Data Download API	GET	http://192.168.4.1/api/history?day=2026-05-29&vd=5&offset=&limit=96	Error/Offline	-----
16	WIFI Connection Check	GET	http://192.168.4.1/api/device/config/update	Error/Offline	-----
17	WIFI Connection Check_2	POST	http://192.168.4.1/api/device/config/update	-----	400 Bad Request
18	Certificate RootCA	POST	http://192.168.4.1/write.html?filename=rootCA.pem	-----	200 OK
19	Certificate Key	POST	http://192.168.4.1/write.html?filename=key.pem	-----	200 OK

20	Certificate Client	POST	http://192.168.4.1/write.html?filename=client.pem	-----	200 OK
23	MQTTServer Get	GET	http://192.168.4.1/api/config/mqtt-server	200 OK	-----
24	MQTTServer Post	POST	http://192.168.4.1/api/config/mqtt-server	-----	200 OK
25	Firmware Update	POST	http://192.168.4.1/update1	404 Not Found	404 Not Found
26	Modbus Poll Access	Get/POST	http://192.168.4.1/api/modbus	-----	404 Not Found
27	Fiddler Request	Get/POST	http://192.168.4.1:85/list.html	-----	-----
28	Device Config Update API	POST	http://192.168.4.1/api/device/config/update	-----	200 OK
21	Restart	Get/POST	http://192.168.4.1/restart1	404 Not Found	404 Not Found

Detailed Execution Logs

Sr 1: Authentication API (Write API Login)

URL: http://192.168.4.1/api/login | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: RUNNING 3-STEP AUTHENTICATION SEQUENCE ---

[Step 1] POST to http://192.168.4.1/api/login
Payload: {
  "username": "RMS-3E30",
  "password": "Admin@123"
}
Response (200): {"Flag":true,"Message":"success","Data":{"token":"83348","valid_for":1440}}

[Step 2] POST to http://192.168.4.1/api/device/config/update
Headers: {
  "Content-Type": "application/json",
  "Authorization": "Bearer 83348",
  "Cookie": "session=83348"
}
Payload: {
  "type": 2,
  "device_username": "SecurityAdmin",
  "device_password": "Admin@123"
}
Response (200): {"Flag":true,"Message":"success","Data":{"info":"User password updated successfully."}}

[Step 3] POST to http://192.168.4.1/api/login
Payload: {
  "username": "SecurityAdmin",
  "password": "Admin@123"
}
Response (200): {"Flag":true,"Message":"success"}

Success! Session token established: 853c550a4be2ac16
```

Sr 2: Authentication API (Read API Login)

URL: http://192.168.4.1/api/auth/status | **Method:** GET | **Read Status:** 200 OK | **Write Status:** -----

```
--- STEP 2: READ VERIFICATION ---
Status: 200 OK
{"Flag":true,"Message":"success"}
```

Sr 3: UUID Checking Single-phase

URL: http://192.168.4.1/api/config/parameter | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 200 OK
{"Flag":true,"status":"success","message":"Parameter mapping configuration saved successfully","table":1}
```

Sr 4: UUID Checking Single-phase(Get)

URL: http://192.168.4.1/api/config/parameter?table=1 | **Method:** GET | **Read Status:** 200 OK | **Write Status:** -----

```
--- STEP 2: READ VERIFICATION ---
Status: 200 OK
{"status":"success","vdinterval":5,"vdintervalmtr":5,"table":1,"parameters":[]}
```

Sr 5: isp Configuration API

URL: http://192.168.4.1/api/config/isp | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":null}
```

Sr 6: Get isp Configuration

URL: http://192.168.4.1/api/config/isp | **Method:** GET | **Read Status:** 200 OK | **Write Status:** -----

```
--- STEP 2: READ VERIFICATION ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":{"apn":"airtelgprs.com","apn1":"airtelgprs.com","apn2":"airtelgprs.com","current_sim":1,"rssi_s":0}}
```

Sr 7: Remote Server Configuration API

URL: http://192.168.4.1/api/config/remote-server | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":null}
```

Sr 8: Remote Server Configuration Read API

URL: http://192.168.4.1/api/config/remote-server | **Method:** GET | **Read Status:** 200 OK | **Write Status:** -----

```
--- STEP 2: READ VERIFICATION ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":{"server_url":"rms.iotscada-pmsg.com","server_port":8883,"client_id":"d:866738083608743$ongridrooftop$510017","username":"866738083608743$ongridrooftop$510017","password":"8dd08acd","solution_type":"ongridrooftop","imei":"866738083623353","server_url1":"rms.iotscada-pmsg.com","server_port1":8883,"client_id1":"d:866082075799828$ongridrooftop$500092","username1":"866082075799828$ongridrooftop$500092","password1":"466b856f","solution_type1":"ongridrooftop","devimei1":"866082075799828"}}
```

Sr 9: Device Metadata API

URL: http://192.168.4.1/api/device/metadata | **Method:** GET | **Read Status:** 200 OK | **Write Status:** -----

```
--- STEP 2: READ VERIFICATION ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":{"deviceType":"RMS/Datalogger","deviceModel":"RMS-3E30","firmwareVersion":"1072","ipAddress":"192.168.4.1","httpPort":80,"httpsPort":0,"username":"RMS-3E30","password":"Admin@123","ssid":"RMS-3E30","macAddress":"80:F1:B2:BA:3E:30","imei":"866738083623353","serialNumber":"1234"}}
```

Sr 10: Secure Broker Connection Trigger & Status API

URL: http://192.168.4.1/api/device/broker/connect | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 200 OK
{"Flag": true,"Message": "success","Data": {"status": 1,"statusText": "ROOTCA_CERTIFICATE_LOADING"}}
```

Sr 11: Read API - Broker Connection Status

URL: http://192.168.4.1/api/device/broker/status | **Method:** GET | **Read Status:** 200 OK | **Write Status:** -----

```
--- STEP 2: READ VERIFICATION ---
Status: 200 OK
{"Flag": true, "Message": "success", "Data": {"status": 1, "statusText": "ROOTCA_CERTIFICATE_LOADING"}}
```

Sr 12: Read API - Get Inverter Communication Configuration

URL: http://192.168.4.1/api/config/inverter-communication | **Method:** GET | **Read Status:** 200 OK | **Write Status:** -----

```
--- STEP 2: READ VERIFICATION ---
Status: 200 OK
{"Flag": true, "Message": "success", "Data": {"asn": "-", "baudrate": 115200, "parity": "N", "stopBit": 1, "databits": 8, "reqCount_1": 2, "slaveID_11": 1, "startAddr_11": 1, "length_11": 120, "funcType_11": 1, "slaveID_12": 0, "startAddr_12": 0, "length_12": 0, "funcType_12": 0, "slaveID_13": 0, "startAddr_13": 0, "length_13": 0, "funcType_13": 0, "slaveID_14": 0, "startAddr_14": 0, "length_14": 0, "funcType_14": 0, "slaveID_15": 0, "startAddr_15": 0, "length_15": 0, "funcType_15": 0, "slaveID_16": 0, "startAddr_16": 0, "length_16": 0, "funcType_16": 0, "slaveID_17": 0, "startAddr_17": 0, "length_17": 0, "funcType_17": 0, "slaveID_18": 0, "startAddr_18": 0, "length_18": 0, "funcType_18": 0, "slaveID_19": 0, "startAddr_19": 0, "length_19": 0, "funcType_19": 0, "slaveID_110": 0, "startAddr_110": 0, "length_110": 0, "funcType_110": 0}}
```

Sr 13: Write API - Get Inverter Communication Configuration

URL: http://192.168.4.1/api/config/inverter-communication | **Method:** POST | **Read Status:** ----- | **Write Status:** 400 Bad Request

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 400 Bad Request
{"Flag": false, "Message": "FAIL", "Data": null}
```

Sr 15: Offline Historical Data Download API

URL: http://192.168.4.1/api/history?day=2026-05-29&vd=5&offset=&limit=96 | **Method:** GET | **Read Status:** Error/Offline | **Write Status:** -----

```
--- STEP 2: READ ERROR ---
HTTPConnectionPool(host='192.168.4.1', port=80): Read timed out. (read timeout=5)
```

Sr 16: WIFI Connection Check

URL: http://192.168.4.1/api/device/config/update | **Method:** GET | **Read Status:** Error/Offline | **Write Status:** -----

```
--- STEP 2: READ ERROR ---
HTTPConnectionPool(host='192.168.4.1', port=80): Read timed out. (read timeout=5)
```

Sr 17: WIFI Connection Check_2

URL: http://192.168.4.1/api/device/config/update | **Method:** POST | **Read Status:** ----- | **Write Status:** 400 Bad Request

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 400 Bad Request
{"Flag": false, "Message": "Required parameters not provided", "Data": null}
```

Sr 18: Certificate RootCA

URL: http://192.168.4.1/write.html?filename=rootCA.pem | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":null}
```

Sr 19: Certificate Key

URL: http://192.168.4.1/write.html?filename=key.pem | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":null}
```

Sr 20: Certificate Client

URL: http://192.168.4.1/write.html?filename=client.pem | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":null}
```

Sr 23: MQTTServer Get

URL: http://192.168.4.1/api/config/mqtt-server | **Method:** GET | **Read Status:** 200 OK | **Write Status:** -----

```
--- STEP 2: READ VERIFICATION ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":{"http_url":"869742085795505","http_port":443,"imei":"866738083623353","username":"866738083608743$ongridrooftop$510017","password":"8dd08acd",}}
```

Sr 24: MQTTServer Post

URL: http://192.168.4.1/api/config/mqtt-server | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 200 OK
{"Flag":true,"Message":"success","Data":null}
```

Sr 25: Firmware Update

URL: http://192.168.4.1/update1 | **Method:** POST | **Read Status:** 404 Not Found | **Write Status:** 404 Not Found

```
--- STEP 1: POST WRITE RESPONSE ---
Status: 404 Not Found
Not found: /update1

--- STEP 2: READ VERIFICATION ---
Status: 404 Not Found
Not found: /update1
```

Sr 26: Modbus Poll Access

URL: http://192.168.4.1/api/modbus | **Method:** Get/POST | **Read Status:** ----- | **Write Status:** 404 Not Found

```
--- STEP 1: POST WRITE RESPONSE ---  
Status: 404 Not Found  
Not found: /api/modbus
```

Sr 27: Fiddler Request

URL: http://192.168.4.1:85/list.html | **Method:** Get/POST | **Read Status:** ----- | **Write Status:** -----

Sr 28: Device Config Update API

URL: http://192.168.4.1/api/device/config/update | **Method:** POST | **Read Status:** ----- | **Write Status:** 200 OK

```
--- STEP 1: POST WRITE RESPONSE ---  
Status: 200 OK  
{"Flag":true,"Message":"success","Data":{"info":"User password updated successfully."}}
```

Sr 21: Restart

URL: http://192.168.4.1/restart1 | **Method:** Get/POST | **Read Status:** 404 Not Found | **Write Status:** 404 Not Found

```
--- STEP 1: POST WRITE RESPONSE ---  
Status: 404 Not Found  
Not found: /restart1  
  
--- STEP 2: READ VERIFICATION ---  
Status: 404 Not Found  
Not found: /restart1
```