

V500 SERIES — THREE PIECE BALL VALVE

Full port · socket weld ends · blowout-proof stem · in-line serviceable

PRODUCT DESCRIPTION

The Meridian V500 is a three piece industrial ball valve. The swing-out centre section allows the seats and body seal to be replaced without removing the valve from the line. Full port bore keeps pressure drop to a minimum across the assembly.

SIZE AND RATING

Nominal size	2 in.
Pressure rating	1500 PSI WOG cold working pressure
Steam rating	250 PSI WSP saturated steam
Temperature range	-20 F to 400 F continuous duty
Port configuration	Full Port
Body construction	Three Piece, bolted body
Flow coefficient	Cv 210
Suitable media	Water, oil, gas and compressed air
Weight	18.6 lb

MATERIALS OF CONSTRUCTION

Body material	Carbon Steel
Material spec	ASTM A105
Ball	Type 316 stainless steel
Stem	Type 316 stainless, blowout proof
Seats	Reinforced PTFE
Body seal	Reinforced PTFE
Gland packing	PTFE, live loaded
Body bolting	ASTM A193 Gr. B7

END CONNECTIONS

Socket weld ends machined to ASME B16.11. NPT threaded and butt weld ends are available to order; consult the ordering matrix on page 2 for the applicable suffix.

OPERATOR

Operator	Gear Operated with handwheel
Mounting	ISO 5211, 2 in. pad

Position indicator fitted as standard. Direct actuator mounting is machined into the body.

APPROVALS AND STANDARDS

API 608	API 607	MSS SP-110	ASME B16.11	CRN registered
---------	---------	------------	-------------	----------------

Design conforms to API 608. Fire safe tested to API 607 Edition 7. Face-to-face dimensions per MSS SP-110. Manufactured in Canada.

MERIDIAN FLOW CONTROL

V500 SERIES — DIMENSIONAL DATA

Technical Data Sheet
Document TDS-V500-EN · Rev. 4

TABLE 1 — DIMENSIONS AND WEIGHTS, SOCKET WELD

PART NO.	SIZE	A (IN)	B (IN)	CV	WEIGHT (LB)
V500-100-SW	1 in.	4.25	2.80	58	6.4
V500-150-SW	1-1/2 in.	5.50	3.35	128	11.2
V500-200-SW	2 in.	6.50	3.90	210	18.6
V500-300-SW	3 in.	8.75	5.10	480	37.4
V500-400-SW	4 in.	10.50	6.20	790	61.0

A = face to face. B = centreline to top of body. Weights are for the bare valve without operator.

TABLE 2 — PRESSURE / TEMPERATURE RATING

TEMPERATURE	-20 TO 100 F	200 F	300 F	400 F
Working pressure, PSI	1500	1310	1080	720

Ratings are for non-shock service with reinforced PTFE seats. Consult Meridian for service above 400 F.

ORDERING MATRIX

POSITION	CODE	DESCRIPTION
End connection	SW	Socket weld to ASME B16.11
	TH	NPT threaded to ASME B1.20.1
	BW	Butt weld, schedule to be specified
Operator	G	Gear operated with handwheel
	L	Lever, 1 in. and below only
	BS	Bare stem with ISO 5211 pad
Seat material	R	Reinforced PTFE, standard
	P	PEEK, high temperature

COMPLIANCE

Lead free	Not certified to NSF/ANSI 372
Material specification	ASTM A105

COUNTRY OF ORIGIN

Manufactured in Canada. CRN registered in all provinces and territories.