

HTML FORMS

- `<form>` element defines a form to collect user info.
3/P
- `<input>` most imp to define user, depending on type attribute.
- `<label>` generally used to define I/P heading.
- `<input type="text" name="Pname">
`
↳ (Takes 3/P as text)
- `<label for="fname">First Name </label>`
→ for attribute must be same as id in input field helps to bind label & input type together
- `<input type="submit" value="Submit" />`
↳ Creates a submit button
- Action attribute; defines the action to be performed when form is submitted
 - `<form action="form.php">`

- Target Attribute; specifies result will open in new or same page

→ `<form action = "form.php" target = "_self">`

↓
target
↓
blank
↓
parent

- Method Attribute; method attribute specifies the HTTP method (GET & POST)

→ Using GET, the form data will be visible in page's address field.

→ POST has no limitations, doesn't display info in page URL.

- * Name Attribute; Must be specify with input element to perform action using ~~an~~ action attribute.

- * autocomplete → Assign in form element to fill automatically.
`autocomplete = "on"`

Specify option size

- <select>element;


size = "4"

```
<select id="no." name="no." size="4">
  <option value="1"> 1 </option>
  :
</select>
```

→ we can add selected attribute to choose default one.

- <textarea>; provides area for commenting

```
<textarea name="msg" rows="10" cols="5">
</textarea>
```



```
<fieldset>
  <legend> Home </legend>
  :
  Content
</fieldset>
```


- <datalist> element; specifies list of pre-defined options.

→ user will see a drop down list of pre-defined options as they input

<input list="no">

<datalist id="no">

<option value="1">

⋮

</datalist>



• HTML INPUT TYPE;
type (attribute)

-> & button

checkbox

color

date

→ can specify min & max ^{attribute}

datetime-local

email

file

hidden

image

month

number

password

radio

range → min and max

reset

search

submit

tel

text

time

url

week

• Input Restrictions;

- checked → pre-selects option
- disabled → I/p should be disabled
- max → maximum value
- maxlength → max. no. in character I/p field
- min → minimum value
- pattern → regular expression to check I/p pattern
- readonly → Input is read only.
- required → must be entered compulsory.
- value → value of I/p field
- step → Increment/Decrement by
- size → specifies size of I/p

→ pattern = "[0-9]{2} - [0-9]{10}"

↳ (used with tel type)

- multiple → so select multiple files or emails
- placeholder → highlight in I/p text

• autofocus → specifies that on I/p field should automatically get focus when page loads.