RaceDay REST API Endpoint Plan

RaceDay – Event Management Platform for South African Road Running, Walking & Cycling | Section B: REST API Endpoint Plan | Roles: None = public Any = logged in Organiser Participant

HTTP method	Route	Description	Role required	Request body	Expected response
POST	/api/auth/register	Creates an Organiser or Participant account and returns an auth token.	None	{ fullName, email, password, phone, role, organisationName?, dateOfBirth? }	201 Created – account + token; 400 – invalid fields; 409 – email exists
POST	/api/auth/login	Verifies email and password, returns a token containing the user's role.	None	{ email, password }	200 OK – token + role + id; 401 – invalid credentials
GET	/api/users/profile	Returns the logged-in user's own profile details.	Any	None	200 OK – profile object; 401 – not authenticated
PUT	/api/users/profile	Updates the logged-in user's own profile fields.	Any	{ fullName?, phone?, emergencyContactName?, emergencyContactPhone? }	200 OK – updated profile; 400 – invalid fields
GET	/api/events	Lists upcoming events, filterable by status or date.	None	None	200 OK – array of events
GET	/api/events/{id}	Returns one event including its venue and categories.	None	None	200 OK – event detail; 404 – not found
POST	/api/events	Creates a new event owned by the organiser.	Organiser	{ eventName, eventDate, startTime, venueId, description }	201 Created – event; 400 – invalid; 404 – venue not found
PUT	/api/events/{id}	Updates an event owned by the organiser.	Organiser	{ eventName?, eventDate?, startTime?,	200 OK – updated; 403 – not owner; 404 – not found

HTTP method	Route	Description	Role required	Request body	Expected response
				description?, status? }	
DELETE	/api/events/{id}	Deletes or cancels an event that has no enrolments.	Organiser	None	204 No Content; 403 – not owner; 404 – not found; 409 – has enrolments
GET	/api/events/{id}/categories	Lists all entry categories offered for an event.	None	None	200 OK – categories; 404 – event not found
POST	/api/events/{id}/categories	Adds a new category (e.g. 21.1km) to an event.	Organiser	{ categoryName, distanceKm, entryFee, maxParticipants }	201 Created – category; 400 – invalid; 409 – duplicate name
PUT	/api/categories/{id}	Edits a category's fee, distance or capacity.	Organiser	{ categoryName?, distanceKm?, entryFee?, maxParticipants? }	200 OK – updated; 403 – not owner; 404 – not found
DELETE	/api/categories/{id}	Removes a category that has no enrolments.	Organiser	None	204 No Content; 409 – enrolments exist; 404 – not found
GET	/api/enrolments	Participants see their own; organisers see enrolments on their events (?eventId=).	Any	None	200 OK – enrolments + bib numbers; 401 – not authenticated
POST	/api/events/{eventId}/enrol	Enrols the logged-in participant into an event category.	Participant	{ categoryId }	201 Created – enrolment + bib; 400 – invalid; 404 – not found; 409 – already enrolled / full
DELETE	/api/enrolments/{id}	Withdraws the participant's own enrolment.	Participant	None	200 OK – withdrawn; 403 – not own; 404 – not found; 409 – result exists
GET	/api/events/{eventId}/results	Public ranked leaderboard of results for an event.	None	None	200 OK – results; 404 – event not found

HTTP method	Route	Description	Role required	Request body	Expected response
GET	`/api/results/me`	Returns the participant's own performance history across events.	Participant	None	`200 OK` – personal results; `401` – not authenticated
POST	`/api/results`	Captures a result for a specific enrolment.	Organiser	`{ enrolmentId, finishTime, position, status }`	`201 Created` – result; `400` – invalid; `404` – enrolment not found; `409` – result exists
PUT	`/api/results/{id}`	Corrects a result (time, position or status).	Organiser	`{ finishTime?, position?, status? }`	`200 OK` – updated; `403` – not owner; `404` – not found
DELETE	`/api/results/{id}`	Removes an erroneous result.	Organiser	None	`204 No Content`; `403` – not owner; `404` – not found

Notes: All routes begin with **/api/**. GET = read · POST = create · PUT = update · DELETE = remove. `2xx` = success · `4xx` = client error (400 invalid · 401 unauthenticated · 403 forbidden · 404 not found · 409 conflict).