Student Name: Yash Karde	UID: 25MCI10090
Branch: MCA(AI/ML)	Section/Group: 25MAM-1 A
Semester: 2nd sem	Date of Performance: 21/04/2026
Subject Name: TECHNICAL SKILLS	Subject Code:

WORKSHEET 10

AIM:

To understand and apply transaction control in PostgreSQL using BEGIN, COMMIT, ROLLBACK, and SAVEPOINT to maintain data integrity during database operations.

S/W Requirement: PostgreSQL and pgAdmin

OBJECTIVES:

Apply transaction control commands for safe and reliable database updates.

Practical / Experiment Steps

Table creation:

```
DROP TABLE IF EXISTS Payroll;
CREATE TABLE Payroll (
   emp_id INT PRIMARY KEY,
   emp_name VARCHAR(50),
   salary DECIMAL(10,2) CHECK (salary > 0)
);
INSERT INTO Payroll VALUES
(1, 'Amit', 30000),
(2, 'Neha', 40000),
(3, 'Ravi', 50000);
SELECT * FROM Payroll;
```



	emp_id [PK] integer	emp_name character varying (50)	salary numeric (10,2)
1	1	Amit	30000.00
2	2	Neha	40000.00
3	3	Ravi	50000.00

Figure 1: Table created and initial data inserted

Experiment 1: Transaction with ROLLBACK

```
BEGIN;
UPDATE Payroll
SET salary = -1000
WHERE emp_id = 3;
SELECT * FROM Payroll;
ROLLBACK;
SELECT * FROM Payroll;
```



Figure 2: Transaction started with BEGIN



Figure 3: Constraint violation error during update



Figure 4: Table state after rollback

Experiment 2: Transaction with SAVEPOINT

```
BEGIN;
UPDATE Payroll
SET salary = salary + 5000
WHERE emp_id = 1;
SAVEPOINT sp1;
UPDATE Payroll
SET salary = salary + 7000
WHERE emp_id = 2;
UPDATE Payroll
SET salary = -1000
WHERE emp_id = 3;
ROLLBACK TO sp1;
COMMIT;
SELECT * FROM Payroll;
```



Figure 5: First valid update before savepoint



Figure 6: Savepoint created successfully

```sql
-- Roll back only till savepoint
ROLLBACK TO sp1;

-- Commit the valid change
COMMIT;

-- Final table
SELECT * FROM Payroll;
```

Data Output Messages Notifications

	emp_id [PK] integer	emp_name character varying (50)	salary numeric (10,2)
1	2	Neha	40000.00
2	3	Ravi	50000.00
3	1	Amit	35000.00

Figure 7: Final result after rollback to savepoint and commit

Data Output Messages Notifications

	emp_id [PK] integer	emp_name character varying (50)	salary numeric (10,2)
1	1	Amit	30000.00
2	2	Neha	40000.00
3	3	Ravi	50000.00

Figure 8: Table data after transaction handling

Outcomes:

1. **BEGIN** starts a transaction block for grouping multiple SQL commands.
2. **ROLLBACK** cancels changes made inside the transaction.
3. **SAVEPOINT** allows partial rollback without losing all valid updates.
4. **CHECK** constraint ensures salary remains greater than zero.
5. **PostgreSQL** transaction control helps maintain consistency and data integrity.