# **Fundamentals of Data Management**

Credit Tasks 10.2.3: Performance

# **Overview**

You'll learn how DBMSs execute queries, how to find out about database statistics, when to create indexes and how to investigate whether an index is being used.

## **Purpose**

Gain practical experience of some performance-related matters in databases.

#### Task

Open XAMPP/ VMWare Player. Follow the instructions to open two connections to the MySQL server from the MySQL Workbench. Work through the tasks below.

## Time

This task should be completed in your lab class and submitted for feedback in lab 10 or at the beginning of lab 11.

#### Resources

 MySQL (on FDM virtual machine) and MySQL Workbench (or other RDBMS and suitable client).

## **Fee**dback

Discuss your solutions with the tutorial instructor.

### Next

Get started on Task 10.2.4.

# Credit Tasks 10.2.3 — Submission Details and Assessment Criteria

Document your solutions to the tasks using a word processor. Upload your solutions to Doubtfire, then discuss it with your tutor.





Use either window and run a simple query:

# EXPLAIN EXTENDED SELECT \* FROM Products;

You will receive a listing that includes the following columns:

ID select_type The type of query, such as SIMPLE (no joins) or UNION. See listing: https://dev.mysql.com/doc/refman/5.7/en/explain-output.html#explain_select_type  table The table accessed to get the rows.  type The type of join used. Most common options: all – This usually means that the table has been searched sequentially, which is expensive (making an index might help).  ref – The DBMS uses an index on the key column to find the matching rows. Listing of all options: https://dev.mysql.com/doc/refman/5.7/en/explain-output.html#jointype_const  The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in ; key The index that was actually used for the search.  key_len The length of the key that was used.  ref Shows which columns or values were compared when the index mentioned under 'key' was used.  rows Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered The percentage of the table rows that will be examined based on the condition in the WHERE clause.  Extra Any additional information.	Column	What the values mean
https://dev.mysql.com/doc/refman/5.7/en/explain- output.html#explain_select_type  The table accessed to get the rows.  type  The type of join used. Most common options: all – This usually means that the table has been searched sequentially, which is expensive (making an index might help).  ref – The DBMS uses an index on the key column to find the matching rows.  Listing of all options: https://dev.mysql.com/doc/refman/5.7/en/explain-output.html#jointype_const  possible_keys  The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in <table_name>;  key  The index that was actually used for the search.  key_len  The length of the key that was used.  ref  Shows which columns or values were compared when the index mentioned under 'key' was used.  rows  Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered  The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>	ID	ID field for the step
table  table  The table accessed to get the rows.  type  The type of join used. Most common options:  all – This usually means that the table has been searched sequentially, which is expensive (making an index might help).  ref – The DBMS uses an index on the key column to find the matching rows.  Listing of all options:  https://dev.mysql.com/doc/refman/5.7/en/explain-output.html#jointype_const  possible_keys  The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in <table_name>;  key  The index that was actually used for the search.  key_len  The length of the key that was used.  ref  Shows which columns or values were compared when the index mentioned under 'key' was used.  rows  Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered  The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>	select_type	The type of query, such as SIMPLE (no joins) or UNION. See listing:
The type of join used. Most common options:  all – This usually means that the table has been searched sequentially, which is expensive (making an index might help).  ref – The DBMS uses an index on the key column to find the matching rows.  Listing of all options:  https://dev.mysql.com/doc/refman/5.7/en/explain-output.html#jointype_const  possible_keys  The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in <table_name>;  key  The index that was actually used for the search.  key_len  The length of the key that was used.  ref  Shows which columns or values were compared when the index mentioned under 'key' was used.  rows  Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered  The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>		
all – This usually means that the table has been searched sequentially, which is expensive (making an index might help).  ref – The DBMS uses an index on the key column to find the matching rows.  Listing of all options:  https://dev.mysql.com/doc/refman/5.7/en/explain-output.html#jointype_const  The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in <table_name>;  key  The index that was actually used for the search.  key_len  The length of the key that was used.  ref  Shows which columns or values were compared when the index mentioned under 'key' was used.  rows  Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered  The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>	table	The table accessed to get the rows.
sequentially, which is expensive (making an index might help).  ref – The DBMS uses an index on the key column to find the matching rows.  Listing of all options: https://dev.mysql.com/doc/refman/5.7/en/explain-output.html#jointype_const  possible_keys The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in <table_name>; key The index that was actually used for the search. key_len The length of the key that was used.  ref Shows which columns or values were compared when the index mentioned under 'key' was used.  rows Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>	type	The type of join used. Most common options:
matching rows. Listing of all options: https://dev.mysql.com/doc/refman/5.7/en/explain- output.html#jointype_const  possible_keys The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in <table_name>; key The index that was actually used for the search. key_len The length of the key that was used.  ref Shows which columns or values were compared when the index mentioned under 'key' was used.  rows Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>		·
https://dev.mysql.com/doc/refman/5.7/en/explain- output.html#jointype_const  The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in <table_name>;  key The index that was actually used for the search.  key_len The length of the key that was used.  ref Shows which columns or values were compared when the index mentioned under 'key' was used.  rows Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>		
possible_keys The names of indexes that could be used. To find out which columns the indexes are made on, use SHOW indexes in <table_name>;  key The index that was actually used for the search.  key_len The length of the key that was used.  ref Shows which columns or values were compared when the index mentioned under 'key' was used.  rows Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>		Listing of all options:
the indexes are made on, use SHOW indexes in <table_name>;  key The index that was actually used for the search.  key_len The length of the key that was used.  ref Shows which columns or values were compared when the index mentioned under 'key' was used.  rows Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered The percentage of the table rows that will be examined based on the condition in the WHERE clause.</table_name>		' '
key_len       The length of the key that was used.         ref       Shows which columns or values were compared when the index mentioned under 'key' was used.         rows       Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.         filtered       The percentage of the table rows that will be examined based on the condition in the WHERE clause.	possible_keys	the indexes are made on, use
ref Shows which columns or values were compared when the index mentioned under 'key' was used.  rows Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  filtered The percentage of the table rows that will be examined based on the condition in the WHERE clause.	key	The index that was actually used for the search.
rows Shows how many rows the DBMS believes it has to examine. This is an estimate based on statistics, not actual values.  The percentage of the table rows that will be examined based on the condition in the WHERE clause.	key_len	The length of the key that was used.
an estimate based on statistics, not actual values.  The percentage of the table rows that will be examined based on the condition in the WHERE clause.	ref	·
condition in the WHERE clause.	rows	·
Extra Any additional information.	filtered	, · · · · · · · · · · · · · · · · · · ·
	Extra	Any additional information.



# **Subtask 10.2.3**

Examine the following query before retrieving the query plan with "EXPLAIN EXTENDED". The COUNT(\*) function returns the number of rows. Since there is no restriction, we should obtain a count of all rows. How do you think the DBMS would execute this query?

SQL

EXPLAIN EXTENDED

SELECT COUNT(\*) FROM Orders;

Run the query and then the query plan. Examine the output with the help of the column explanations given above.

Describe in your own words how the DBMS accesses the rows. Is this different from what you expected? Can you reason why this strategy was chosen?

Document and upload your findings.

