

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION

PRODUCT NAME	Rubber Bonded Grinding Wheels
END USE	Grinding wheel
MANUFACTURER	Western Abrasives 1170 NE 63 rd Avenue Portland, Oregon 97213 Phone: (503) 234-0733 Fax: (503) 235-3851
EMERGENCY PHONE NUMBER	(503) 234-0733

SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION	Acute Toxicity, Oral – 5 Acute Toxicity, Dermal – 4 Acute Toxicity, Inhalation – 5 Serious Eye Damage/Eye Irritation – 2B Skin Corrosion/Irritation – 2
SIGNAL WORD	WARNING
HAZARD STATEMENT	May be harmful if swallowed (H303) Harmful in contact with skin (H312) May be harmful if inhaled (H333) Causes eye irritation (H320) Causes skin irritation (H315)

HAZARD PICTOGRAMS



PRECAUTIONARY

STATEMENT(S)

Prevention

P264 – Wash hands and exposed skin thoroughly after handling.

P280 – Wear protective gloves and clothing. Chemical resistant or impervious gloves are sufficient.

Response

P302 + P352 + P362 + P363 – IF ON SKIN: Wash with plenty

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016

of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse.

P305 + P351 + P338 + P310 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

P332 + P313 – If skin irritation occurs: Get medical attention.

P312 + P304 – IF SWALLOWED OR INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P501 – Dispose of contents or container in accordance with local, regional, national and international regulations.

HAZARDS NOT

N/A

OTHERWISE CLASSIFIED

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE / MIXTURE

Mixture

OTHER MEANS OF IDENTIFICATION

N/A

CAS # / IDENTIFIERS

INGREDIENT NAME

% BY WEIGHT

CAS NUMBER

Aluminum Oxide

50 – 90

1344-28-1

Rubber

12 - 15

N/A

Gamma-Aminopropyltriethoxysilane

0.1 – 5

919-30-2

Pigment Green 7

0.1 – 5

1328-53-6

Hydrated Amorphous Silica

0.1 – 5

7631-86-9

Polymer

0.1 – 5

N/A

Calcium Silicate

0.1 – 5

1344-95-2

Iron Oxide

0.1 – 5

1309-37-1

Calcium Hydroxide

0.1 – 5

1305-62-0

Phenolic Resin

0.1 – 5

N/A

Magnesium Oxide

0.1 – 5

1309-48-4

Titanium Dioxide

0.1 – 5

13463-67-7

Zinc Oxide

0.1 – 5

1314-13-2

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016

Any concentrations shown in a range are to protect trade secret confidentiality or is due to batch variation. There are no additional ingredients present, which within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

SECTION 4 – FIRST AID MEASURES

DESCRIPTION OF NECESSARY FIRST AID MEASURES

EYE CONTACT	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention.
INHALATION	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
SKIN CONTACT	Wash affected areas with soap and water. If irritation develops, get medical attention. Remove and launder contaminated clothing before reuse.
INGESTION	Never give fluids or induce vomiting if the victim is unconscious or have convulsions. Seek immediate medical attention.
MOST IMPORTANT SYMPTOMS / EFFECTS, ACUTE AND DELAYED	
EYE CONTACT	May cause eye irritation.
INHALATION	May cause respiratory tract irritation.
SKIN CONTACT	Causes skin irritation.
INGESTION	May cause gastrointestinal irritation.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDS, IF NECESSARY

EYE CONTACT	N/A
INHALATION	N/A
SKIN CONTACT	N/A
INGESTION	N/A

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:	Foam CO ₂ , Dry Chemical, Water, Fog Foam
SUITABLE MEDIA	
EXTINGUISHING MEDIA:	N/A
UNSUITABLE MEDIA	
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	N/A

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016

SPECIAL PROTECTIVE ACTIONS N/A

FOR FIRE-FIGHTERS

SPECIAL EQUIPMENT FOR FIRE-FIGHTERS As in any fire, wear pressure-demand self-contained breathing apparatus (SCBA) (MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES FOR NON-EMERGENCY PERSONNEL

Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing dust/fumes/mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

FOR EMERGENCY PERSONNEL

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel.

ENVIRONMENTAL PRECAUTIONS

Avoid runoff into storm sewers and ditches that lead to waterways. Consult your state or local authorities for proper disposal in the event that more restrictive requirements apply.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP LARGE SPILLS

Discard any product, residue, disposal container or liner in full compliance with federal, state and local regulations.

SMALL SPILLS

Same protocol as above.

SECTION 7 – HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

PROTECTIVE MEASURES

Inspect for defects before use. Use in a well ventilated area. Keep out of reach of children. If user operations generate dust, fume, or mist, use ventilation to keep exposure to airborne contaminants below the respective exposure limits. Use safety glasses and gloves to handle.

GENERAL HYGIENE

Do not take internally. Wash thoroughly after handling.

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016

Remove contaminated clothing and wash before reuse. Avoid breathing dust/fumes/mist.

CONDITIONS FOR SAFE
STORAGE, INCLUDING
ANY INCOMPATIBILITIES

Store away from heat and moisture.

SECTION 8 – EXPOSURE CONTROL/PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

COMPOUND	CAS #	OSHA PEL 8- HR TWA	ACGIH TLV 8-HR TWA
Aluminum Oxide	1344-28-1	5 mg/m ³	1 mg/m ³
Hydrated amorphous silica	7631-86-9	<u>80 mg/m³</u> %SiO ₂	10 mg/m ³
Calcium Silicate	1344-95-2	15 mg/m ³ (Total Dust) 5 mg/m ³ (Respirable)	1 mg/m ³
Iron Oxide	1307-37-1	10 mg/m ³	5 mg/m ³
Calcium Hydroxide	1305-62-0	15 mg/m ³ (Total Dust) 5 mg/m ³ (Respirable)	5 mg/m ³
Magnesium Oxide	1309-48-4	15 mg/m ³	10 mg/m ³
Titanium Dioxide	13463-67-7	15 mg/m ³	10 mg/m ³
Zinc Oxide	1314-13-2	15 mg/m ³ (Total Dust) 5 mg/m ³ (Respirable)	2 mg/m ³ 10 mg/m ³ (Ceiling)

CONTROLS

ENGINEERING CONTROLS

Local exhaust ventilation may be necessary to control any air contaminants to within their respective exposure limits during the use of this product.

PERSONAL PROTECTIVE EQUIPMENT

Wear a NIOSH/MSHA approved respirator when the product used in poorly ventilated areas or if the workplace levels of ingredients exceed exposure limits. When contact is likely,

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016

wear gloves, safety glasses with a face shield, and clean protective clothing to cover arms and legs at a minimum.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

PHYSICAL STATE	Solid
COLOR	Green
ODOR	None
ODOR THRESHOLD	ND
pH	ND
MELTING POINT	ND
BOILING POINT	ND
FLASH POINT	ND
EVAPORATION RATE	ND
FLAMMABILITY (SOLID, GAS)	ND
UPPER / LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	N/A
VAPOR PRESSURE	ND
VAPOR DENSITY	ND
RELATIVE DENSITY	ND
SOLUBILITY(IES)	ND
PARTITION COEFFICIENT: N-OCTANOL / WATER	ND
AUTO-IGNITION TEMPERATURE	ND
DECOMPOSITION TEMPERATURE	ND
VISOCITY	ND

SECTION 10 – STABILITY AND REACTIVITY

REACTIVITY	This product is not reactive under normal conditions
CHEMICAL STABILITY	This product is stable under normal storage conditions.
POSSIBILITY OF	Will not occur under normal conditions.
HAZARDOUS REACTION	
CONDITIONS TO AVOID	None.
INCOMPATIBLE	Strong acids and oxidizing agents.
MATERIALS	
HAZARDOUS	Formaldehyde, carbon monoxide, carbon dioxide, nitrogen
DECOMPOSITION	oxide, ammonia, phenol, aromatic and aliphatic hydrocarbons,

Western Abrasives, Inc.
1170 NE 63rd Avenue
Portland, Oregon 97213
SDS Revision Date: May 13, 2016

SECTION 11 – TOXICOLOGICAL INFORMATION

IRRIATION / CORROSION Causes irritation to skin.

MUTAGENICITY	N/A
--------------	-----

REPRODUCTIVE TOXICITY N/A

SPECIFIC TARGET ORGAN TOXICITY	N/A
--------------------------------	-----

SPECIFIC TARGET ORGAN TOXICITY	N/A
--------------------------------	-----

ASPIRATION HAZARD	N/A
-------------------	-----

POTENTIAL ACUTE HEALTH EFFECTS

INHALATION	May cause irritation to respiratory tract.
------------	--

INGESTION	May cause irritation to gastrointestinal tract.
-----------	---

EYE CONTACT	N/A
-------------	-----

SKIN CONTACT	N/A
--------------	-----

INGESTION	N/A
-----------	-----

SHORT TERM EXPOSURE – POTENTIAL ND

SHORT TERM EXPOSURE – POTENTIAL	ND
---------------------------------	----

LONG TERM EXPOSURE – POTENTIAL	ND
--------------------------------	----

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016

IMMEDIATE EFFECTS

LONG TERM EXPOSURE – POTENTIAL ND

DELAYED EFFECTS

POTENTIAL CHRONIC HEALTH EFFECTS

GENERAL ND

CARCINOGENICITY N/A

MUTAGENICITY N/A

TERATOGENICITY N/A

DEVELOPMENTAL EFFECTS N/A

FERTILITY EFFECTS N/A

NUMERICAL MEASURES OF TOXICITY ND

(ACUTE TOXICITY ESTIMATE)

TOXICOLOGICAL DATA:

INGREDIENT	ORAL RAT (LD50)	SKIN RABBIT (LD50)	INHALATION RAT (LC50)
Aluminum Oxide	>5000 mg/kg	N/A	N/A
Gamma-Aminopropyltriethoxysilane	N/A	>2000 mg/kg	>7.35 mg/l
Pigment Green 7	>5000 mg/kg	>5000 mg/kg	N/A
Amorphous Silica	>22500 mg/kg	N/A	N/A
Calcium Silicate	>5000 mg/kg	N/A	N/A
Iron Oxide	>5000 mg/kg	N/A	N/A
Calcium Hydroxide	>5000 mg/kg	N/A	N/A
Magnesium Oxide	>3870 mg/kg	N/A	N/A
Titanium Dioxide	>5000 mg/kg	>10000 mg/kg	>6.82 mg/l
Zinc Oxide	>5000 mg/kg	N/A	N/A

SECTION 12 – ECOLOGICAL INFORMATION

TOXICITY	ND
PERSISTENCE AND DEGRADABILITY	ND
BIOACCUMULATIVE POTENTIAL	ND
MOBILITY IN SOIL	ND
OTHER ADVERSE EFFECTS	ND

SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL Review all local, state, and federal regulations concerning

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016

CONSIDERATIONS	health and pollution for appropriate disposal procedures.
----------------	---

SECTION 14 – TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME	Not regulated
--------------------------	---------------

SECTION 15 – REGULATORY INFORMATION

U.S. FEDERAL REGULATION

OSHA	Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)
CERLA – SARA HAZARD CATEGORY	This product has been reviewed according to the EPA “Hazard Categories” promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following category: None.
SARA SECTION 313	This product does contains toxic chemical(s) at or above the de minimus concentrations subject to the reporting requirements of section 313 of Title III Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.
TOXIC SUBSTANCES CONTROL ACT	This product meets the compositional requirements of the Toxic Substances Control Act and contains only chemical ingredients that are listed on the TSCA inventory.
CALIFORNIA PROP. 65	This product contains no chemical(s) known to California to cause cancer and/or birth defects or other reproductive harm.

SECTION 16 – OTHER INFORMATION

HMIS RATINGS	HEALTH	FLAMMABILITY	REACTIVITY	PERSONAL PROTECTION
	1	1	0	

EUROPEAN PRECAUTIONARY PICTOGRAMS

RUBBER BONDED GRINDING WHEELS

Western Abrasives, Inc.

1170 NE 63rd Avenue

Portland, Oregon 97213

SDS Revision Date: May 13, 2016



PREVIOUS SDS REVISION 2/14

DATE

REASON FOR REVISION ND

VOLATILE ORGANIC ND

COMPOUNDS (VOC'S)

LEGEND

N/A – Not Applicable, ND – Not Determined

ABBREVIATIONS USED

ACGIH – American Conference of Governmental Industrial Hygienists

OSHA – Occupational Safety and Health Administration

TLV – Threshold Limit Value

PEL – Permissible Exposure Limit

TWA – Time Weighted Average

STEL – Short Term Exposure Limit

NTP – National Toxicology Program

IARC – International Agency for Research on Cancer

NOTICE TO READER

The information contained herein is based on the data available to us and is believed to be correct. However, Western Abrasives, Inc. makes no warranty, express or implied regarding the accuracy of this data or the results to be obtained from the use thereof.

END OF SAFETY DATA SHEET