


```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
# Seaborn library can be used to draw a variety of charts such as
# regression plots
import seaborn as sns
```

```
dataset = sns.load_dataset('titanic')
dataset.head()
```

	survived	pclass	sex	age	sibsp	parch	fare	embarked	class	who
0	0	3	male	22.0	1	0	7.2500	S	Third	male
1	1	1	female	38.0	1	0	71.2833	C	First	woman
2	1	3	female	26.0	0	0	7.9250	S	Third	woman
3	1	1	female	35.0	1	0	53.1000	S	First	woman
4	0	3	male	35.0	0	0	8.0500	S	Third	male


```
sns.distplot(dataset['fare'])
```

```
/usr/local/lib/python3.7/dist-packages/seaborn/distributions.py:2619: FutureWarning: `FutureWarning`
warnings.warn(msg, FutureWarning)
<matplotlib.axes._subplots.AxesSubplot at 0x7f51ae481750>
```




```
# to remove kernel density estimation line use kde = False
sns.distplot(dataset['fare'], kde=False)
```

```
/usr/local/lib/python3.7/dist-packages/seaborn/distributions.py:2619: FutureWarning.warn(msg, FutureWarning)
<matplotlib.axes._subplots.AxesSubplot at 0x7f51ac295a10>
```




```
# sort individual data values in classes of bins
sns.distplot(dataset['fare'], kde=False, bins=10)
```

```
/usr/local/lib/python3.7/dist-packages/seaborn/distributions.py:2619: FutureWarning.warn(msg, FutureWarning)
<matplotlib.axes._subplots.AxesSubplot at 0x7f51abd6e990>
```




```
# display the mutual distribution of each column
sns.jointplot(x='age', y='fare', data=dataset)
```

```
<seaborn.axisgrid.JointGrid at 0x7f51abce8710>
```



```
# for hexagonal design of plot
sns.jointplot(x='age', y='fare', data=dataset, kind='hex')
```

```
<seaborn.axisgrid.JointGrid at 0x7f51abce9410>
```



```
dataset = dataset.dropna()
```

```
# pairplot plots a joint plot for all the possible
# combination of numeric and Boolean columns
```

```
sns.pairplot(dataset)
```

```

-----
KeyError                                Traceback (most recent call last)
/usr/local/lib/python3.7/dist-packages/numpy/lib/histograms.py in
_unsigned_subtract(a, b)
    350     try:
--> 351         dt = signed_to_unsigned[dt.type]
    352     except KeyError:

```

**KeyError:** <class 'numpy.bool\_'>

During handling of the above exception, another exception occurred:


```


TypeError                                Traceback (most recent call last)
-----
15 frames
<__array_function__ internals> in histogram_bin_edges(*args, **kwargs)

/usr/local/lib/python3.7/dist-packages/numpy/lib/histograms.py in
_unsigned_subtract(a, b)
    351         dt = signed_to_unsigned[dt.type]
    352     except KeyError:
--> 353         return np.subtract(a, b, dtype=dt)
    354     else:
    355         # we know the inputs are integers, and we are deliberately
casting

```

**TypeError:** numpy boolean subtract, the ``-`` operator, is not supported, use the bitwise\_xor, the ``^`` operator, or the logical\_xor function instead.





```
sns.pairplot(dataset, hue='sex')
```

```

ValueError                                Traceback (most recent call last)
<ipython-input-14-35ffbbc0d2e4> in <module>()
----> 1 sns.pairplot(dataset, hue='sex')

```

16 frames

```

/usr/local/lib/python3.7/dist-packages/scipy/_lib/_util.py in
_asarray_validated(a, check_finite, sparse_ok, objects_ok, mask_ok,
as_inexact)


```

```

    247     if not objects_ok:
    248         if a.dtype is np.dtype('O'):
--> 249             raise ValueError('object arrays are not supported')
    250     if as_inexact:
    251         if not np.issubdtype(a.dtype, np.inexact):


```

**ValueError:** object arrays are not supported



```
# rugplot() is used to draw small bars along x-axis for each  
sns.rugplot(dataset['fare'])
```

<matplotlib.axes.\_subplots.AxesSubplot at 0x7f51a4694350>



---

✓ 0s completed at 18:45

● ✕