

User login and Activity logs API (SSO)

User login review

This API returns a list of user login events within a specified date and time range.

Endpoint

Method: GET

Base URL: <https://api.example.com/sso/v1>

Full URL with parameters:

https://api.example.com/sso/v1/login?start_date=01/01/2026&end_date=31/01/2026

Authentication

This API uses Bearer Token authentication. Include the `Authorization` header with your access token in your request: `Authorization: Bearer <your\_access\_token>`.

Query Parameters

Parameter	Type	Required	Description	Example
Start date	string	Yes	The beginning of the date range for the events to retrieve	01/01/2026
End date	string	Yes	The end of the date range for the events to retrieve	31/01/2026

Response

A successful request returns HTTP 200 with a JSON array of event objects. An empty array [] is returned if no event exists in the specified range.

Response Schema

Field	Type
Device type	string
Login Time	Date Time
State	string
Auto ID	int
User Agent	string
Browser	string
Login Type	object
IP Adress	string
Username	string
Error	string
User Email	string

Sample response

JSON

```
[
  {
    "Device type": "Desktop",
    "Login Time": "2026-01-15T08:30:00Z",
    "State": "Success",
    "Auto ID": 1001,
    "User Agent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64)",
    "Browser": "Chrome",
    "Login Type": { "method": "SSO" },
    "IP Adress": "192.168.1.1",
    "Username": "jdoe",
```

```
[
  {
    "Error": null,
    "User Email": "jdoe@example.com"
  }
]
```

Error Responses

The API returns standard HTTP status codes. All error responses include JSON body with an error message.

Status code	Meaning	Description
200 OK	Success	Request succeeded. Returns a JSON array of event objects.
400 Bad Request	Invalid Input	Start Date or End Date is missing, malformed, or in an unsupported format.
401 Unauthorized	Auth Failed	Missing or invalid basic Auth credentials.
500 Server Error	Server Fault	An unexpected error occurred on the server. Retry after a short delay.

User Activity Overview

This API endpoint returns a list of user activity log events within a specified date and time range. It is designed for audit logging, monitoring, and event reporting use cases.

Endpoint

Method: GET

Base URL: <https://api.example.com/sso/v1>

Full URL with parameters:

https://api.example.com/sso/v1/activity?start_date=01/01/2026&end_date=31/01/2026

Authentication

This API uses Bearer Token authentication. Include the `Authorization` header with your access token in your request: `Authorization: Bearer <your\_access\_token>`.

Query Parameters

Parameter	Type	Required	Description	Example
Start date	string	Yes	The beginning of the date range for the events to retrieve	01/01/2026
End date	string	Yes	The end of the date range for the events to retrieve	31/01/2026

Response

A successful request returns HTTP 200 with a JSON array of event objects. An empty array [] is returned if no event exists in the specified range.

Response schema

Field	Type
App Name	string
Emil Snapshot	Date Time
Name Snapshot	string
Page Title	int
Page URL	string
Occured At	string
Public IP	object
Browser	string

User Agent	string
Error	string
Full Name	string
Email	string
User Roles	string

Sample response

JSON

```
[
  {
    "App Name": "DashboardApp",
    "Emil Snapshot": "2026-01-15T09:00:00Z",
    "Name Snapshot": "John Doe",
    "Page Title": 101,
    "Page URL": "https://app.example.com/dashboard",
    "Occured At": "2026-01-15T09:00:00Z",
    "Public IP": { "ip": "203.0.113.195" },
    "Browser": "Chrome",
    "User Agent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64)",
    "Error": null,
    "Full Name": "John Doe",
    "Email": "jdoe@example.com",
    "User Roles": "Admin"
  }
]
```

Error Responses

The API returns standard HTTP status codes. All error responses include JSON body with an error message.

Status code	Meaning	Description
-------------	---------	-------------

200 OK	Success	Request succeeded. Returns a JSON array of event objects.
400 Bad Request	Invalid Input	Start Date or End Date is missing, malformed, or in an unsupported format.
401 Unauthorized	Auth Failed	Missing or invalid basic Auth credentials.
500 Server Error	Server Fault	An unexpected error occurred on the server. Retry after a short delay.

Troubleshooting

- **401 Unauthorized errors:** Check token validity and ensure the Authorization header includes a valid Bearer token.
- **500 Server Errors:** Retry your request after a short delay, as this indicates a temporary server issue.
- **Invalid input errors:** Verify date formats and ensure required parameters like start_date and end_date are provided correctly.

FAQs

1. How can I retrieve logs for a specific user?
Currently, logs are retrieved by date range. You can filter the returned array by the Username or Email field to isolate a specific user's logs.
2. What is the format for the date parameter?
Date parameters should be formatted as dd/mm/yyyy (e.g., 01/01/2026).