MediaWiki API help

This is an auto-generated MediaWiki API documentation page.

Documentation and examples: https://www.mediawiki.org/wiki/API

action=expandtemplates

(main | expandtemplates)

• This module requires read rights.

Source: MediaWikiLicense: GPL-2.0+

Expands all templates in wikitext.

• https://www.mediawiki.org/wiki/API:Parsing_wikitext#expandtemplates

```
Parameters: title
```

Title of page.

Default: API

text

Wikitext to convert.

This parameter is required.

revid

Revision ID, for {{REVISIONID}} and similar variables.

Type: integer

prop

Which pieces of information to get.

Note that if no values are selected, the result will contain the wikitext, but the output will be in a deprecated format.

wikitext

The expanded wikitext.

categories

Any categories present in the input that are not represented in the wikitext output.

properties

Page properties defined by expanded magic words in the wikitext.

volatile

Whether the output is volatile and should not be reused elsewhere within the page.

tti

The maximum time after which caches of the result should be invalidated.

modules

Any ResourceLoader modules that parser functions have requested be added to the output. Either jsconfigvars or encodedjsconfigvars must be requested jointly with modules.

jsconfigvars

Gives the JavaScript configuration variables specific to the page.

encodedjsconfigvars

Gives the JavaScript configuration variables specific to the page as a JSON string.

parsetree

The XML parse tree of the input.

Values (separate with |): wikitext, categories, properties, volatile, ttl, modules, jsconfigvars, encodedjsconfigvars, parsetree

includecomments

Whether to include HTML comments in the output.

Type: boolean (<u>details</u>)

generatexml

Deprecated.

Generate XML parse tree (replaced by prop=parsetree).

Type: boolean (details)

Example:

Retrieved from "https://codex.wordpress.org/Special:ApiHelp"