

MediaWiki API help

This is an auto-generated MediaWiki API documentation page.

Documentation and examples: <https://www.mediawiki.org/wiki/API>

action=revisiondelete

([main](#) | **revisiondelete**)

- This module requires read rights.
- This module requires write rights.
- This module only accepts POST requests.
- Source: MediaWiki
- License: [GPL-2.0+](#)

Delete and undelete revisions.

- <https://www.mediawiki.org/wiki/API:Revisiondelete>

Parameters:

type

Type of revision deletion being performed.

This parameter is required.

One of the following values: revision, archive, oldimage, filearchive, logging

target

Page title for the revision deletion, if required for the type.

ids

Identifiers for the revisions to be deleted.

This parameter is required.

Separate values with |. Maximum number of values is 50 (500 for bots).

hide

What to hide for each revision.

Values (separate with |): content, comment, user

show

What to unhide for each revision.

Values (separate with |): content, comment, user

suppress

Whether to suppress data from administrators as well as others.

One of the following values: yes, no, nochange

Default: nochange

reason

Reason for the deletion or undeletion.

token

A "csrf" token retrieved from [action=query&meta=tokens](#)

This parameter is required.

Examples:

Hide content for revision 12345 on the page Main Page.

[api.php?action=revisiondelete&target=Main%20Page&type=revision&ids=12345&hide=content&token=123ABC](#) [\[open in sandbox\]](#)

Hide all data on log entry 67890 with the reason BLP violation.

[api.php?action=revisiondelete&type=logging&ids=67890&hide=content|comment|user&reason=BLP%20violation&token=123ABC](#) [\[open in sandbox\]](#)

Retrieved from "<https://codex.wordpress.org/Special:ApiHelp>"