Search resources

add_ping(int|WP_Post $post, string|array $uri): int|false

Adds a URL to those already pinged.

Parameters

$post int|WP_Post required

Post ID or post object.

$uri string|array required

Ping URI or array of URIs.

Return

int|false How many rows were updated.

Source

wp-includes/post.php

Expand code   Copy

```php
function add_ping( $post, $uri ) {
    global $wpdb;

    $post = get_post( $post );

    if ( ! $post ) {
        return false;
    }

    $pung = trim( $post->pinged );
    $pung = preg_split( '/\s/', $pung );

    if ( is_array( $uri ) ) {
```

View all references · View on Trac · View on GitHub

Hooks

apply_filters('add_ping', string $new)

Filters the new ping URL to add for the given post.

Related

Uses

[clean_post_cache()](#)	
wp-includes/post.php	

[wpdb::update()](#)	
wp-includes/class-wpdb.php	

[Show 2 more](#)

Used by

[pingback()](#)	
wp-includes/comment.php	

Changelog

Version	Description
[4.7.0](#)	$uri can be an array of URIs.
[1.5.0](#)	Introduced.

User Contributed Notes

You must [log in](#) before being able to contribute a note or feedback.

[About](#)

[News](#)

[Hosting](#)

[Privacy](#)

[Showcase](#)

[Themes](#)

[Plugins](#)

[Patterns](#)

[Learn](#)

[Documentation](#)

[Developers](#)

[WordPress.tv ↗](#)

[Get Involved](#)

[Events](#)

[Donate ↗](#)

[Swag Store ↗](#)

[WordPress.com ↗](#)

[Matt ↗](#)

[bbPress ↗](#)

[BuddyPress ↗](#)