

[Home](#) / [Reference](#) / [Functions](#) / `add_permastruct()`

Search resources



```
add_permastruct( string $name, string $struct, array $args = array() )
```

Adds a permalink structure.

Description

See also

- [WP\\_Rewrite::add\\_permastruct\(\)](#)

Parameters

**\$name** string required

Name for permalink structure.

**\$struct** string required

Permalink structure.

**\$args** array optional

Arguments for building the rules from the permalink structure, see `WP_Rewrite::add_permastruct()` for full details.

Default: `array()`

Source

wp-includes/rewrite.php

[Expand code](#)[Copy](#)

```
function add_permastruct( $name, $struct, $args = array() ) {
    global $wp_rewrite;

    // Back-compat for the old parameters: $with_front and $sep_mask.
    if ( ! is_array( $args ) ) {
        $args = array( 'with_front' => $args );
    }

    if ( func_num_args() === 4 ) {
        $args['ep_mask'] = func_get_arg( 3 );
    }

    $wp_rewrite->add_permastruct( $name, $struct, $args );
}
```

[View all references](#) · [View on Trac](#) · [View on GitHub](#)

Related

Uses

[WP\\_Rewrite::add\\_permastruct\(\)](#)

wp-includes/class-wp-rewrite.php

Used by

[WP\\_Taxonomy::add\\_rewrite\\_rules\(\)](#)

wp-includes/class-wp-taxonomy.php

[WP\\_Post\\_Type::add\\_rewrite\\_rules\(\)](#)

wp-includes/class-wp-post-type.php

Changelog

Version	Description
<a href="#">3.0.0</a>	Introduced.

User Contributed Notes

Marcio Zebedeu5 years ago

0

You can change rules to rewrite your type of posting as well as change your structure. Imagine that your permalink structure is like:

```
/locations/%k7_locations%
```

you can switch to

```
/test/%message%
```

Copy

```
global $wp_rewrite;
$args = array(
    'with_front' => true,
    'ep_mask' => 3,
    'paged' => 1,
    'feed' => 1,
    'forcomments' => 0,
    'walk_dirs' => 1,
    'endpoints' => 1
);
add_permastruct( 'locations', 'test/%message/', $args);
```

output:

Copy

Array

```
(  
    [with_front] => 1  
    [ep_mask] => 3  
    [paged] => 1  
    [feed] => 1  
    [forcomments] => 0  
    [walk_dirs] => 1  
    [endpoints] => 1  
    [struct] => /test/%message/%  
)
```

[Log in to add feedback](#)

Philipp Stracker3 years ago

^ 0 v

To add a custom URL-/permalink-structure, this function must be called on every request (not only once). I usually do this in the 'init' hook.

However, the related function `flush_rewrite_rules()` should only be called when the permalink structure changes.

Sample:

Copy

```
add_action( 'init', 'wpdocs_custom_permalink' );  
function wpdocs_custom_permaLinks() {  
    // Register the permastruct and rewrite tag on every page load:  
    add_permastruct( 'legal', 'legal/%my_slug%', [ 'ep_mask' => EP_PERMALINK ] );  
    add_rewrite_tag( '%my_slug%', '([^/]+)', "post_type=page&name=" );  
  
    // Only flush rewrite rules, if your permalink changed (e.g. on plugin activation):  
    if ( $has_changed ) {  
        flush_rewrite_rules();  
    }  
}
```

[Log in to add feedback](#)

You must [log in](#) before being able to contribute a note or feedback.

[About](#)  
[News](#)  
[Hosting](#)  
[Privacy](#)  
[Showcase](#)  
[Themes](#)  
[Plugins](#)  
[Patterns](#)

[Learn](#)  
[Documentation](#)  
[Developers](#)  
[WordPress.tv ↗](#)  
[Get Involved](#)  
[Events](#)  
[Donate ↗](#)  
[Swag Store ↗](#)  
[WordPress.com ↗](#)  
[Matt ↗](#)  
[bbPress ↗](#)  
[BuddyPress ↗](#)



CODE IS POETRY