



[Home](#) / [Reference](#) / [Functions](#) / `admin_url()`

Search resources



```
admin_url( string $path = "", string $scheme = 'admin' ): string
```

Retrieves the URL to the admin area for the current site.

Parameters

\$path string optional

Path relative to the admin URL.

Default: ''

\$scheme string optional

The scheme to use. Default is 'admin', which obeys [force_ssl_admin\(\)](#) and [is_ssl\(\)](#).

'http' or 'https' can be passed to force those schemes.

Default: 'admin'

Return

string Admin URL link with optional path appended.

Source

wp-includes/link-template.php

Copy

```
function admin_url( $path = '', $scheme = 'admin' ) {  
    return get_admin_url( null, $path, $scheme );  
}
```

[View all references](#) · [View on Trac](#) · [View on GitHub](#)

Related

Uses

[get_admin_url\(\)](#)

wp-includes/link-template.php

Used by

[WP_Plugin_Dependencies::check_plugin_dependencies_during_ajax\(\)](#)

wp-includes/class-wp-plugin-dependencies.php
WP_Plugin_Dependencies::display_admin_notice_for_unmet_dependencies()
wp-includes/class-wp-plugin-dependencies.php
WP_Widget_Media::get_l10n_defaults()
wp-includes/widgets/class-wp-widget-media.php
wp_admin_bar_edit_site_menu()
wp-includes/admin-bar.php
deactivated_plugins_notice()
wp-admin/includes/plugin.php

[Show 110 more](#)

Changelog

Version	Description
2.6.0	Introduced.

User Contributed Notes

Codex8 years ago

^ 13 v

Examples

Copy

```
<?php echo admin_url(); ?>
```

Output: <http://example.com/wp-admin/> (or https protocol when appropriate)

Copy

```
// Generate URL to admin's "Categories" page, and force https
<?php echo admin_url( 'edit-tags.php?taxonomy=category', 'https' ); ?>
```

Output: <https://example.com/wp-admin/edit-tags.php?taxonomy=category>

[Log in to add feedback](#)

xandercalvert2 years ago

^ 4 v

If you are looking for the post edit url for admin end and you have the post id (suppose `$post_id`) with you, then you can use the following code for getting the url.

Copy

```
$post_id = 1731; // For example
$post_url = add_query_arg( array(
    'post' => $post_id
```

```
post => $post_id,  
'action' => 'edit',  
) , admin_url( 'post.php' ) );  
  
// returns http://example.com/wp-admin/post.php?post=1731&action=edit
```

[Log in to add feedback](#)

Codex8 years ago

^ 1 ▾

Default Usage

Copy

```
<?php $url = admin_url(); ?>
```

[Log in to add feedback](#)

Kowsar Hossain10 months ago

^ 1 ▾

The presence of a leading slash in the path doesn't affect the output, as it will be internally removed. Thus, both calls to `admin_url()` will yield the same result:

Copy

```
admin_url( 'test' ); // returns http://example.com/wp-admin/test  
admin_url( '/test' ); // returns http://example.com/wp-admin/test
```

[Log in to add feedback](#)

israelakinola1 year ago

^ -1 ▾

Logout Users based on specific capabilities and role

Expand codeCopy

```
if ( ! current_user_can( 'edit_posts' ) && ! is_admin() ) {  
    $redirect_url = site_url();  
} else {  
    $redirect_url = '/wp-login.php';  
}  
  
function wpdocs_redirect_after_logout() {  
    global $redirect_url;  
  
    wp_safe_redirect( $redirect_url );  
  
    exit;  
}
```

[Log in to add feedback](#)

Codex8 years ago

^ -6 v

Usage

Copy

```
<?php admin_url( $path, $scheme ); ?>
```

[Log in to add feedback](#)

You must [log in](#) before being able to contribute a note or feedback.

- [About](#)
- [News](#)
- [Hosting](#)
- [Privacy](#)
- [Showcase](#)
- [Themes](#)
- [Plugins](#)
- [Patterns](#)
- [Learn](#)
- [Documentation](#)
- [Developers](#)
- [WordPress.tv ↗](#)
- [Get Involved](#)
- [Events](#)
- [Donate ↗](#)
- [Swag Store ↗](#)
- [WordPress.com ↗](#)
- [Matt ↗](#)
- [bbPress ↗](#)
- [BuddyPress ↗](#)



CODE IS POETRY

