MediaWiki API help

This is an auto-generated MediaWiki API documentation page.

Documentation and examples: https://www.mediawiki.org/wiki/API

action=undelete

(main | **undelete**)

- This module requires read rights.
- This module requires write rights.
- This module only accepts POST requests.
- Source: MediaWiki
- License: [GPL-2.0+](GPL-2.0+)

Restore revisions of a deleted page.

A list of deleted revisions (including timestamps) can be retrieved through list=deletedrevs, and a list of deleted file IDs can be retrieved through list=filearchive.

- https://www.mediawiki.org/wiki/API:Undelete

Parameters:

title

    Title of the page to restore.

    This parameter is required.

reason

    Reason for restoring.

    Default: (empty)

tags

    Change tags to apply to the entry in the deletion log.

    Values (separate with |):

timestamps

    Timestamps of the revisions to restore. If both *timestamps* and *fileids* are empty, all will be restored.

    Type: list of timestamps (allowed formats)
    Separate values with |. Maximum number of values is 50 (500 for bots).

fileids

    IDs of the file revisions to restore. If both *timestamps* and *fileids* are empty, all will be restored.

    Type: list of integers
    Separate values with |. Maximum number of values is 50 (500 for bots).

watchlist

    Unconditionally add or remove the page from the current user's watchlist, use preferences or do not change watch.

    One of the following values: watch, unwatch, preferences, nochange
    Default: preferences

token

    A "csrf" token retrieved from action=query&meta=tokens

    This parameter is required.

Examples:

Undelete page `Main Page`.
    api.php?action=undelete&title=Main%20Page&token=123ABC&reason=Restoring%20main%20page [open in sandbox]
Undelete two revisions of page `Main Page`.
    api.php?action=undelete&title=Main%20Page&token=123ABC&timestamps=2007-07-03T22:00:45Z|2007-07-02T19:48:56Z [open in sandbox]

Retrieved from "https://codex.wordpress.org/Special:ApiHelp"