

MediaWiki API help

This is an auto-generated MediaWiki API documentation page.

Documentation and examples: <https://www.mediawiki.org/wiki/API>

action=tag

([main](#) | **tag**)

- This module requires read rights.
- This module requires write rights.
- This module only accepts POST requests.
- Source: MediaWiki
- License: [GPL-2.0+](#)

Add or remove change tags from individual revisions or log entries.

- <https://www.mediawiki.org/wiki/API:Tag>

Parameters:

rcid

One or more recent changes IDs from which to add or remove the tag.

Type: list of integers

Separate values with |. Maximum number of values is 50 (500 for bots).

revid

One or more revision IDs from which to add or remove the tag.

Type: list of integers

Separate values with |. Maximum number of values is 50 (500 for bots).

logid

One or more log entry IDs from which to add or remove the tag.

Type: list of integers

Separate values with |. Maximum number of values is 50 (500 for bots).

add

Tags to add. Only manually defined tags can be added.

Values (separate with |):

remove

Tags to remove. Only tags that are either manually defined or completely undefined can be removed.

Separate values with |. Maximum number of values is 50 (500 for bots).

reason

Reason for the change.

Default: (empty)

token

A "csrf" token retrieved from [action=query&meta=tokens](#)

This parameter is required.

Examples:

Add the vandalism tag to revision ID 123 without specifying a reason

[api.php?action=tag&revid=123&add=vandalism&token=123ABC](#) [\[open in sandbox\]](#)

Remove the spam tag from log entry ID 123 with the reason Wrongly applied

[api.php?action=tag&logid=123&remove=spam&reason=Wrongly+applied&token=123ABC](#) [\[open in sandbox\]](#)

Retrieved from "<https://codex.wordpress.org/Special:ApiHelp>"