



CL1002 <i>Programming</i> <i>Fundamentals Lab</i>	Lab 08 Nested Loops and Nd-Arrays
--	---

NATIONAL UNIVERSITY OF COMPUTER AND EMERGING SCIENCES

Fall 2024

AIMS AND OBJECTIVES

Aim:

To understand and implement the concepts of nested loops and N-dimensional arrays (2D and 3D arrays) in C programming.

Objectives:

- Learn how nested loops work and their application in solving problems that require repeated actions.
- Understand how to declare, initialize, and manipulate 2D and 3D arrays.
- Apply nested loops to handle complex data structures like 2D and 3D arrays.
- Solve problems involving array operations, matrix manipulations, and pattern generation using nested loops.

Introduction

In programming, loops execute a block of code multiple times. Sometimes, we need to execute multiple loops inside another loop to handle complex operations. This concept is known as **nested loops**. Nested loops are useful when dealing with multidimensional data structures like matrices (2D arrays) and 3D arrays, where each element can be accessed by iterating through each dimension.

N-dimensional arrays (Nd-arrays) allow storing data in a structured format, such as grids, matrices, or tables. A **2D array** represents data in rows and columns, making it easy to work with matrices, while a **3D array** can represent a set of matrices or tables, adding another layer of complexity.

In the easiest way, A **2D-array** is multiple **1D-arrays**. And a **3D-array** is multiple **2D-arrays**.

Section 1: Nested Loops

Explanation: A nested loop is a loop inside another loop. The inner loop runs completely every time the outer loop executes once. This structure is particularly useful for:

- Generating patterns
- Iterating over multi-dimensional arrays
- Performing repeated operations that depend on each other.

Example 1: Generating a Simple Pattern

Task: Print a right-angled triangle pattern using nested loops.

```
#include <stdio.h>
int main() {
    int i, j;
    for (i = 1; i <= 5; i++) { // Outer loop for rows
        for (j = 1; j <= i; j++) { // Inner loop for columns
            printf("* ");
        }
        printf("\n");
    }
    return 0;
}
```

Output:

```
*
* *
* * *
* * * *
* * * * *
```

Example 2: Multiplication Table

Task: Display a multiplication table up to 5x5 using nested loops.

```
#include <stdio.h>

int main() {
    int i, j;
    for (i = 1; i <= 5; i++) {
        for (j = 1; j <= 5; j++) {
            printf("%d\t", i * j);
        }
        printf("\n");
    }
    return 0;
}
```

Output:

1	2	3	4	5
2	4	6	8	10
3	6	9	12	15
4	8	12	16	20
5	10	15	20	25

Example 3: Inverted Pyramid Pattern

Task: Print an inverted right-angled pyramid pattern using nested loops.

```
#include <stdio.h>

int main() {
    int rows = 5;
    for (int i = rows; i >= 1; i--) { // Outer loop for rows
        for (int j = 1; j <= i; j++) { // Inner loop for columns
            printf("* ");
        }
        printf("\n");
    }
    return 0;
}
```

Output:

```
* * * * *
* * * *
* * *
* *
*
```

Reference:

- [Learn C Programming - Patterns](#)

Problem:

1. Write a C program to generate the following pattern:

```
1
1 2
1 2 3
1 2 3 4
```

Section 2: 2D Arrays and Nested Loops

Explanation: A 2D array is like a grid or table. Each element is identified by two indices: one for the row and one for the column. Nested loops are often used to iterate over 2D arrays.

Example 1: Matrix Addition

Task: Write a program to add two 2x2 matrices using nested loops.

```
#include <stdio.h>

int main() {
    int mat1[2][2] = {{1, 2}, {3, 4}};
    int mat2[2][2] = {{5, 6}, {7, 8}};
    int result[2][2];

    // Adding two matrices
    for (int i = 0; i < 2; i++) {
        for (int j = 0; j < 2; j++) {
            result[i][j] = mat1[i][j] + mat2[i][j];
        }
    }

    // Displaying the result
    printf("Sum of two matrices:\n");
    for (int i = 0; i < 2; i++) {
        for (int j = 0; j < 2; j++) {
            printf("%d ", result[i][j]);
        }
        printf("\n");
    }
    return 0;
}
```

Output:

```
6 8
10 12
```

References:

- Matrix Operations in C

Problems:

1. Write a program to take a 2D array input from the user and display its transpose.

Section 3: 3D Arrays and Nested Loops

Explanation: A 3D array can be visualized as multiple 2D grids stacked on top of each other. Each element is accessed using three indices. Nested loops are used to navigate through each layer, row, and column.

Example 1: Initializing a 3D Array

Task: Write a program to initialize and display a 2x2x2 3D array.

```
#include <stdio.h>

int main() {
    int arr[2][2][2] = {
        {{1, 2}, {3, 4}},
        {{5, 6}, {7, 8}}
    };

    // Displaying the 3D array
    for (int i = 0; i < 2; i++) {
        for (int j = 0; j < 2; j++) {
            for (int k = 0; k < 2; k++) {
                printf("%d ", arr[i][j][k]);
            }
            printf("\n");
        }
        printf("\n");
    }
    return 0;
}
```

Output:

```
1 2
3 4

5 6
7 8
```

References:

- 3D Array Manipulation

Problems:

1. Create a 3D array representing 2 pages of a 3x3 matrix. Initialize it and find the sum of all the elements on each page.

More problems :D

1. Write a C program that generates a sequence of prime numbers within a given range using nested loops.
2. Generate a pattern of odd numbers in decreasing order starting from a user-specified number using nested loops.
3. Write a C program to find the saddle point(s) in a given 3x3 matrix. A saddle point is an element that is the smallest in its row and the largest in its column.
4. Write a C program to multiply two matrices of size 3x3 and display the result matrix.
5. Write a C program to generate a diamond shape pattern using nested loops. The program should take the number of rows for the upper half of the diamond as input from the user.

```
  *
 * *
* * *
* * * *
 * * * *
  * * *
   * *
    *
```