# DEEPINSPECT AI

## AI DRIVEN NETWORK SECURITY SYSTEM

**Authors : Shashank Kumar Srivastava (** work.shashank.srivastava@gmail.com **), Ankit Raj, Aryan Gupta**

**Supervisors : Mr. Ajay Kumar (** Professor **) (** *ajaykushwahacse@gmail.com* **), Mr. Mohit Singh Yadav (** Assistant Professor **) (** *mohitsingh.yadav@ipec.org.in* **),** Inderprastha engineering college, Ghaziabad, Uttar Pradesh, India -201010

Department of Computer Science & Engineering, Inderprastha Engineering College, Ghaziabad, Uttar Pradesh, India,
Dr. APJ Abdul Kalam Technical University, Lucknow 226031, Uttar Pradesh

***Abstract --*** *In the evolving landscape of cybersecurity, traditional rule-based systems are increasingly insufficient to detect and respond to sophisticated threats. This research presents the design and development of an AI Driven Network Security System that leverages machine learning and data-driven models to proactively monitor, analyse, and secure network environments. By integrating real-time traffic analysis with anomaly detection techniques, the system can identify unusual behaviour patterns, flagging potential intrusions, and automating threat response. The core of the system utilizes supervised and unsupervised learning algorithms to improve accuracy over time, adapting to emerging threats without human intervention. This paper also explores the deployment of the model in a simulated network environment to assess its effectiveness in identifying common attacks such as DDoS, port scanning, and data exfiltration. Results demonstrate significant improvement in threat detection rates, reduced false positives, and enhanced responsiveness compared to conventional security solutions. The proposed system aims to bridge the gap between static defence mechanisms and the dynamic nature of cyber threats through intelligent automation.*

**Keywords:-** *Artificial Intelligence, Network Security, Intrusion Detection System (IDS), Anomaly Detection, Machine Learning.*

## 1. INTRODUCTION

As the digital landscape continues to expand, networks are increasingly exposed to a wide array of sophisticated and rapidly evolving cyber threats. Traditional security systems, which largely depend on static rules and signature-based detection methods, are struggling to keep pace with these modern attack techniques [1][6][27]. This growing complexity demands more intelligent, adaptive, and proactive solutions that can safeguard networks in real time. In response to this challenge, the project introduces an DeepInspect AI aimed at monitoring, analysing, and defending network environments through the use of machine learning (ML) and artificial intelligence (AI) [3][19][24].

### 1.1 BACKGROUND

The rapid advancement of digital infrastructure and the widespread adoption of connected devices have significantly expanded the attack surface for cybercriminals [25][26]. From large-scale Distributed Denial-of-Service (DDoS) attacks to highly targeted phishing and malware campaigns, modern threats have become more sophisticated and harder to detect using traditional tools [1][2][28]. Conventional network security mechanisms—such as firewalls, antivirus programs, and signature-based Intrusion Detection Systems (IDS)—rely heavily on known threat patterns, making them ineffective against zero-day exploits and stealthy attacks that mimic legitimate behaviour [6][29].

This evolving threat landscape has led to a growing interest in incorporating Artificial Intelligence (AI) and Machine Learning (ML) into cybersecurity solutions [19][23][24]. AI and ML enable systems to process massive amounts of network data, detect hidden patterns, and make autonomous decisions with minimal human intervention [3][22]. Specifically, anomaly-based models can learn what constitutes "normal" network behaviour and flag deviations as potential threats [1][10]. This dynamic approach increases adaptability and offers greater protection against previously unseen attacks [11][21].
Recent studies and practical implementations have shown that integrating AI into network defence not only improves detection accuracy but also supports real-time behaviour analysis and automated incident responses [4][8][14]. Nevertheless, challenges remain regarding the quality of training data, model accuracy, and the balance between detection sensitivity and false positives [7][12][20]. This project builds on these findings by developing a comprehensive AI-powered network security system that combines both supervised and unsupervised learning to deliver intelligent, adaptive, and scalable protection [5][15][30].

## 1.2 METHODOLOGY

The development of the DeepInspect AI followed a systematic methodology consisting of data acquisition, preprocessing, model development, integration, and evaluation:

***Data Collection:***
Network traffic was collected using packet sniffing tools such as Wireshark and TCPDump, along with publicly available datasets like CICIDS2017 and NSL-KDD [2][5][11]. These datasets include labelled entries for both normal behaviour and various forms of malicious activity, such as brute force attacks, infiltration, and port scans.

***Data Preprocessing:***
The collected network data was cleaned and pre-processed to extract essential features like source/destination IPs, ports, protocol types, flow durations, packet sizes, and byte rates. Redundant and irrelevant features were removed through feature selection techniques, and the data was normalized to enhance model performance and consistency [3][7].

***Model Selection and Training:***
Two types of models were employed:
**Supervised Learning Models (**e.g., **Random Forest, Support Vector Machines (SVM), Logistic Regression)** were trained on labelled datasets to detect known threats [2][3][8].

**Unsupervised Learning Models (**e.g., **K-Means Clustering, Isolation Forests)** were used to detect anomalies in unlabelled data, thereby identifying unknown or emerging threats [12][13][14].

Each model underwent training and validation using separate subsets of the dataset and was evaluated based on metrics such as detection accuracy, precision, recall, and false positive rates [4][9].

***System Integration and Real-Time Detection:***
The trained models were deployed into a real-time monitoring framework using Python and the Scikit-learn library. Live network packets were continuously processed through the detection pipeline. When an anomaly or known attack was identified, the system automatically generated alerts or executed predefined mitigation actions like blocking malicious IP addresses or isolating affected traffic [9][14][17].

***Evaluation:***

The effectiveness of the system was assessed using standard metrics—accuracy, precision, recall, and F1-score. A comparative study against traditional IDS solutions further demonstrated improvements in detection capability, response time, and overall adaptability [10][11][15].

## 2. LITERATURE REVIEW

The application of Artificial Intelligence (AI) and Machine Learning (ML) in cybersecurity has gained significant traction in recent years due to the limitations of traditional rule-based Intrusion Detection Systems (IDS). These conventional systems are often ineffective against sophisticated and evolving threats.
One of the earliest contributions to anomaly-based intrusion detection was made by Denning [1], who proposed a model for identifying unauthorized system access by monitoring deviations from normal behaviour. This foundational work paved the way for intelligent, behaviour-based security systems.
Dhanabal and Shantharajah [2] conducted a comparative analysis of machine learning algorithms using the KDD Cup 1999 dataset, demonstrating that algorithms such as Random Forest and Decision Trees could effectively classify known attacks. However, their study also emphasized the inability of these models to detect zero-day threats. Similar concerns were raised by Sommer and Paxson [6], who discussed the limits of ML in practical intrusion detection, particularly its susceptibility to adversarial manipulation and overfitting.
Buczak and Guven [3] provided a comprehensive survey of ML techniques in network security, categorizing methods into supervised, unsupervised, and semi-supervised learning. They highlighted the effectiveness of SVM, k-Means, and ensemble methods in various security applications. Additionally, Nguyen and Armitage [7] explored the role of traffic classification in anomaly detection, reinforcing the importance of pre-processing and feature selection.

Recent studies have shifted focus toward deep learning. Sahu and Yadav [4] applied Recurrent Neural Networks (RNNs) and Convolutional Neural Networks (CNNs) to model complex sequential attack patterns in network traffic. While the models showed improved detection accuracy, they required extensive computational resources and large training datasets. Similarly, Kim et al. [8] employed deep autoencoders to detect novel threats with high precision, though their performance decreased in high-speed network environments.

Vinayakumar et al. [9] presented a scalable deep learning framework for real-time intrusion detection using Long Short-Term Memory (LSTM) networks, capable of capturing temporal dependencies in traffic data. In another effort, Shone et al. [10] developed a non-symmetric deep autoencoder for unsupervised anomaly detection, showing promising results on benchmark datasets.

The CICIDS2017 dataset, introduced by the Canadian Institute for Cybersecurity, has emerged as a benchmark for modern IDS research. Sharafaldin et al. [5] demonstrated the dataset's utility in developing hybrid systems capable of detecting both known and unknown threats. Likewise, Ferrag et al. [11] reviewed CICIDS2017 applications and highlighted its richness in capturing contemporary attack vectors.

Despite these advancements, many systems still struggle with high false-positive rates and real-time performance limitations. Lin et al. [12] examined the trade-offs between detection accuracy and speed in IDS systems, concluding that lightweight models like decision trees, when combined with anomaly detection, can improve responsiveness. Shen et al. [13] integrated federated learning to enable collaborative threat detection without compromising data privacy, an emerging challenge in distributed systems.

This research proposes a hybrid AI-based solution that addresses these challenges using both supervised and unsupervised learning models to enhance adaptability and detection capability. Hybrid frameworks like those

proposed by Alrawashdeh and Purdy [14] and Tang et al. [15] have already shown that combining techniques such as deep learning and clustering significantly boosts the ability to detect zero-day attacks while maintaining operational efficiency.

## 3. APPLICATIONS

The DeepInspect AI has a wide range of applications across various domains that rely on secure, real-time data transmission and infrastructure protection. Some of the key applications include:

### 3.1 Enterprise Network Security

Organizations can deploy this system to continuously monitor internal networks, detect insider threats, prevent unauthorized access, and respond to attacks without manual intervention. It strengthens defence against advanced persistent threats (APTs) and targeted intrusions.

### 3.2 Cloud Infrastructure Protection

As businesses increasingly migrate to cloud environments, this system can be integrated with cloud platforms to analyse traffic between virtual machines, detect abnormal usage patterns, and secure APIs and services against misuse or attack.

### 3.3 Internet of Things (IoT) Environments

IoT networks are particularly vulnerable due to their distributed nature and limited built-in security. The proposed system can help identify compromised IoT devices, unusual behaviour, or botnet activity, enhancing overall IoT ecosystem resilience.

### 3.4 Critical Infrastructure Security

Sectors such as energy, healthcare, transportation, and finance can benefit from intelligent threat detection to safeguard operational technology (OT) systems and sensitive data from cyber sabotage or data breaches.

### 3.5 Educational and Research Networks

Academic institutions with large, open networks can use this system to protect student and research data while promoting safe internet usage and mitigating risks associated with open-access environments.

### 3.6 Government and Défense Systems

National security agencies can deploy AI-driven network security to protect classified data, monitor large-scale infrastructures, and respond to cyber warfare attempts in real-time with minimal human oversight.

## 4. ROLE, IMPACT & KEY TAKEAWAYS

The DeepInspect AI demonstrated a significant improvement in detecting and mitigating threats compared to conventional rule-based methods. Through the application of supervised and unsupervised machine learning algorithms, the system was able to analyse real-time network traffic, identify malicious patterns, and respond to anomalies effectively.

During testing, the system achieved a **40% reduction in network anomalies**, indicating a substantial decrease in undetected or misclassified threats. Additionally, it maintained an overall **efficiency rate of approximately 78%**, balancing accuracy, speed, and adaptability in various network conditions.

These outcomes confirm the system's potential as a scalable and intelligent security solution, capable of evolving with emerging cyber threats while minimizing the need for manual monitoring and intervention.

***Contamination Factor***

In anomaly detection algorithms, the **contamination factor** refers to the expected **proportion of anomalies** in the dataset. It helps the model determine how many data points should be classified as outliers. If the actual anomaly rate is unknown, this parameter acts as a best-guess estimate and influences the decision boundary.

***Random State***

The **random state** is a seed value used to ensure **reproducibility** of results. It controls the randomness involved in processes like sampling or model initialization. By setting a random state, you ensure that the algorithm produces consistent results across multiple runs.

***Comparative Analysis of Our Work vs. Existing Literature***

To validate these outcomes, the system was compared against multiple state-of-the-art approaches, each utilizing different AI methodologies. Below is an in-depth comparative analysis:

**Zhang et al. [20]** employed a hybrid CNN-LSTM model on the NSL-KDD dataset, achieving 84% accuracy. However, their reliance on static datasets limits real-time application.
**Our Advantage:** Our system dynamically adapts to live network traffic, enabling effective detection of both known and novel threats, ensuring operational resilience in real-time environments.

**Ahmed and Khan [21]** utilized ensemble methods (Decision Trees + SVM), reporting a 75% detection rate but with a high false positive rate in complex traffic.
**Our Advantage**: We reduced false positives by 18% while maintaining high accuracy under high-volume conditions, ensuring better reliability in production-grade networks.

**Patel et al. [22]** proposed a fast reinforcement learning-based IDS. Despite its speed, it was computationally expensive and lacked hardware scalability.
**Our Advantage**: Our model optimizes for both speed and efficiency, allowing cost-effective deployment even on mid-range infrastructure without sacrificing performance.

**Li et al. [23]** used Deep Belief Networks for anomaly detection with 82% accuracy but faced overfitting and long training times on high-dimensional data.
**Our Advantage**: We adopted lightweight unsupervised models like Isolation Forests that train faster and generalize better across dynamic and heterogeneous network environments.

**Hossain et al. [24]** introduced autoencoder-based anomaly detection with good irregularity detection but lacked an adaptive feedback loop and had a high false positive rate.
**Our Advantage**: Our model integrates a feedback-driven retraining mechanism, improving classification precision and adaptability to evolving traffic patterns.

**Sharma et al. [25]** focused on a federated learning-based IDS for IoT, emphasizing privacy but introducing synchronization overhead and communication-related privacy risks.
**Our Advantage**: Our centralized architecture ensures faster rollout and updates with minimal coordination overhead, enhancing scalability without compromising on speed.

**Bhatia and Reddy [26]** proposed a fuzzy logic + neural network system for better interpretability but faced scalability challenges in enterprise-scale environments.
**Our Advantage**: Our system is designed for seamless scalability, supporting both small-scale and enterprise-level networks with minimal manual configuration.

| Study | Methodology | Accuracy/Performance | Key Limitation | Our Strengths |
|---|---|---|---|---|
| *Zhang et al.[20]* | *CNN-LSTM* | *84%* | *Static dataset only* | *Real-time adaptability* |
| *Ahmed & Khan [21]* | *Ensemble (DT + SVM)* | *75%* | *High false positives* | *18% reduction in false positives* |
| *Patel et al.[22]* | *Reinforcement Learning* | *High speed* | *High resource cost* | *Efficient with moderate resources* |
| *Li et al. [23]* | *Deep Belief Networks* | *82%* | *Long training time* | *Lightweight, faster retraining* |
| *Hossain et al. [24]* | *AutoEncoders* | *80%+* | *High false positives* | *Better feedback and adaptation* |
| *Sharma et al. [25]* | *Federated Learning* | *Secure, distributed* | *Privacy & sync issues* | *Simpler, centralized deployment* |
| *Bhatia & Reddy [26]* | *Fuzzy + Neural Net* | *High interpretability* | *Poor scalability* | *Better for large enterprise networks* |
| *Alazab et al.[27]* | *Blockchain + AI* | *Strong data integrity* | *Processing delay* | *Faster real-time responses* |

**Alazab et al.** developed a blockchain-integrated AI IDS for secure logging, which added traceability but also latency due to ledger overhead.
**Our Advantage**: Prioritizing speed, our system ensures rapid threat detection and mitigation—critical during active cyber-attacks—without the delay introduced by blockchain layers.

The comparison across multiple studies clearly shows that the proposed system not only holds its ground in terms of detection accuracy and anomaly
response but excels in **practical deployment scenarios** where **real-time response, resource efficiency,** and **low maintenance** overhead are critical.

Unlike many existing models that either overfit, lack scalability, or demand high computational resources, our DeepInspect AI strikes an optimal balance. It offers dynamic adaptability, moderate training complexity, and live feedback loops—making it not only technically sound but also deployable in real-world organizational environments.

***RESULT***

The **DeepInspect AI** outperformed conventional rule-based and earlier AI-based models across multiple performance metrics. By harnessing a hybrid approach using both supervised and unsupervised learning techniques, the system not only enhanced threat detection accuracy but also ensured faster, more reliable responses in dynamic environments.

A key achievement was a **40% reduction in undetected or misclassified anomalies**, showing the model's improved ability to discern between normal and malicious network behaviour. This resulted in fewer blind spots and better protection against stealthy attacks.
The system maintained an **overall efficiency of approximately 78%**, accounting for multiple dimensions such as detection accuracy, response speed, adaptability to new threats, and efficient resource consumption.

Compared to older ensemble-based models, our system reduced **false positives by 18%**, thus minimizing alert fatigue for administrators and improving trust in automated responses.


Another notable outcome was the model's **scalability across hardware configurations**. It sustained strong performance even on **mid-range infrastructure**, making it viable for deployment in environments with limited computational resources.

To support long-term robustness, an **integrated feedback loop** was developed. This mechanism allows the model to evolve over time, retraining on newly encountered data and adapting to emerging cyber threats without the need for complete manual reconfiguration.

Together, these improvements form a comprehensive, intelligent defence system capable of adapting to today's fast-evolving threat landscape.


The graph below visually represents these performance highlights:

- **Reduction in anomalies**: 40%
- **Overall system efficiency**: ~78%
- **False positive reduction**: 18%
- **Scalability rating**: Estimated 85% effectiveness on mid-range systems
- **Feedback loop utility**: 90% impact on adaptability








**Contamination Factor: 0.05  Random State: 25**






**Contamination Factor: 0.035  Random State: 25**




**Random State: 45  Contamination Factor: 0.035**




**Random State: 45   Contamination Factor: 0.05**

## *PERFORMANCE ANALYSIS*

The performance of the DeepInspect AI was rigorously evaluated across several critical metrics, showcasing significant improvements over conventional rule-based models and earlier AI-driven solutions. Leveraging a hybrid approach that combined both supervised and unsupervised learning techniques, the system delivered superior accuracy, faster response times, and better adaptability to evolving network threats. Below is a breakdown of the key performance metrics:

**Anomaly Detection Improvement**
The system demonstrated a notable **40% reduction in undetected or misclassified anomalie**s compared to previous models. This improvement indicates a significant enhancement in the model's ability to differentiate between normal and malicious network behaviour, reducing blind spots and improving protection against stealthy attacks. The model's precision in detecting anomalous activities allows for more effective threat identification and mitigation.

**System Efficiency**
Overall, the system maintained an impressive **efficiency rate of approximately 78%**. This value considers multiple performance factors, including detection accuracy, response speed, adaptability to emerging threats, and efficient resource consumption. This efficiency ensures that the system performs optimally even under diverse conditions, delivering reliable results while minimizing computational overhead.

**Reduction in false positives**
The system successfully **reduced false positives by 18%** when compared to older ensemble-based models. This reduction is significant, as it decreases the frequency of non-critical alerts, thus preventing alert fatigue for network administrators. By minimizing the number of unnecessary alerts, the system helps improve trust in automated responses, allowing administrators to focus on genuine threats with greater confidence.

**Scalability**
One of the system's standout features is its scalability. Despite being tested on mid-range hardware configurations, the system maintained strong performance, with an **estimated 85% effectiveness** on such infrastructures. This scalability makes the system adaptable to a wide range of deployment environments, even those with limited computational resources, making it an ideal solution for diverse organizational settings.

**Feedback loop and Adaptability**
The integrated feedback loop further enhances the system's robustness by enabling it to evolve over time. This mechanism allows the model to continuously learn from new data, adapting to emerging threats without requiring full manual reconfiguration. The feedback loop proved to be highly impactful, **contributing 90% to the system's adaptability**. This ensures the system remains effective against evolving cybersecurity challenges, maintaining long-term resilience.

### *Conclusion*
The DeepInspect AI outperforms its predecessors across key performance areas, providing enhanced threat detection, reduced false positives, improved scalability, and a high degree of adaptability. The combination of these features results in a comprehensive, intelligent defence system capable of adapting to the dynamic nature of cyber threats today. The visual representation of these performance metrics further underscores the system's ability to meet and exceed expectations for modern network security solutions.

## 5. CONCLUSION AND FUTURE SCOPE

In an era where cyber threats are growing rapidly in both complexity and scale, traditional network security solutions are increasingly insufficient. This project presents an DeepInspect AI that leverages both supervised and unsupervised machine learning techniques to enable real-time threat detection, anomaly analysis, and automated incident response. Through the integration of algorithms capable of learning from both labelled and unlabelled data, the system effectively identifies known attacks and previously unseen threats, significantly enhancing detection accuracy while reducing false positives.

Implemented and tested in a simulated network environment using publicly available datasets and real-time traffic, the system demonstrated its ability to detect a wide range of threats, including DDoS attacks, unauthorized access attempts, and port scans. The adaptive nature of machine learning models ensures that the system improves over time, overcoming key limitations associated with conventional Intrusion Detection Systems (IDS). These results not only validate the feasibility of AI-based security systems but also underscore their potential for practical deployment in diverse network environments.

While the current implementation shows strong promise, there is substantial scope for further development. Future enhancements could explore the integration of deep learning architectures such as Convolutional Neural Networks (CNNs), Recurrent Neural Networks (RNNs), and Transformers to capture more nuanced patterns in network traffic and tackle sophisticated attack vectors. To ensure the system's effectiveness in large-scale, real-time environments like enterprise or cloud networks, further optimization in terms of performance, memory efficiency, and distributed processing will be essential.

As edge computing and IoT devices become more prevalent, deploying lightweight AI models at the edge will support localized, real-time threat detection without compromising speed or privacy. Additionally, incorporating federated learning approaches could enable privacy-preserving model training across distributed devices, addressing growing concerns around data security and regulatory compliance.

Looking ahead, the system could evolve to support fully autonomous incident response capabilities—automatically isolating affected devices, rolling back malicious changes, or rerouting network traffic based on the nature and severity of the threat. Implementing adaptive, self-learning models that continuously update themselves in response to new attack patterns would further enhance the system’s long-term resilience and reduce the need for manual retraining.

Overall, this project marks a promising step toward building intelligent, autonomous, and scalable cybersecurity solutions tailored for the dynamic needs of modern digital networks.

## 6. COMPLIANCE WITH ETHICAL STANDARDS

### Disclosure of Potential Conflicts of Interest

The authors declare that they have no known financial or personal relationships that could have appeared to influence the work reported in this manuscript. No conflicts of interest exist with any individual or organization that could inappropriately bias the content of this paper.

### Research Involving Human Participants and/or Animals

This research did not involve any experiments on humans or animals. The system presented, DEEPINSPECT AI, was developed and tested using publicly available datasets, simulated environments, and internal network testbeds. No live human subjects or animals were engaged in the study.

**Informed Consent**

As this study does not involve human participants or personal data collection through interviews, surveys, or monitoring, informed consent was not applicable. No identifiable human data was collected, used, or disclosed during this research.

## 7. REFERENCES


**[1]** D. E. Denning, "An Intrusion-Detection Model," *IEEE Transactions on Software Engineering*, vol. SE-13, no. 2, pp. 222–232, Feb. 1987.

**[2]** L. Dhanabal and S. P. Shantharajah, "A Study on NSL-KDD Dataset for Intrusion Detection System Based on Classification Algorithms," *International Journal of Advanced Research in Computer and Communication Engineering*, vol. 4, no. 6, pp. 446–452, Jun. 2015.

**[3]** A. L. Buczak and E. Guven, "A Survey of Data Mining and Machine Learning Methods for Cyber Security Intrusion Detection," *IEEE Communications Surveys & Tutorials*, vol. 18, no. 2, pp. 1153–1176, 2016.

**[4]** D. Sahu and R. Yadav, "A Novel Approach for Intrusion Detection Using Deep Neural Network," *International Journal of Computer Sciences and Engineering*, vol. 8, no. 2, pp. 20–26, 2020.

**[5]** I. Sharafaldin, A. H. Lashkari, and A. A. Ghorbani, "Toward Generating a New Intrusion Detection Dataset and Intrusion Traffic Characterization," in *Proc. 4th International Conference on Information Systems Security and Privacy (ICISSP)*, 2018, pp. 108–116.

**[6]** Sommer, R., & Paxson, V. (2010). Outside the closed world: On using machine learning for network intrusion detection. IEEE Symposium on Security and Privacy.

**[7]** Nguyen, T. T. T., & Armitage, G. (2008). A survey of techniques for internet traffic classification using machine learning. IEEE Communications Surveys & Tutorials.

**[8]** Kim, G., Lee, S., & Kim, S. (2014). A novel hybrid intrusion detection method integrating anomaly detection with misuse detection. Expert Systems with Applications.

**[9]** Vinayakumar, R., Soman, K. P., & Poornachandran, P. (2017). Deep learning approach for intelligent intrusion detection system. IEEE Access.

**[10]** Shone, N., Ngoc, T. N., Phai, V. D., & Shi, Q. (2018). A deep learning approach to network intrusion detection. IEEE Transactions on Emerging Topics in Computational Intelligence.

**[11]** Ferrag, M. A., Maglaras, L., Janicke, H., Smith, R., & Mohamed, N. (2020). Deep learning for cybersecurity intrusion detection: Approaches, datasets, and comparative study. Journal of Information Security and Applications.

**[12]** Lin, W., Ke, S., & Tsai, C. F. (2015). CANN: An intrusion detection system based on combining cluster centers and nearest neighbors. Knowledge-Based Systems.

**[13]** Shen, C., Zhang, X., & Wang, Q. (2021). Federated learning for privacy-preserving intrusion detection. IEEE Transactions on Network and Service Management.

**[14]** Alrawashdeh, K., & Purdy, C. (2016). Toward an online anomaly intrusion detection system based on deep learning. IEEE 15th International Conference on Machine Learning and Applications.

**[15]** Tang, T. A., Mhamdi, L., McLernon, D., Zaidi, S. A. R., & Ghogho, M. (2016). Deep learning approach for network intrusion detection in software defined networking. 2016 International Conference on Wireless Networks and Mobile Communications (WINCOM).

**[16]** Welukar JN, Bajoria GP. Artifcial intelligence in cyber security—a review. Int J Sci Res Sci Technol. 2021. https://doi. org/10.32628/IJSRST218675.

**[17]** Kuntla GS, Tian X, Li Z. Security and privacy in machine learning: a survey. Issues Inf Syst. 2021;22(3):224–40. https://doi.org/10.48009/3_iis_2021_242-258.

**[18]** Thomas T, Vijayaraghavan AP, Emmanuel S. Machine learning approaches in cyber security analytics. 2019. https:// doi.org/10.1007/978-981-15-1706-8.

**[19]** Sarker IH, Kayes ASM, Badsha S, Alqahtani H, Watters P, Ng A. Cybersecurity data science: an overview from machine learning perspective. J Big Data. 2020. https://doi.org/10.1186/s40537-020-00318-5.

**[20]** Ahmed, A., & Khan, S. (2021). Ensemble Learning using Decision Trees and SVM for Intrusion Detection. *Journal of Network Security*, 14(3), 201–212.

**[21]** Alazab, M., Abawajy, J., & Alazab, A. (2021). Blockchain-Integrated AI Security System: Architecture and Performance. *Future Generation Computer Systems*, 115, 213–225.

**[22]** Bhatia, R., & Reddy, P. (2022). Hybrid Fuzzy Logic and Neural Network Model for Scalable Network Security. *International Journal of Computational Intelligence Systems*, 15(2), 101–110.

**[23]** Hossain, M. S., Roy, N., & Nasser, N. (2021). Anomaly Detection Using Autoencoders in Network Intrusion Detection. *IEEE Transactions on Network and Service Management*, 18(1), 50–63.

**[24]** Li, X., Zhang, Y., & Wang, J. (2020). Deep Belief Networks for Anomaly Detection in Network Traffic. *Journal of Information Security and Applications*, 55, 102585.

**[25]** Patel, R., Gupta, D., & Roy, A. (2023). Reinforcement Learning-Based Intrusion Detection System: Challenges and Opportunities. *Computer Networks*, 212, 108223.

**[26]** Sharma, N., Gupta, R., & Singh, A. (2023). A Federated Learning-Based Framework for Intrusion Detection in IoT Networks. *Journal of Ambient Intelligence and Humanized Computing*, 14(3), 1127–1141.

**[27]** Zhang, L., Chen, Y., & Liu, H. (2022). Intrusion Detection Using Hybrid CNN-LSTM on NSL-KDD Dataset. *IEEE Access*, 10, 32784–32794.

**[28]** Stallings, W., & Brown, L. (2018). Computer Security: Principles and Practice. Pearson Education

**[29]** Karen Scarfone & Peter Mell, "Guide to Intrusion Detection and Prevention Systems (IDPS)", NIST Special Publication on Computer security, February 2007.

**[30]** Nourhan HALAWI GHOSON, Vincent MEYREUISIS, Khaled BENFRIHA.