EXP.NO:86)

Configuration of Wireless LAN using Cisco Packet Tracer

Aim:

To configure a wireless LAN using Cisco Packet Tracer by connecting three PCs to a Linksys Wireless Router, assigning static IP addresses, configuring the SSID and WEP security, and verifying connectivity

Procedure:

1. Open Cisco Packet Tracer and place a Linksys Wireless Router and three PCs (PC0, PC1 and PC2) in the workspace
2. Open the wireless Router and go to the Administration tab. Set the username and Password as admin, then save the settings.
3. Go to the Wireless tab and change the default SSID to MotherNetwork
4. Open Wireless Security, Select WEP as the Security mode and set key1: 0123456789. Save the Settin
5. Configure the Static IP address of the three PCs as follows

	PC	IP Address	Subnet Mask	Default Gatew
1.	PC0	192.168.0.2	255.255.255.0	192.168.0.1
2.	PC1	192.168.0.3	255.255.255.0	192.168.0.1
3.	PC2	192.168.0.4	255.255.255.0	192.168.0.

6. For each PC, open Desktop → PC Wireless → Connect and refresh the available networks.

7. Select MotherNetwork and click Connect.

8. Enter the WEP Key and Connect the PC to the Wireless Router.

9. Repeat the same Wireless connection process for PC1 and PC2.

10. Open the Command prompt on PC0 and verify Connectivity.

11. Verify that all ping requests receive replies with 0% packet loss.

Result:

The Wireless LAN was successfully configured using Cisco Packet Tracer. The three PCs were connected to the Linksys Wireless Router using the MotherNetwork SSID and WEP Security.