Git4agents: Governed Promotion and Conflict Resolution for Fleets of Coding Agents

Yashwanth Gathuku
Independent researcher, Cleveland, Ohio, USA
yashwanth8035@gmail.com

***Abstract*—Coding agents now work on one repository in parallel, and Git is a poor gatekeeper for them: it records ancestry, but a passing CI run, a branch permission or a clean merge says little about whether an agent's state should become canonical, and overlapping edits are left to people. Git4agents keeps Git as the history layer and governs canonicalization around it. Agents write only to isolated contender forks under declared work claims; an independent evaluator, blind commit-then-reveal verifiers and non-compensatory gates decide; a single-use permit bound to the exact reviewed commit authorizes promotion; and every promotion ships a signed bundle that verifies offline. This demonstration adds *governed resolution*: when agents edit the same lines, an untrusted resolver may write only the conflicted hunks, each agent's frozen witness checks must still pass, and the resolved commit is bound to a content-addressed conflict capsule in the signed ledger. In 64 resolution attempts on eight conflicting scenarios over three npm packages, the earlier resolve path admitted 37 wrong resolutions; the governed path admitted none and refused one correct one. Git4agents runs on Cloudflare Workers, Durable Objects and Artifacts. Video: https://youtu.be/VIDEO-ID. Code: https://github.com/YashwanthGathuku/Git4agents.**

I. Introduction

Concurrent coding agents collide often: replaying merges of 747 pairs of co-active pull requests, Xu et al. found textual conflicts in 41.7% of cross-agent pairs against 19.8% of pairs by the same agent [1]. Handing those conflicts to a language model is not yet a safe default. The best models reproduce fewer than 60% of developers' resolutions [2]; high textual similarity to the developer's file does not mean a resolution is safe [3]; and an LLM judge accepted four of five structurally invalid resolutions [4].

Git's governance assumes a few people who take turns: branch permissions decide who may merge, CI trusts the tests in the branch, and the merge itself is the record. With agent fleets each assumption fails. An agent can claim a task is done when it is not, edit the tests it is judged by, push stale state, or resolve a conflict by quietly keeping one side. Git4agents separates the two questions Git conflates: *Git decides ancestry; Git4agents decides canonicality.* This paper contributes:

- a deployed trust layer that admits agent work to canonical history only through independent evidence, non-overridable gates and an exact-state, single-use permit, with offline-verifiable proof (Sec. II);
- *governed resolution*: a hunk-level resolution lease, frozen per-agent witness checks, a resolution ladder whose model rung must agree in both orders, and a binding of every resolved commit to its conflict capsule (Sec. III);
- evidence from live runs on Cloudflare and a resolution benchmark of 204 attempts (Sec. V).

II. The Git4agents Trust Layer

Git4agents is one Cloudflare Worker. A *TaskAuthority* Durable Object per task is the single writer of its state: the frozen task and baseline, work claims, conflict reports, contenders, evaluations, verifier commitments, verdicts, permits and a hash-chained ledger. Cloudflare Artifacts [5] holds the canonical repository and one fork per contender; push events reach the authority through a Queue; a Workflow and a Container perform the only canonical write. Control, agent and evaluation calls use separate credentials.

Fig. 1 shows a task's path. Agents first declare *Work-Claims*—paths, symbols, contracts read and modified—which deterministic set rules classify as GREEN, AMBER, RED or BLOCKED. Each contender commits to its own fork; a *fork crew* of sub-agents shares one fork, and per-file three-way merges compose their commits into one candidate or report a conflict. An independent evaluator runs hidden tests against the immutable candidate; editing test files or runner configuration is evidence tampering and quarantines the contender mechanically. Blind verifiers commit to SHA-256 commitments before they see candidates and then reveal. The verdict seam evaluates mandatory gates first and never lets a score compensate for a failed gate; no override path exists. On ACCEPT the authority issues a permit whose id hashes the task, baseline, candidate tree, evidence, policy and expected destination head. It is single-use and expires if the destination head moves. Promotion fast-forwards to the reviewed commit itself, and the authority signs in-toto statements [6] in DSSE envelopes [7] together with the ledger, which anyone can check offline against a pinned key.

Agents reach Git4agents over REST or the Model Context Protocol [8]. The MCP surface has seven tools—inspect the task and work graph, check clearance, claim work, open a contender fork, read the ledger, verify a permit—and deliberately none that evaluates, decides, issues a permit or promotes.

III. Governed Resolution

Before this work, a conflicted crew either stopped or ran an operator's resolver command, checked only for leftover conflict markers. Auditing that path, we found that the resolver




Fig. 1. A task in Git4agents. Shaded steps are governed resolution (Sec. III): the resolution ladder tries Mergiraf, then intent replay in both orders, and every candidate must pass the hunk lease and the frozen witness gate. The task authority records every step before promotion; only the promotion path writes canonical history.

had to rebuild every clean edit itself and could write anywhere: a resolver that wrote one file produced a commit whose parents named every agent's commit while its tree held none of their other work. Governed resolution treats every resolver—a structured merge tool, a model, a person's script—as an untrusted producer.

Resolution lease. The authority writes the *pre-composed* tree: the baseline plus every non-conflicting edit, including the clean regions of a conflicted file, which `git merge-file --diff3` splits into clean segments and conflicted hunks. Each hunk holds its baseline text. The resolver reads its inputs from outside the repository and may change only the hunks; the resolved file must contain every clean segment byte-for-byte and in order, or the resolution is refused. Files with three or more sides are leased whole.

Conflict capsule. A `CONFLICTED` record becomes a content-addressed capsule: digests of the baseline, contributing commits, every hunk and the frozen witness manifest. The authority computes its id itself.

Frozen witnesses. Each agent declares small checks of its own intent in the crew configuration. They are read and hashed once, before any agent runs, and executed from copies outside every candidate tree, so neither an agent nor a resolver can weaken them. A check t counts as a witness for side i only if it discriminates that side:

$$witness_i(t) \iff \neg pass(t, base) \wedge pass(t, sha_i). \quad (1)$$

A candidate R is refused (REFUSE) if any witness fails on R or a check that passed on the baseline regresses; it goes to REVIEW if some conflicting side has no witness, since absent evidence is not evidence that intent survived; otherwise it is admitted (ADMIT). SAM [9] applies a similar pass/fail criterion with generated unit tests to *detect* semantic conflicts after a merge; Git4agents uses agent-declared checks, frozen before an untrusted resolver runs, as a non-compensatory *admission* gate.

Resolution ladder. Rungs run under the lease and every candidate meets the same gate: Mergiraf's syntax-aware merge [10], then *intent replay*, then REVIEW. A replayer (for example an LLM; adapters for the Anthropic Messages API and Workers AI are included) is asked to re-apply one side's intent onto the other side's version of each hunk, in both orders, yielding R_{AB} and R_{BA}. Both admitted: the conflict commutes under the witnesses and R_{AB} is kept. Only one admitted: the result depends on order, which we treat as a genuine semantic conflict and escalate instead of letting one order win. The criterion follows the requirement that merging concurrent patches not depend on their order [11]; here it is an admission signal for an untrusted model. A person may clear a REVIEW caused by a missing witness; a REFUSE is never cleared.

Listing 2. A sub-agent with a witness in a crew configuration (abridged).

```
{ "id": "sub-api", "intent": "Change the API handler and name the contract api.",
  "paths": ["src/api/**", "src/contract.js"],
  "command": "<the agent's command>",
  "witnesses": [{ "id": "api-label", "script": "witnesses/demo/api-label.mjs" }] }
```

Binding. The authority records a resolved commit only if it answers the recorded capsule and its frozen witness manifest with an ADMIT, or a REVIEW cleared by a named operator, and it writes a `resolution_recorded` ledger entry over that binding. A crew whose claims were RED or BLOCKED but merged cleanly needs a witness check as well; a clean merge that breaks a witness is reported as a semantic conflict and never pushed. The promotion bundle carries the resolution, and offline verification gains a line that fails if it is altered, removed or names another commit (Listing 1).

Listing 1. Last lines of `npm run demo:resolution` (harness key).

```
ledger chain.......... OK
resolution............ CAPSULE 534980c69009 ·command ·witnesses ADMIT
VERIFIED
```

IV. Demonstration

The video shows (1) the live trust board, which renders a real task's claims, contenders, gates and ledger; (2) the recorded live cheater run, in which a contender that edits a test file is quarantined mechanically while an honest contender is promoted; (3) offline verification of a live bundle, and NOT VERIFIED after a one-byte change; and (4) governed resolution: two agents rewrite the same line, a resolver that keeps one side is refused with the lost intent named, a resolver that keeps both is admitted, and the bound commit verifies offline. Locally, `npm test`, `npm run demo:resolution` and `npm run bench:resolution` reproduce everything in Sec. V.2 without a Cloudflare account. A crew declares each sub-agent's scope and witnesses in one file (Listing 2); the runner then needs only a resolver setting, e.g. `MADGRIX_RESOLVE_LADDER=1` with an optional replayer command.

TABLE I
RESOLUTION BENCHMARK: 8 CONFLICTING SCENARIOS × 8 RESOLVER BEHAVIORS PER PIPELINE. TWO RUNS GAVE IDENTICAL OUTCOMES.

Pipeline	Admitted	Correct	False accepts	Correct refused
P0 earlier path	49	12	37	0
P1 lease	36	19	17	1
P2 lease + witnesses	19	19	**0**	1

TABLE II
ADMITTED (OF WHICH WRONG) PER RESOLVER BEHAVIOR, CONFLICTING SCENARIOS.

Behavior	P0	P1	P2
keep one side (ours / theirs)	16 (16)	12 (12)	0 (0)
union merge	8 (5)	8 (5)	3 (0)
leave conflict markers	0 (0)	0 (0)	0 (0)
reference resolution	8 (0)	8 (0)	8 (0)
reference + delete another's file	8 (8)	0 (0)	0 (0)
reference, clean work not rebuilt	8 (8)	8 (0)	8 (0)
Mergiraf 0.20.0	1 (0)	0 (0)	0 (0)

V. EVALUATION

1) Live runs on Cloudflare. Four recorded end-to-end runs promoted the exact reviewed commit and produced bundles that verify offline. A fork crew of one parent and twelve subagents on an import of `sindresorhus/ky` composed and promoted one commit. In the live cheater run, a contender that edited a test was quarantined, one that claimed completion failed the hidden tests, and the honest contender was promoted. At the coordination layer, 3,000 of 3,000 concurrent claims were accepted; at 5,000, 4,997 were accepted and all 249 seeded overlaps were flagged with no false flags. The agents in these runs are scripted processes: the runs show the protocol, not the coding ability of models. A local attack harness blocks all 26 attack trials; the suite has 482 tests.

2) Resolution benchmark. Twelve scenarios on three MIT packages (`indent-string`, `escape-string-regexp`, `decamelize`) each give two agents stated intents: six change the same lines, two overlap only in an option list, two merge cleanly as text but break behavior (a changed default that another agent's new helper relies on), and two merge cleanly and correctly. Each agent also makes one clean edit elsewhere, so lost work is observable. Eight resolver behaviors—keep one side, keep the other, git's union merge, leave markers, the reference resolution, the reference plus deleting another agent's file, the reference without rebuilding clean files, and Mergiraf 0.20.0—run through three pipelines: *P0*, the earlier resolve path loaded unchanged from the repository's history; *P1*, the lease; and *P2*, the lease plus witnesses. A held-out acceptance test per scenario, which no pipeline sees, judges every admitted candidate.

Tables I and II show the conflicting scenarios. The lease removes two failure classes: P0 admits every resolver that deletes another agent's file and every one that does not rebuild clean work (8 of 8 each, all wrong), while P1 refuses the first and makes the second correct, because the authority writes clean work. The lease cannot see intent: keeping one side is admitted and wrong 12 times under P1 and refused every time under P2. Union merge is correct in 3 of 8 scenarios, and P2 admits exactly those three. The one correct candidate refused is Mergiraf's only successful merge: correct, but it rewrote a clean line's whitespace, and the lease compares bytes. Mergiraf resolved 1 of 8 conflicts; it did not merge additions to a destructured option list. On the clean-merging scenarios, P0 and P1 admit both semantic conflicts; P2 refuses both and admits both controls. A witness check took 89 ms median (116 ms maximum) per candidate.

3) Threats to validity. The scenarios are few, small and written by the author; they exercise the gates' mechanics and give no real-world precision. Witnesses and acceptance tests share an author, and each witness checks a subset of its acceptance test, so P2's zero false accepts partly reflect that design: a resolution that keeps every witnessed behavior but breaks an unwitnessed one is admitted. Resolver behaviors are scripted; no LLM resolver was evaluated, and dual-order replay was tested only with deterministic replayers. A resolved crew has not yet run on Cloudflare.

VI. RELATED WORK

Structured merge tools such as Mergiraf [10] and version control systems that store conflicts as first-class objects, such as Jujutsu [12], improve how conflicts are represented and resolved; Git4agents decides whether a resolution may become canonical and can use either as a rung. LLM merge resolution is advancing [2]–[4]; these studies motivate gating model output by behavior rather than similarity. SAM [9] detects semantic conflicts with generated tests after a merge. Supply-chain attestation [6], [7] records how an artifact was built; Git4agents applies it to why a commit was allowed to become canonical.

VII. CONCLUSION AND AVAILABILITY

Git4agents governs how agent work becomes canonical, and now governs how overlapping agent work is resolved: a resolver writes only what is in conflict, every side's frozen intent must survive, and the outcome is bound to its conflict in a signed, offline-verifiable record. Next steps are evaluating LLM replayers with dual-order agreement on real conflicts, re-running witnesses in the independent evaluator, and a live resolved crew. The code, benchmark and specifications are available under Apache-2.0 at https://github.com/YashwanthGathuku/Git4agents; a live deployment is at https://madgrix.ygathuku96.workers.dev.

ACKNOWLEDGMENT

Parts of the implementation and of this paper's text were drafted with the assistance of an AI model and were reviewed and edited by the author.

References

[1] G. Xu, A. Subramanian, and N. Karthik, "AI agent pull requests on GitHub: Frequency, structure, and merge conflict rates," arXiv:2607.04697, 2026.

[2] B. Schesch and M. D. Ernst, "Merge-Bench: Resolve merge conflicts with large language models," in *Proc. Int. Conf. Pattern Recognition (ICPR)*, 2026, arXiv:2605.25890.

[3] W. Zhang, J. Yang, J. Wu, Z. Tang, and S. Wu, "SWE-Git-Bench: A focused worktree-level benchmark for real merge conflict resolution," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2026, poster.

[4] B. Shen, "Can large language models resolve real Java merge conflicts? An evaluation with a calibrated LLM-as-judge," arXiv:2607.27674, 2026.

[5] Cloudflare, "Cloudflare Artifacts documentation," https://developers.cloudflare.com/artifacts/, accessed Oct. 2026.

[6] S. Torres-Arias, H. Afzali, T. K. Kuppusamy, R. Curtmola, and J. Cappos, "in-toto: Providing farm-to-table guarantees for bits and bytes," in *Proc. 28th USENIX Security Symposium*, 2019, pp. 1393–1410.

[7] Secure Systems Lab, "DSSE: Dead simple signing envelope," https://github.com/secure-systems-lab/dsse, accessed Oct. 2026.

[8] Model Context Protocol, "Model context protocol specification," https://modelcontextprotocol.io, accessed Oct. 2026.

[9] L. Da Silva, P. Borba, T. Maciel, W. Mahmood, T. Berger, J. Moisakis, A. Gomes, and V. Leite, "Detecting semantic conflicts with unit tests," *Journal of Systems and Software*, vol. 214, p. 112070, 2024.

[10] A. Delpeuch *et al.*, "Mergiraf: Syntax-aware merge driver for Git," https://mergiraf.org, 2025, version 0.20.0.

[11] S. Mimram and C. Di Giusto, "A categorical theory of patches," *Electronic Notes in Theoretical Computer Science*, vol. 298, pp. 283–307, 2013.

[12] Jujutsu contributors, "First-class conflicts," https://github.com/jj-vcs/jj/blob/main/docs/conflicts.md, 2026, accessed Oct. 2026.