

COLLEGE CODERS

React JS Lesson 12 – Lifting State Up (Premium Notes)

1) What is Lifting State Up

- Lifting State Up means moving shared state to the nearest common parent component.
- Parent manages data, children receive it through props.

Example:

```
const [count, setCount] = useState(0);
```

Explanation:

- State is stored in parent instead of child.

2) Why Lifting State Up is Needed

- Needed when multiple child components require same data.

Example:

```
<ChildA count={count} />  
<ChildB count={count} />
```

Explanation:

- Both children receive same state.

3) Problems Without Lifting State

- Separate child states become independent.
- Data becomes inconsistent.

Example:

ChildA → own state
ChildB → own state


Explanation:

- Both children cannot stay synced.

4) Lifting State to the Parent Component

- Move state to parent and send values down.

Example:



COLLEGE CODERS

```
function Parent(){  
  const [name, setName] = useState('');  
}
```

Explanation:

- Parent becomes single source of truth.

5) Sharing State Between Child Components

- One child updates, another child displays.

Example:

```
<InputBox setName={setName} />  
<Display name={name} />
```

Explanation:

- Children communicate through parent.

6) Props Usage with Lifted State

- Parent sends both state and update function.

Example:

```
<Child count={count} setCount={setCount} />
```

Explanation:

- Child can read and update parent state.

7) Real-Life Examples of Lifting State Up


- Cart quantity update.
- Search input shared across components.
- Dark mode toggle.

Example:

Search box + Result list

Explanation:

- Search value stored in parent.



COLLEGE CODERS

8) Common Mistakes to Avoid

- Do not duplicate same state in multiple children.
- Do not mutate props directly.

Example:

Wrong: Child keeps duplicate state

Explanation:

- One shared source is best.

9) When to Use Lifting State Up

- Use when sibling components need same data.
- Use before Context API if structure is simple.

Example:

Sibling communication → parent state

Explanation:

- Best for medium-size component sharing.

Mini Project – Shared Counter

- Parent stores count.
- One child increases count.
- Another child displays count.