

COLLEGE CODERS

React JS Lesson 3 – Props (Premium Notes)

1) What are Props?

- Props means properties.
- Props are used to send data from parent component to child component.
- They help components receive external values.

Example:

```
function App(){  
  return <Product name="Pizza" />  
}
```

Explanation:

- Product component receives name value from parent.
- Props make component dynamic.

2) Why do we use Props?

- Props make components reusable.
- Same component can display different data.

Example:

```
<Product name="Pizza" />  
<Product name="Burger" />
```

Explanation:

- Same Product component used twice with different values.

3) How to pass props from Parent to Child

- Props are passed like HTML attributes while calling component.


Example:

```
<Product name="Pizza" price="199" />
```

Explanation:

- name and price travel from parent to child.

4) How to receive props in Child component



COLLEGE CODERS

- Props are received inside function parameter.

Example:

```
function Product(props){  
  return <h2>{props.name}</h2>  
}
```

Explanation:

- props object stores all values.

5) Accessing props

- Use dot notation to access values.

Example:

```
<p>{props.price}</p>
```

Explanation:

- price is read using props.price.

6) Destructuring props

- Destructuring extracts values directly.

Example:

```
function Product({name, price}){  
  return <h2>{name} - {price}</h2>  
}
```

Explanation:

- No need to write props.name repeatedly.


7) Sending multiple props

- Multiple values can be sent together.

Example:

```
<Product name="Pizza" price="199" rating="4.5" />
```

Explanation:



COLLEGE CODERS

- One component can receive many values.

8) Props vs Function Arguments

- Props behave similar to function arguments.
- Parent sends values, child receives them.

Example:

```
function greet(name){  
  return name;  
}
```

Explanation:

- Props concept is same but used between components.

9) Props are read-only

- Props should never be changed inside child component.
- React follows one-way data flow.

Example:

```
props.name = "Burger" // Wrong
```

Explanation:


- Changing props directly causes React warning.

10) Real Project – Product/Food Card

- Create reusable card for product display.

Example:

```
function Product({name, price, rating}){  
  return (  
    <div>  
      <h2>{name}</h2>  
      <p>{price}</p>  
      <p>{rating}</p>  
    </div>  
  )  
}
```



COLLEGE CODERS

Explanation:

- One card reused for multiple products.

Assignment

- Create FoodCard component.
- Pass food name, price, quantity, rating.
- Render minimum 3 reusable cards.