

COLLEGE CODERS

React JS Lesson 4 – State and useState (Premium Notes)

1) What is State?

- State stores changing data inside a component.
- Whenever state changes, UI updates automatically.

Example:

```
const [count, setCount] = useState(0);
```

Explanation:

- count stores current value.
- setCount updates value.

2) Why we use useState with const

- useState returns two values.
- We use const because values come as array destructuring.

Example:

```
const [name, setName] = useState("Rohith");
```

Explanation:

- name stores current state.
- setName changes it.

3) How State Updates & Re-rendering Works

- When state updates, component runs again.
- React updates only changed UI part.

Example:


```
setCount(count + 1);
```

Explanation:

- React re-renders component after update.

4) Difference Between Props & State

- Props come from parent.



COLLEGE CODERS

- State belongs to component itself.

Example:

Props → external data

State → internal data

Explanation:

- Props cannot change directly.
- State can change.

5) Updating State (setState logic & async behaviour)

- setState does not update immediately.
- React schedules update for performance.

Example:

```
setCount(count + 1);  
console.log(count);
```

Explanation:

- console may show old value because update is async.

6) Passing State from Parent → Child

- Parent sends state using props.

Example:

```
<Child count={count} />
```

Explanation:

- Child receives latest parent state.


7) Updating Parent State from Child (Lifting State Up)

- Parent sends update function to child.

Example:

```
<Child setCount={setCount} />
```

Explanation:



COLLEGE CODERS

- Child uses parent function to update parent state.

8) Parent + Child Re-rendering Flow

- Parent updates first.
- Child receives new data and re-renders.

Example:

Parent → Child → UI update

Explanation:

- React follows top-down rendering.

9) Mini Project – Counter App using Parent & Child

- Parent stores count.
- Child button updates count.

Example:

```
function Child({count, setCount}){  
  return <button onClick={()=>setCount(count+1)}>Increase</button>  
}
```

Explanation:

- Child updates parent count.

Assignment

- Create parent-child counter app.
- Add increase and decrease buttons.
- Display count in child.