

COLLEGE CODERS

React JS Lesson 5 – Conditional Rendering (Premium Notes)

1) if / else

- Use normal JavaScript if/else before return statement.
- Useful when logic is larger.

Example:

```
function App(){  
  const isLogin = true;  
  
  if(isLogin){  
    return <h1>Welcome User</h1>  
  }else{  
    return <h1>Please Login</h1>  
  }  
}
```

Explanation:

- If condition true → Welcome User shown.
- Else condition false → Please Login shown.

2) Ternary operator

- Ternary is short form of if/else.
- Used directly inside JSX.

Example:

```
<h1>{isLogin ? "Welcome User" : "Please Login"}</h1>
```


Explanation:

- Condition true gives first value.
- Condition false gives second value.

3) Logical AND (&&)

- Used when only true condition output is needed.

Example:



COLLEGE CODERS

```
{isLoggedIn && <h2>Dashboard Visible</h2>}
```

Explanation:

- If isLoggedIn true → Dashboard shown.
- If false → nothing appears.

4) State-based UI toggling

- State controls UI visibility dynamically.

Example:

```
const [show,setShow] = useState(false);
```

```
<button onClick={()=>setShow(!show)}>Toggle</button>
```

```
{show && <p>Hello Student</p>}
```

Explanation:

- Click changes state.
- React shows/hides text instantly.

5) Mini Project – Show / Hide Text Toggle

- Toggle text using one button.

Example:

```
const [show,setShow] = useState(false);
```

```
<button onClick={()=>setShow(!show)}>
```

```
{show ? "Hide" : "Show"}
```

```
</button>
```


```
{show && <h2>College Coders</h2>}
```

Explanation:

- Button text also changes dynamically.

6) Mini Project – Show / Hide Password App

- Change input type using state.



COLLEGE CODERS

Example:

```
const [show,setShow] = useState(false);
```

```
<input type={show ? "text" : "password"} />
```

```
<button onClick={()=>setShow(!show)}>  
  {show ? "Hide" : "Show"}  
</button>
```

Explanation:

- Password becomes visible when show=true.

Assignment

- Create login/logout toggle.
- Create one password toggle app.
- Use ternary for button text.