

COLLEGE CODERS

React JS Lesson 7 – Forms in React (Premium Notes)

1) What are Forms in React

- Forms collect user data such as name, email, password.
- React manages form data using state.

Example:

```
<form>
  <input />
  <button>Submit</button>
</form>
```

Explanation:

- Form contains input fields and submit button.

2) What are Controlled Components

- Controlled component means input value is controlled by React state.

Example:

```
const [name, setName] = useState("");

<input value={name} onChange={(e)=>setName(e.target.value)} />
```

Explanation:

- Input value always comes from state.

3) How React controls input values using useState

- useState stores current input value.


Example:

```
const [email, setEmail] = useState("");

<input value={email} onChange={(e)=>setEmail(e.target.value)} />
```

Explanation:

- Typing updates state immediately.



COLLEGE CODERS

4) Handling multiple inputs in a single form

- Each input can share same state object.

Example:

```
<input name="name" />
<input name="email" />
```

Explanation:

- name attribute identifies field.

5) Using one object state for form data

- Store all fields in one object.

Example:

```
const [formData,setFormData] = useState({
  name:"",
  email:"
});
```

Explanation:

- One object manages full form.

6) Creating reusable handleChange function

- One function updates multiple inputs.

Example:

```
function handleChange(e){
  setFormData({...formData,[e.target.name]:e.target.value})
}
```


Explanation:

- Dynamic key updates matching field.

7) Handling form submit in React

- Use onSubmit event in form.

Example:



COLLEGE CODERS

`<form onSubmit={handleSubmit}>`

Explanation:

- Submit calls function.

8) Preventing default form refresh

- Browser normally refreshes after submit.
- `preventDefault` stops that.

Example:

```
function handleSubmit(e){  
  e.preventDefault();  
}
```

Explanation:

- Form stays on same page.

9) Displaying submitted data (not while typing)

- Store submitted values separately.

Example:

```
setSavedData(formData);
```

Explanation:

- Display only after submit.

10) Resetting input values after form submit


- Clear fields after submit.

Example:

```
setFormData({  
  name:"",  
  email:"  
});
```

Explanation:

- Inputs become empty again.



COLLEGE CODERS

11) Conditional rendering after form submission

- Show output only after submit.

Example:

```
{savedData && <h2>{savedData.name}</h2>}
```

Explanation:

- Output appears only when data exists.

Mini Project – Student Registration Form

- Take name, email, and course.
- Display data only after submit.
- Reset form after submit.