

Congratulations! You passed!

Grade received 100%

Latest Submission Grade 100%

To pass 80% or higher

Go to next
item

1. What does `flow_from_directory` give you on the `ImageDataGenerator`?

1 / 1 point

- ☐ The ability to easily load images for training
- ☐ The ability to pick the size of training images
- ☐ The ability to automatically label images based on their directory name
- ☒ All of the above



Correct

That's right! The `flow_from_directory` method takes the path to a directory & generates batches of augmented data.

2. If my Image is sized 150x150, and I pass a 3x3 Convolution over it, what size is the resulting image?

1 / 1 point

- ☐ 153x153
- ☐ 450x450
- ☒ 148x148
- ☐ 150x150

✓ **Correct**

Nailed it! Applying a 3x3 convolution would result in a 148x148 image.

3. If my data is sized 150x150, and I use Pooling of size 2x2, what size will the resulting image be?

1 / 1 point

☐ 149x149

☐ 148x148

☐ 300x300

☒ 75x75

✓ **Correct**

Nailed it! Applying 2x2 pooling would result in a 75x75 image.

4. If I want to view the history of my training, how can I access it?

1 / 1 point

☒ Create a variable 'history' and assign it to the return of model.fit or model.fit_generator

☐ Pass the parameter 'history=true' to the model.fit

☐ Use a model.fit_generator

☐ Download the model and inspect it

✓ **Correct**

Exactly! The History.history attribute is a record of training loss values and metrics values at successive epochs.

5. What's the name of the API that allows you to inspect the impact of convolutions on the images?

1 / 1 point

☐ The model.convolution API

☐ The model.images API

☒ The model.layers API

☐ The model.pools API

☒ **Correct**

6. When exploring the graphs, the loss levelled out at about .75 after 2 epochs, but the accuracy climbed close to 1.0 after 15 epochs. What's the significance of this?

1 / 1 point

☐ There was no point training after 2 epochs, as we overfit to the validation data

☒ There was no point training after 2 epochs, as we overfit to the training data

☐ A bigger training set would give us better validation accuracy

☐ A bigger validation set would give us better training accuracy

☒ **Correct**

Correct! Those values indicate overfitting to the training data.

7. Why is the validation accuracy a better indicator of model performance than training accuracy?

1 / 1 point

☐ It isn't, they're equally valuable

- ☐ There's no relationship between them
- ☒ The validation accuracy is based on images that the model hasn't been trained with, and thus a better indicator of how the model will perform with new images.
- ☐ The validation dataset is smaller, and thus less accurate at measuring accuracy, so its performance isn't as important
- ☒ **Correct**

8. Why is overfitting more likely to occur on smaller datasets?

1 / 1 point

- ☐ Because in a smaller dataset, your validation data is more likely to look like your training data
- ☐ Because there isn't enough data to activate all the convolutions or neurons
- ☐ Because with less data, the training will take place more quickly, and some features may be missed
- ☒ Because there's less likelihood of all possible features being encountered in the training process.

- ☒ **Correct**
Undoubtedly! A smaller size decreases the likelihood that the model will recognize all possible features during training.