Scanner IMAP Auxiliary Modules a11y.text Scanner IMAP Auxiliary Modules imap_version a11y.text imap_version The imap_version auxiliary module is a relatively simple banner grabber for IMAP servers. msf > use auxiliary/scanner/imap/imap_version msf auxiliary(imap_version) > show options

Module options (auxiliary/scanner/imap/imap_version):

Name Current Setting Required Description		
IMAPPASS	no	The password for the specified username
IMAPUSER	no	The username to authenticate as
RHOSTS	yes	The target address range or CIDR identifier
RPORT 143	yes	The target port
THREADS 1	yes	The number of concurrent threads To configure the module, we
will only set the RHOSTS and THREADS values and let it run. Note that you can also pass		
credentials to the module. msf auxiliary(imap_version) > set RHOSTS 192.168.1.200-240		
RHOSTS => 192.168.1.200-240		
msf auxiliary(imap_version) > set THREADS 20		
THREADS => 20		
msf auxiliary(imap_version) > run		

- [*] 192.168.1.215:143 IMAP * OK [CAPABILITY IMAP4REV1 LOGIN-REFERRALS STARTTLS AUTH=LOGIN] [192.168.1.215] IMAP4rev1 2001.315rh at Sun, 23 Jan 2011 20:47:51 +0200 (IST)\x0d\x0a
- [*] Scanned 13 of 55 hosts (023% complete)
- [*] 192.168.1.224:143 IMAP * OK Dovecot ready.\x0d\x0a

- [*] 192.168.1.229:143 IMAP * OK IMAPrev1\x0d\x0a
- [*] Scanned 30 of 55 hosts (054% complete)
- [*] Scanned 31 of 55 hosts (056% complete)
- [*] Scanned 38 of 55 hosts (069% complete)
- [*] Scanned 39 of 55 hosts (070% complete)
- [*] Scanned 40 of 55 hosts (072% complete)
- [*] 192.168.1.234:143 IMAP * OK localhost Cyrus IMAP4 v2.3.2 server ready\x0d\x0a
- [*] Scanned 52 of 55 hosts (094% complete)
- [*] Scanned 53 of 55 hosts (096% complete)
- [*] Scanned 54 of 55 hosts (098% complete)
- [*] Scanned 55 of 55 hosts (100% complete)
- [*] Auxiliary module execution completed

msf auxiliary(imap_version) > Next Scanner NetBIOS Auxiliary Modules Prev Scanner MSSQL Auxiliary Modules